

The automultiplechoice package*

Alexis Bienvenue
paamc@passoire.fr

November 21, 2021

Abstract

This package helps designing multiple choice exams ready for automated marking from papers scans.

Answers and questions are optionally shuffled, creating different sheets for every student.

1 Introduction

The package `automultiplechoice` helps formatting multiple choice questionnaires with automated marking from papers scans in mind:

- The package can produce different copies of the question sheet for each student, optionally shuffling answers and questions for each student.
- Markers can be printed on each sheet, so as to be able to analyse scans after examination. All the needed information about the position of the markers and the boxes to be checked by the students is given in an auxiliary file during \LaTeX run.

See Auto Multiple Choice (AMC) software (<https://www.auto-multiple-choice.net/>) for an integration of this package, with user interface for automated marking.

2 Samples

We begin with several samples to see what can be done with the `automultiplechoice` package. All `automultiplechoice` commands and options will be detailed further.

For all these samples, two sets of questions are used: a group of geography questions, and a group of history questions. These are defined in a common \LaTeX file named `questions.tex`:

```
\element{geography}{  
  \begin{question}{Ghana}  
    What is the capital of Ghana?  
    \begin{choiceshoriz}  
      \correctchoice{Accra}  
      \wrongchoice{Addis Abeba}  
      \wrongchoice{Ankara}  
      \wrongchoice{Apia}
```

*This document corresponds to version revision: `r:d5fe5a59` from AMC 1.5.2

```

        \end{choiceshoriz}
    \end{question}
}

\element{geography}{
    \begin{question}{Thailand}
        What is the capital of Thailand?
        \begin{choiceshoriz}
            \correctchoice{Bangkok}
            \wrongchoice{Banjul}
            \wrongchoice{Beijing}
            \wrongchoice{Beirut}
            \wrongchoice{Berlin}
        \end{choiceshoriz}
    \end{question}
}

\element{geography}{
    \begin{question}{Egypt}
        What is the capital of Egypt?
        \begin{choices}
            \correctchoice{Cairo}
            \wrongchoice{Caracas}
            \wrongchoice{Cayenne}
            \wrongchoice{Chisinau}
            \wrongchoice{Conakry}
        \end{choices}
    \end{question}
}

\element{geography}{
    \begin{question}{Ireland}
        What is the capital of Ireland?
        \begin{multicols}{3}
            \begin{choices}
                \correctchoice{Dublin}
                \wrongchoice{Dili}
                \wrongchoice{Djibouti}
                \wrongchoice{Doha}
                \wrongchoice{Dakar}
                \wrongchoice{Dhaka}
            \end{choices}
        \end{multicols}
    \end{question}
}

\element{history}{
    \begin{questionmult}{1901}
        Which of the following events are taking place during the year

```

```

1901?
\begin{choices}
  \correctchoice{Funeral of Queen Victoria in London}
  \correctchoice{Official end of the Caste War of Yucat\'an}
  \wrongchoice{King George of Greece becomes absolute monarch of Crete}
  \wrongchoice{The first line of the Paris M\'etro is opened}
\end{choices}
\end{questionmult}
}

\element{history}{
  \begin{questionmult}{1850}
    Which of the following events are taking place during the year
    1850?
    \begin{choices}
      \correctchoice{American Express is founded by Henry Wells \& William Fargo}
      \wrongchoice{Napoleon Bonaparte crosses the Alps and invades Italy}
      \wrongchoice{Kwang-su becomes emperor of China}
      \wrongchoice{First horse-drawn omnibuses established in London}
    \end{choices}
  \end{questionmult}
}

\element{history}{
  \begin{questionmult}{1971}
    Which of the following events are taking place during the year
    1971?
    \begin{choices}
      \correctchoice{Apollo 14 lands on the Moon}
      \correctchoice{The Soviet Union launches Salyut 1}
      \correctchoice{Death of Louis Armstrong}
      \wrongchoice{The first commercial Concorde flight takes off}
    \end{choices}
  \end{questionmult}
}

```

We will ask automultiplechoice package to include two geography questions and two history questions at random for each student, shuffling questions and answers, with the following code:

```

\cleargroup{all}
\shufflegroup{geography}
\copygroup[2]{geography}{all}
\shufflegroup{history}
\copygroup[2]{history}{all}
\shufflegroup{all}
\insertgroup{all}

```

You can read these commands as “clear group **all**, shuffle questions inside group **geography** and copy the first two to group **all**, do the same for group **history**, shuffle the four questions copied into **all** and print them”.

2.1 Standard layout

A set of 30 students sheets can be produced from the following L^AT_EX source named `sample-amc.tex`:

```
\documentclass{article}
\usepackage{automultiplechoice}
\usepackage{multicol}
\begin{document}

\input{questions.tex}

\onecopy{30}{

\noindent{\bf AMC \hfill SAMPLE TEST}

\vspace{3ex}
```

For this test, package `{\sf automultiplechoice}` is used without any option. Page markers are printed in view of an automated marking from papers scans. DRAFT indications can be cancelled using `{\tt nowatermark}` option.

Commands from `{\sf automultiplechoice}` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

```
\vspace{3ex}

\cleargroup{all}

\shufflegroup{geography}
\copygroup[2]{geography}{all}
\shufflegroup{history}
\copygroup[2]{history}{all}
\shufflegroup{all}
\insertgroup{all}

}
\end{document}
```

producing a 30-pages document (every page has number 1), from which we show the first pages on page 7.

Note that “DRAFT” indications can be cancelled using option `nowatermark`, or using AMC software.

You can see on each page markers that can be used for automated completed answer sheets scans analysis:

- Four circles ● are printed in the corners, to be able to analyse any rotation or scaling of the scans.
- Binary boxes are printed in the header area, so as to be able to read student sheet number and page number. On page 2 for example, you can see that these binary boxes are coding 2/1/59:



+2/1/59+

Here, 2 is the student sheet number, 1 is the page number for this student, and 59 is a checking value that can be used for checking correct identification from a scan.

If you also use `calibration` option, `automultiplechoice` will produce a `.xy` file with informations about the exact position in the page of all the markers, and all the boxes. This option is automatically set by AMC software, which then use the information in the `.xy` file for automated marking.

2.2 Separate answer sheet

In some situations, you may need a separate answer sheet:

- this makes cheating even more difficult;
- this can reduce the number of pages to scan.

This is done using `separateanswersheet` option of `automultiplechoice` package. You also have to use commands `\AMCformBegin` to indicate the beginning of this separate answer sheet (usually after a `\clearpage` or `\AMCcleardoublepage` command), and `\AMCform` to insert the form to be completed by the students, as in the following example (`sample-separate.tex`):

```
\documentclass{article}
\usepackage[separateanswersheet]{automultiplechoice}
\usepackage{multicol}
\begin{document}
```

```
\input{questions.tex}
```

```
\onecopy{30}{
```

```
\noindent{\bf AMC \hfill SAMPLE TEST}
```

```
\vspace{3ex}
```

For this test, package `{\sf automultiplechoice}` is used with `{\tt separateanswersheet}` option, so that all answers are to be filled on a separate sheet by students. Page markers are printed in view of an automated marking from papers scans. DRAFT indications can be cancelled using `{\tt nowatermark}` option.

Commands from `{\sf automultiplechoice}` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

```
\vspace{3ex}
```

```
\cleargroup{all}
```

```

\shufflegroup{geography}
\copygroup[2]{geography}{all}
\shufflegroup{history}
\copygroup[2]{history}{all}
\shufflegroup{all}
\insertgroup{all}

```

```

\clearpage

```

```

\AMCformBegin

```

This is the answer sheet: all answers are to be ticked on this page to be taken into account.

```

\vspace{2ex}

```

```

\AMCform

```

```

}
\end{document}

```

First pages of the result are shown on page 8. There are now 2 pages per student: the first with questions, and the second for answers. Only the second will be completed by the students, and scanned for analysis.

2.3 Without markers

With the `nopage` option, package `automultiplechoice` does not include any page markers for scan processing. I'm afraid you can't use any automated marking software with this layout, but you can still use answer sheet and corrected answer sheet (option `indivanswers`, added here) for a manual marking...

The \LaTeX source `sample-plain.tex` that only differs from `sample-amc.tex` by its options passed to `automultiplechoice`:

```

\usepackage[nopage,indivanswers]{automultiplechoice}

```

produces a 30-pages document, from which we show the first pages on page 9.

First pages from L^AT_EX source detailed in section 2.1 – see sample-amc.pdf

●  ● +1/1/60+

AMC SAMPLE TEST

For this test, package `automultiplechoice` is used without any option. Page markers are printed in view of an automated marking from papers scans. DRAFT indications can be cancelled using `\nocancelmark` option.

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 Which of the following events are taking place during the year 1971?

☐ The Soviet Union launches Salyut 1
☐ The first commercial Concorde flight takes off
☐ Death of Louis Armstrong
☐ Apollo 14 lands on the Moon

Question 2 What is the capital of Egypt?

☐ Cayenne
☐ Caracas
☐ Cuito
☐ Conakry
☐ Chisinau

Question 3 Which of the following events are taking place during the year 1850?

☐ Napoleon Bonaparte crosses the Alps and invades Italy
☐ First horse-drawn omnibuses established in London
☐ American Express is founded by Henry Wells & William Fargo
☐ Kwang-on becomes emperor of China

Question 4 What is the capital of Ghana?

☐ Accra ☐ Addis Ababa ☐ Ankara ☐ Apia

● For your examination, preferably print documents compiled from `automultiple-choice`. ●

●  ● +2/1/60+

AMC SAMPLE TEST

For this test, package `automultiplechoice` is used without any option. Page markers are printed in view of an automated marking from papers scans. DRAFT indications can be cancelled using `\nocancelmark` option.

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 Which of the following events are taking place during the year 1901?

☐ The first line of the Paris Metro is opened
☐ Official end of the Caste War of Yucatán
☐ King George of Greece becomes absolute monarch of Creta
☐ Funeral of Queen Victoria in London

Question 2 What is the capital of Ireland?

☐ Djibouti ☐ Dhaka ☐ Dhaka
☐ Dili ☐ Dili ☐ Dakar

Question 3 What is the capital of Ghana?

☐ Apia ☐ Accra ☐ Addis Ababa ☐ Ankara

Question 4 Which of the following events are taking place during the year 1850?

☐ Napoleon Bonaparte crosses the Alps and invades Italy
☐ First horse-drawn omnibuses established in London
☐ American Express is founded by Henry Wells & William Fargo
☐ Kwang-on becomes emperor of China

● For your examination, preferably print documents compiled from `automultiple-choice`. ●

●  ● +3/1/52+

AMC SAMPLE TEST

For this test, package `automultiplechoice` is used without any option. Page markers are printed in view of an automated marking from papers scans. DRAFT indications can be cancelled using `\nocancelmark` option.

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 Which of the following events are taking place during the year 1971?

☐ The Soviet Union launches Salyut 1
☐ The first commercial Concorde flight takes off
☐ Apollo 14 lands on the Moon
☐ The Soviet Union launches Salyut 1
☐ Death of Louis Armstrong

Question 2 Which of the following events are taking place during the year 1850?

☐ First horse-drawn omnibuses established in London
☐ Kwang-on becomes emperor of China
☐ Napoleon Bonaparte crosses the Alps and invades Italy
☐ American Express is founded by Henry Wells & William Fargo

Question 3 What is the capital of Ireland?

☐ Dhaka ☐ Dhaka ☐ Dakar
☐ Dili ☐ Dili ☐ Djibouti

Question 4 What is the capital of Thailand?

☐ Beijing ☐ Bangkok ☐ Bangkok ☐ Beirut ☐ Berlin

● For your examination, preferably print documents compiled from `automultiple-choice`. ●

●  ● +4/1/52+

AMC SAMPLE TEST

For this test, package `automultiplechoice` is used without any option. Page markers are printed in view of an automated marking from papers scans. DRAFT indications can be cancelled using `\nocancelmark` option.

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 Which of the following events are taking place during the year 1971?

☐ The Soviet Union launches Salyut 1
☐ Apollo 14 lands on the Moon
☐ Death of Louis Armstrong
☐ The first commercial Concorde flight takes off

Question 2 What is the capital of Egypt?

☐ Caracas
☐ Cayenne
☐ Cuito
☐ Conakry
☐ Chisinau

Question 3 Which of the following events are taking place during the year 1850?

☐ American Express is founded by Henry Wells & William Fargo
☐ Napoleon Bonaparte crosses the Alps and invades Italy
☐ First horse-drawn omnibuses established in London
☐ Kwang-on becomes emperor of China

Question 4 What is the capital of Ireland?

☐ Djibouti ☐ Dhaka ☐ Dakar
☐ Dili ☐ Dili ☐ Dublin

● For your examination, preferably print documents compiled from `automultiple-choice`. ●

First pages from L^AT_EX source detailed in section 2.2 – see sample-separate.pdf

•  • +1/1/60+

AMC SAMPLE TEST

For this test, package `automultiplechoice` is used with `separateanswersheet` option, so that all answers are to be filled on a separate sheet by students. Page markers are printed in view of an automated marking from papers scans. DRAFT indications can be cancelled using `nowatermark` option.

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 Which of the following events are taking place during the year 1971?

☐ A The Soviet Union launches Salyut 1
☐ B The first commercial Concorde flight takes off
☐ C Death of Louis Armstrong
☐ D Apollo 14 lands on the Moon

Question 2 What is the capital of Egypt?

☐ A Cayenne
☐ B Caracas
☐ C Cairo
☐ D Cusack
☐ E Chisum

Question 3 Which of the following events are taking place during the year 1850?

☐ A Napoleon Bonaparte crosses the Alps and invades Italy
☐ B First horse-drawn omnibuses established in London
☐ C American Express is founded by Henry Wells & William Fargo
☐ D Kwang-on becomes emperor of China

Question 4 What is the capital of Ghana?

☐ A Accra ☐ B Addis Ababa ☐ C Ankara ☐ D Apia

• For your examination, preferably print documents compiled from `automultiple-choice`. •

•  • +1/2/60+

This is the answer sheet: all answers are to be ticked on this page to be taken into account.

Question 1: ☐ A ☐ B ☐ C ☐ D
Question 2: ☐ A ☐ B ☐ C ☐ D
Question 3: ☐ A ☐ B ☐ C ☐ D
Question 4: ☐ A ☐ B ☐ C ☐ D

• For your examination, preferably print documents compiled from `automultiple-choice`. •

•  • +2/1/60+

AMC SAMPLE TEST

For this test, package `automultiplechoice` is used with `separateanswersheet` option, so that all answers are to be filled on a separate sheet by students. Page markers are printed in view of an automated marking from papers scans. DRAFT indications can be cancelled using `nowatermark` option.

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 Which of the following events are taking place during the year 1901?

☐ A The first line of the Paris Metro is opened
☐ B Official end of the Cato War of Yunan
☐ C King George of Greece becomes absolute monarch of Crete
☐ D Funeral of Queen Victoria in London

Question 2 What is the capital of Ireland?

☐ A Djibouti ☐ B Dhaka ☐ C Doha
☐ D Dublin ☐ E Dili ☐ F Dakar

Question 3 What is the capital of Ghana?

☐ A Apia ☐ B Accra ☐ C Addis Ababa ☐ D Ankara

Question 4 Which of the following events are taking place during the year 1850?

☐ A Napoleon Bonaparte crosses the Alps and invades Italy
☐ B First horse-drawn omnibuses established in London
☐ C American Express is founded by Henry Wells & William Fargo
☐ D Kwang-on becomes emperor of China

• For your examination, preferably print documents compiled from `automultiple-choice`. •

•  • +2/2/60+

This is the answer sheet: all answers are to be ticked on this page to be taken into account.

Question 1: ☐ A ☐ B ☐ C ☐ D
Question 2: ☐ A ☐ B ☐ C ☐ D
Question 3: ☐ A ☐ B ☐ C ☐ D
Question 4: ☐ A ☐ B ☐ C ☐ D

• For your examination, preferably print documents compiled from `automultiple-choice`. •

First pages from L^AT_EX source detailed in section 2.3 – see sample-plain.pdf

AMC

SAMPLE TEST

For this test, package `automultiplechoice` is used with the following options:

- `nopage`, so that no page markers are printed: nothing is planned for future automated marking from papers scans.
- `indivanswers`, so that correct answers are indicated (this is the corrected answer sheet. Without this option, you get the question sheet).

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 Which of the following events are taking place during the year 1971?

☒ The Soviet Union launches Soyuz 1
☐ The first commercial Concorde flight takes off
☐ Death of Louis Armstrong
☒ Apollo 14 lands on the Moon

Question 2 What is the capital of Egypt?

☐ Cayenne
☐ Caracas
☒ Cairo
☐ Cusquey
☐ Chisinau

Question 3 Which of the following events are taking place during the year 1850?

☐ Napoleon Bonaparte crosses the Alps and invades Italy
☐ First horse-drawn omnibuses established in London
☒ American Express is founded by Henry Wells & William Fargo
☐ Kwang-sun becomes emperor of China

Question 4 What is the capital of Ghana?

☒ Accra ☐ Addis Ababa ☐ Ankara ☐ Apia

1

AMC

SAMPLE TEST

For this test, package `automultiplechoice` is used with the following options:

- `nopage`, so that no page markers are printed: nothing is planned for future automated marking from papers scans.
- `indivanswers`, so that correct answers are indicated (this is the corrected answer sheet. Without this option, you get the question sheet).

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 Which of the following events are taking place during the year 1901?

☐ The first line of the Paris Metro is opened
☒ Official end of the Cretan War of Vassilakis
☐ King George of Greece becomes absolute monarch of Crete
☒ Funeral of Queen Victoria in London

Question 2 What is the capital of Ireland?

☐ Djibouti ☐ Dhaka ☐ Doha
☒ Dublin ☐ Dili ☐ Dakar

Question 3 What is the capital of Ghana?

☐ Apia ☒ Accra ☐ Addis Ababa ☐ Ankara

Question 4 Which of the following events are taking place during the year 1850?

☐ Napoleon Bonaparte crosses the Alps and invades Italy
☐ First horse-drawn omnibuses established in London
☒ American Express is founded by Henry Wells & William Fargo
☐ Kwang-sun becomes emperor of China

1

AMC

SAMPLE TEST

For this test, package `automultiplechoice` is used with the following options:

- `nopage`, so that no page markers are printed: nothing is planned for future automated marking from papers scans.
- `indivanswers`, so that correct answers are indicated (this is the corrected answer sheet. Without this option, you get the question sheet).

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 Which of the following events are taking place during the year 1971?

☐ The first commercial Concorde flight takes off
☒ Apollo 14 lands on the Moon
☒ The Soviet Union launches Soyuz 1
☒ Death of Louis Armstrong

Question 2 Which of the following events are taking place during the year 1850?

☐ First horse-drawn omnibuses established in London
☐ Kwang-sun becomes emperor of China
☐ Napoleon Bonaparte crosses the Alps and invades Italy
☒ American Express is founded by Henry Wells & William Fargo

Question 3 What is the capital of Ireland?

☐ Dhaka ☐ Doha ☐ Dakar
☐ Dili ☒ Dublin ☐ Djibouti

Question 4 What is the capital of Thailand?

☐ Beijing ☐ Banjul ☒ Bangkok ☐ Beirut ☐ Berlin

1

AMC

SAMPLE TEST

For this test, package `automultiplechoice` is used with the following options:

- `nopage`, so that no page markers are printed: nothing is planned for future automated marking from papers scans.
- `indivanswers`, so that correct answers are indicated (this is the corrected answer sheet. Without this option, you get the question sheet).

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 Which of the following events are taking place during the year 1971?

☒ The Soviet Union launches Soyuz 1
☒ Apollo 14 lands on the Moon
☒ Death of Louis Armstrong
☐ The first commercial Concorde flight takes off

Question 2 What is the capital of Egypt?

☐ Caracas
☐ Cayenne
☒ Cairo
☐ Cusquey
☐ Chisinau

Question 3 Which of the following events are taking place during the year 1850?

☒ American Express is founded by Henry Wells & William Fargo
☐ Napoleon Bonaparte crosses the Alps and invades Italy
☐ First horse-drawn omnibuses established in London
☐ Kwang-sun becomes emperor of China

Question 4 What is the capital of Ireland?

☐ Djibouti ☐ Dhaka ☐ Dakar
☐ Dili ☐ Doha ☒ Dublin

1

3 Usage

3.1 Package options

The following options are available for package `automultiplechoice`:

`noshuffle` cancels answers shuffling for all questions.

`noshufflegroups` cancels groups shuffling.

`answers` produces a common corrected answers sheet.

`indivanswers` shows the boxes that corresponds to correct choices on the question sheet.

`box` includes every question in a \LaTeX box, so that they can't be cutted on two different pages.

`asbox` does the same for questions in the separate answer sheet.

`separateanswersheet` asks for a separate answer sheet (see section 2.2 for an example). Commands `\AMCformBegin` and `\AMCform` must be used to describe the separate answer sheet (see section 3.6).

`digits` puts digits instead of letters in the boxes, when `separateanswersheet` (or `insidebox`) is used.

`outsidebox` prints boxes labels outside the boxes on the answersheet when `separateanswersheet` is set.

`init` initializes the random generator from time. *This option is only for testing: don't use it for a real exam!*

`completemulti` adds an answer "None of these answers are correct." at the end of each multiple question (question with no, one or several correct answers), so as to make the difference between "I don't know" and "I think none of the answers are correct".

`insidebox` puts a letter (or a digit if `digits` option is used) inside the boxes, even if `separateanswersheet` is not used. The `insidebox` option is implicitly called when using `separateanswersheet`: no need to call it then.

`calibration` asks for logging positions of boxes and markers in the `.xy` file. Without this option, a \LaTeX run updates the document but not the `.xy` file.

`nowatermark` cancels the "DRAFT" indications above pages.

`catalog` is used for formatting a catalog of questions, not an exam. Then the question identifiers will be printed.

`keys` defines the way the question identifiers will be printed on the catalog file. With `keys=next` (the default), the question identifiers will be printed next to the questions numbers. With `keys=line`, the question identifiers will be printed on one line before the question text, so that the question will look close to the final result on the exam copies.

`francais` asks for french localisation.

`lang=XX` asks for localisation in XX language. At present, only CA (Catalan), DE (German), ES (Spanish), FR (French), IT (Italian), JA (Japanese), NO (Norwegian) and NL (Dutch) are available.

`plain` cancels `environ` and `etex` automatic loading. The default behaviour is to load `environ` and `etex` packages if available, as they improve `automultiplechoice`. This is not done when `plain` option is set.

`nopage` cancels markers print and page layout definition (see sample in section 2.3).

`automarks` , when used with `separateanswersheet`, cancels markers print on the subject page (they are only shown on the answer sheet pages).

`postcorrect` tells that correct answers won't be given in the LaTeX source. The teacher will fill one answer sheet for AMC to analyse the scan and set correct answers from it.

`fullgroups` cancels the use of the optional parameter of `\insertgroup` and `\copygroup`, so that each group is always fully inserted and fully copied.

`storebox` asks to use `\storebox` instead of `\savebox` to handle ovals (when using oval shape). The package `storebox` will be loaded.

`pdfform` use this option to produce PDF forms. The PDF sheet won't be printed, but filled by each student with a PDF reader. The completed PDF will then be sent to the teacher, and given to AMC for data capture.

See also section 3.8 for a french version of some of these options.

3.2 Questions and answers

We make a difference between two kind of multiple choice questions:

- **Simple questions:** there is one and only one correct choices among the proposed choices, *and this is announced to the student*. Thus, the student is asked to check one answer if he thinks this is the good one, and to check none if he has no idea.
- **Multiple questions:** there can be zero, one or several correct choices among the proposed choices. This is also announced to the student (using the `\multiSymbole` sign, with default ♣), so that the student is asked to check all the boxes corresponding to correct choices, and to let unchecked all boxes corresponding to wrong choices.

`question (env.)` Simple questions are enclosed in a `{question}{<id>}` environment, and multiple questions `questionmult (env.)` are enclosed in a `{questionmult}{<id>}` environment. These environments contain the question text, and the proposed choices inside a `choices`-like environment (see next). The `<id>` argument is a question identifier. Each question must have a unique identifier, different from the other questions identifiers.

Questions environments

Question 1 What is the elevation of Mount Everest?

- ☐ 8,253 m
☐ 8,810 m
☐ 8,848 m

Question 2 ♣ Which contries are in the Americas?

- ☐ Cambodia
☐ Guatemala
☐ Canada
☐ Switzerland

```
\begin{question}{everest}
  What is the elevation of
  Mount Everest?
  \begin{choices}
    \correctchoice{8,848\,m}
    \wrongchoice{8,253\,m}
    \wrongchoice{8,810\,m}
  \end{choices}
\end{question}

\begin{questionmult}{americas}
  Which contries are in the Americas?
  \begin{choices}
    \correctchoice{Guatemala}
    \correctchoice{Canada}
    \wrongchoice{Switzerland}
    \wrongchoice{Cambodia}
  \end{choices}
\end{questionmult}
```

`\AMCcompleteMulti` For multiple questions, it is sometimes useful to make the difference between a student who thinks that none of he choices are correct, and a student who did not answer the question. `\AMCnoCompleteMulti` The use of package option `completemulti` can be used in this case: it adds a choice to all multiple questions. Commands `\AMCcompleteMulti` and `\AMCnoCompleteMulti` can also be used to change this behaviour for a single question.

Additional answer “none” for a single question

Question 3 ♣ Which contries are in the Americas?

- ☐ Guatemala
☐ Cambodia
☐ Canada
☐ Switzerland
☐ *None of these answers are correct.*

```
\begin{questionmult}{americas}
  \AMCcompleteMulti
  Which contries are in the Americas?
  \begin{choices}
    \correctchoice{Guatemala}
    \correctchoice{Canada}
    \wrongchoice{Switzerland}
    \wrongchoice{Cambodia}
  \end{choices}
\end{questionmult}
```

`choices` (*env.*)
`choiceshoriz` (*env.*)
`choicescustom` (*env.*)

Depending on the formatting style for answers, one can choose one of the following ones:

- Environment `choices` is usually chosen for long answers:

The `choices` environment

Question 4 ♣ What are the possible uses of latex?

- ☐ Latex is used as a fuel for some space launch vehicles.
- ☐ Latex from the chicle and jelutong trees is used in chewing gum.
- ☐ Natural rubber is the most important product obtained from latex.

```
\begin{questionmult}{latex}
What are the possible uses of latex?
\begin{choices}
\correctchoice{Natural rubber is
the most important product
obtained from latex.}
\correctchoice{Latex from the chicle
and jelutong trees is used in
chewing gum.}
\wrongchoice{Latex is used as a fuel
for some space launch vehicles.}
\end{choices}
\end{questionmult}
```

- environment `choiceshoriz` is chosen for short answers:

The `choiceshoriz` environment

Question 5 How many legs for an insect?

- ☐ 2 ☐ 6 ☐ 8

```
\begin{question}{insect}
How many legs for an insect?
\begin{choiceshoriz}
\correctchoice{6}
\wrongchoice{2}
\wrongchoice{8}
\end{choiceshoriz}
\end{question}
```

- environment `choicescustom` is provided to customize answers formatting. See 3.9.3 for details.

`\correctchoice` As you have seen in these examples, the `choices`-like environments contain `\correctchoice{<text>}` and `\wrongchoice` and `\wrongchoice{<text>}` commands, with the text of the proposed choice as argument.

3.3 Scoring

`\scoring` Scoring strategies can be given in the L^AT_EX source. They don't have any impact on the question sheet: they are only transmitted to the analysis software through the `.amc` file. See AMC `\scoringDefaultM` documentation to write proper commands for your needs. `\scoring{<score>}` can be used inside a `\question` or `questionmult` environment to describe the scoring strategy for the question, or after a `\correctchoice` or `\wrongchoice` command to describe score associated to a particular choice. `\scoringDefaultM{<score>}` and `\scoringDefaultS{<score>}` define default scoring strategies for multiple and simple questions. `\QuestionIndicative` tags a question that is not taken into account to compute the mark – for example, it can be used for a question about the way students have enjoyed the course.

3.4 Groups of questions

Several commands are available that allows shuffling questions for each question sheet. They handle groups of questions. These groups will usually contain questions, but can be made of any L^AT_EX content.

\element The command `\element{<groupname>}{<content>}` adds element with content `<content>` to the group named `<groupname>`. The command `\shufflegroup{<groupname>}` shuffles elements of group named `<groupname>`. The command `\insertgroup[<n>]{<groupname>}` inserts elements of group `<groupname>` one after one. If optional parameter `<n>` is given, only the first `<n>` elements of the group are inserted in the document. The command `\insertgroupfrom[<n>]{<groupname>}{<i>}` does the same, starting from element at index `<i>` (the first element has index 0).

As an example without questions in groups elements, let us create a small group named **serie**, containing five elements, and play with it:

Managing groups	
Numbers: one two three four five. Three numbers from the second (index=1) one: two three four. Two of them after shuffling: two four.	<pre> \element{serie}{ one} \element{serie}{ two} \element{serie}{ three} \element{serie}{ four} \element{serie}{ five} Numbers:\insertgroup{serie}. Three numbers from the second (index=1) one:\insertgroupfrom[3]{serie}{1}. \shufflegroup{serie} Two of them after shuffling:\insertgroup[2]{serie}. </pre>

\cleargroup The command `\cleargroup{<groupname>}` clears all the elements of group `<groupname>`, making an empty group. The command `\copygroup[<n>]{<from>}{<to>}` copies the elements of group `<from>` to group `<to>` – if optional parameter `<n>` is given, only the `<n>` first elements are copied. The command `\copygroupfrom[<n>]{<from>}{<to>}{<i>}` does the same, starting from element at index `<i>` (the first element has index 0).

As an example again without questions:

Three digits from 2 to 4 and two letters: A 2 3 F 4.

Three digits and two letters: 2 8 4 E D.

Three digits and two letters: 4 E 2 5 A.

```
\element{digits}{ 1}\element{digits}{ 2}\element{digits}{ 3}
\element{digits}{ 4}\element{digits}{ 5}\element{digits}{ 6}
\element{digits}{ 7}\element{digits}{ 8}\element{digits}{ 9}
\element{letters}{ A}\element{letters}{ B}\element{letters}{ C}
\element{letters}{ D}\element{letters}{ E}\element{letters}{ F}

\shufflegroup{letters}
\cleargroup{mixed}
\copygroupfrom[3]{digits}{mixed}{1}\copygroup[2]{letters}{mixed}
\shufflegroup{mixed}
Three digits from 2 to 4 and two letters:\insertgroup{mixed}.

\shufflegroup{digits}\shufflegroup{letters}
\cleargroup{mixed}
\copygroup[3]{digits}{mixed}\copygroup[2]{letters}{mixed}
\shufflegroup{mixed}
Three digits and two letters:\insertgroup{mixed}.

\shufflegroup{digits}\shufflegroup{letters}
\cleargroup{mixed}
\copygroup[3]{digits}{mixed}\copygroup[2]{letters}{mixed}
\shufflegroup{mixed}
Three digits and two letters:\insertgroup{mixed}.
```

You can find an example involving questions in section [2](#).

3.5 Students identification

`\namefield` There are two ways to associate students to their sheets.

- Always add to one page of each copy some place for the student to write down his name. If you want AMC software to be able to cut the scan around this area to present it to you and ask you to read the written name (this is called manual association), you must use the `\namefield{<descr>}` command. The `<descr>` argument contains the \LaTeX code used to format the name field on the page. For example:

The name field

Name and surname:

.....

```
\namefield{\fbox{
  \begin{minipage}{15em}
    Name and surname:\vspace*{3ex}\par
    \noindent\dotfill\vspace{2mm}
  \end{minipage}
}}
```

You can see that the `\namefield` command has no effect on the produced document. In fact, its only purpose is to log in the `.xy` file information about the position of the name field on the page, to be used by the software analysing the scans.

- For automated student identification, if for example students have a 6-digits student number, you can ask them to code it somewhere on the question sheet. This can be done using the `\AMCcodeGridInt[⟨opts⟩]{⟨key⟩}{⟨ndigits⟩}` command, where `⟨key⟩` is the key identifier, that can be used to retrieve coded student numbers from the scans, and `⟨ndigits⟩` is the number of digits for numbers to be coded.

Student ID											
<input type="checkbox"/> 0	<input type="checkbox"/> 0	<input type="checkbox"/> 0	<input type="checkbox"/> 0	<input type="checkbox"/> 0	<input type="checkbox"/> 0	<input type="checkbox"/> 0	<code>\AMCcodeGridInt{student}{6}</code>				
<input type="checkbox"/> 1	<input type="checkbox"/> 1	<input type="checkbox"/> 1	<input type="checkbox"/> 1	<input type="checkbox"/> 1	<input type="checkbox"/> 1	<input type="checkbox"/> 1					
<input type="checkbox"/> 2	<input type="checkbox"/> 2	<input type="checkbox"/> 2	<input type="checkbox"/> 2	<input type="checkbox"/> 2	<input type="checkbox"/> 2	<input type="checkbox"/> 2					
<input type="checkbox"/> 3	<input type="checkbox"/> 3	<input type="checkbox"/> 3	<input type="checkbox"/> 3	<input type="checkbox"/> 3	<input type="checkbox"/> 3	<input type="checkbox"/> 3					
<input type="checkbox"/> 4	<input type="checkbox"/> 4	<input type="checkbox"/> 4	<input type="checkbox"/> 4	<input type="checkbox"/> 4	<input type="checkbox"/> 4	<input type="checkbox"/> 4					
<input type="checkbox"/> 5	<input type="checkbox"/> 5	<input type="checkbox"/> 5	<input type="checkbox"/> 5	<input type="checkbox"/> 5	<input type="checkbox"/> 5	<input type="checkbox"/> 5					
<input type="checkbox"/> 6	<input type="checkbox"/> 6	<input type="checkbox"/> 6	<input type="checkbox"/> 6	<input type="checkbox"/> 6	<input type="checkbox"/> 6	<input type="checkbox"/> 6					
<input type="checkbox"/> 7	<input type="checkbox"/> 7	<input type="checkbox"/> 7	<input type="checkbox"/> 7	<input type="checkbox"/> 7	<input type="checkbox"/> 7	<input type="checkbox"/> 7					
<input type="checkbox"/> 8	<input type="checkbox"/> 8	<input type="checkbox"/> 8	<input type="checkbox"/> 8	<input type="checkbox"/> 8	<input type="checkbox"/> 8	<input type="checkbox"/> 8					
<input type="checkbox"/> 9	<input type="checkbox"/> 9	<input type="checkbox"/> 9	<input type="checkbox"/> 9	<input type="checkbox"/> 9	<input type="checkbox"/> 9	<input type="checkbox"/> 9					

For smaller number of digits, the “horizontal” form can be preferred:

Student ID, horizontal form											
<input type="checkbox"/> 0	<input type="checkbox"/> 1	<input type="checkbox"/> 2	<input type="checkbox"/> 3	<input type="checkbox"/> 4	<input type="checkbox"/> 5	<input type="checkbox"/> 6	<input type="checkbox"/> 7	<input type="checkbox"/> 8	<input type="checkbox"/> 9		
<input type="checkbox"/> 0	<input type="checkbox"/> 1	<input type="checkbox"/> 2	<input type="checkbox"/> 3	<input type="checkbox"/> 4	<input type="checkbox"/> 5	<input type="checkbox"/> 6	<input type="checkbox"/> 7	<input type="checkbox"/> 8	<input type="checkbox"/> 9		
<input type="checkbox"/> 0	<input type="checkbox"/> 1	<input type="checkbox"/> 2	<input type="checkbox"/> 3	<input type="checkbox"/> 4	<input type="checkbox"/> 5	<input type="checkbox"/> 6	<input type="checkbox"/> 7	<input type="checkbox"/> 8	<input type="checkbox"/> 9		

`\AMCcodeGridInt[h]{student}{3}`

3.6 Separate answer sheet

`\AMCformBegin` To produce separate answer sheets as seen in section 2.2,

`\AMCform`

`\AMCcleardoublepage`

1. use the `separateanswersheet` package option.
2. use the `\AMCformBegin` command at the beginning of the answer sheet description. This command usually follows a command to get a new page. This command can be the classical `\clearpage` for single-sided question sheets, or the `\AMCcleardoublepage` command, that

go to the next odd numbered page, so that the answer sheet is on a separate sheet even when printing in duplex mode.

3. use the `\AMCform` command to insert all boxes for all questions.

See section 2.2 for an example.

3.7 Random computation questions

One can use the \LaTeX package `fp` to make random computation questions, as can be seen in the following example (don't forget to load package `fp`):

Random computation questions

Question 6 How much are 2 plus 8?

☐ 9 ☒ 10 ☐ 16 ☐ -6

```

\begin{question}{\simplesum}
  \FPeval\VQa{trunc(1+random*8,0)}
  \FPeval\VQb{trunc(4+random*5,0)}
  \FPeval\VQsum{clip(VQa+VQb)}
  \FPeval\VQnoA{clip(VQa+VQb-1)}
  \FPeval\VQnoB{clip(VQa*VQb)}
  \FPeval\VQnoC{clip(VQa-VQb)}
  How much are \VQa{} plus \VQb{}?
  \begin{choiceshoriz}
    \correctchoice{\VQsum}
    \wrongchoice{\VQnoA}
    \wrongchoice{\VQnoB}
    \wrongchoice{\VQnoC}
  \end{choiceshoriz}
\end{question}
    
```

In this example, `\VQa` and `\VQb` are used to store two random integers (the first between 1 and 8, and the second between 4 and 8). Then `\VQsum` stores the sum of these two integers, and `\VQnoA`, `\VQnoB` and `\VQnoC` are other values that will be used as distractors in the multiple choice question.

\AMCIntervals In some cases, command `\AMCIntervals{\langle x \rangle}{\langle x0 \rangle}{\langle x1 \rangle}{\langle \delta \rangle}` from `automultiplechoice` can be useful. It adds a sequence of choices made of intervals $[x_i, x_i + \delta[$ of length $\langle \delta \rangle$ covering the interval $[\langle x0 \rangle, \langle x1 \rangle[$, using `\correctchoice` when $\langle x \rangle$ lies in the interval, and `\wrongchoice` otherwise.

Pick the right interval

Question 7 Let X and Y be two independent random variables, following exponential laws with respective parameters 5 and 8. In which interval lies the probability $P[X < Y]$?

- | | | | | |
|-------------------------------------|--|-------------------------------------|-------------------------------------|-------------------------------------|
| <input type="checkbox"/> [0, 0.1[| <input type="checkbox"/> [0.2, 0.3[| <input type="checkbox"/> [0.4, 0.5[| <input type="checkbox"/> [0.6, 0.7[| <input type="checkbox"/> [0.8, 0.9[|
| <input type="checkbox"/> [0.1, 0.2[| <input checked="" type="checkbox"/> [0.3, 0.4[| <input type="checkbox"/> [0.5, 0.6[| <input type="checkbox"/> [0.7, 0.8[| <input type="checkbox"/> [0.9, 1[|

```
\begin{question}{inf-expo-indep}
  \FPeval\VQa{trunc(2 + random * 4,0)}
  \FPeval\VQb{trunc(6 + random * 5,0)}
  \FPeval\VQr{VQa/(VQa+VQb)}
  Let  $X$  and  $Y$  be two independent random variables, following
  exponential laws with respective parameters  $\VQa$  and  $\VQb$ .
  In which interval lies the probability  $\text{P}[X < Y]$ ?
  \begin{multicols}{5}
    \begin{choices}[o]
      \AMCIntervals{\VQr}{0}{1}{0.1}
    \end{choices}
  \end{multicols}
\end{question}
```

`\AMCnumericChoices` One can also use the `\AMCnumericChoices` command to ask the student to enter a numerical value as his answer, as in the following example:

Numeric choices

Question 8

Compute $\sqrt{11}$ and round it with two digits after period.

	<input type="checkbox"/> 0	<input type="checkbox"/> 1	<input type="checkbox"/> 2	<input checked="" type="checkbox"/> 3	<input type="checkbox"/> 4	<input type="checkbox"/> 5	<input type="checkbox"/> 6	<input type="checkbox"/> 7	<input type="checkbox"/> 8	<input type="checkbox"/> 9
	.									
<input checked="" type="checkbox"/> +	<input type="checkbox"/> 0	<input type="checkbox"/> 1	<input type="checkbox"/> 2	<input checked="" type="checkbox"/> 3	<input type="checkbox"/> 4	<input type="checkbox"/> 5	<input type="checkbox"/> 6	<input type="checkbox"/> 7	<input type="checkbox"/> 8	<input type="checkbox"/> 9
<input type="checkbox"/> -	<input type="checkbox"/> 0	<input type="checkbox"/> 1	<input checked="" type="checkbox"/> 2	<input type="checkbox"/> 3	<input type="checkbox"/> 4	<input type="checkbox"/> 5	<input type="checkbox"/> 6	<input type="checkbox"/> 7	<input type="checkbox"/> 8	<input type="checkbox"/> 9

```
\begin{questionmultx}{sqrt}
  \FPeval\VQa{trunc(5+random*15,0)}
  \FPeval\VQs{VQa^0.5}

  Compute  $\sqrt{\VQa}$  and round it with two digits after period.

  \AMCnumericChoices{\VQs}{digits=3,decimals=2,sign=true,
    borderwidth=0pt,backgroundcol=lightgray,approx=5}
\end{questionmultx}
```

Note the use of `questionmultx` environment: we need this question to be *multiple* as several boxes has to be ticked, but we can't say that *several answers are correct*, so we don't show the ♣.

Available options that can be used in the second argument of the `\AMCnumericChoices` command are the following (`\bool` can be `true` or `false`, and `\color` must be a color known by the `xcolor` package):

`digits=\num` gives the number of digits to request (defaults to 3).

`decimals=\num` gives the number of digits after period to request (defaults to 0). Note that when `decimals` is positive, the LaTeX package `fp` must be loaded.

`base=\num` gives the base for digits and decimals (defaults to 10).

`significant=\bool` if `true`, the numbers to code are the first *significant* digits from the first argument of `\AMCnumericChoices`. For example, the right answer to `\AMCnumericChoices{56945.23}{digits=2,significant=true}` is 57.

`exponent=\num` gives the number of digits for the exponent, when requesting to enter the result in scientific notation.

`nozero=\bool` if `true`, the choice 0 is removed for all digits. May be useful when `\AMCnumericChoices` is used to get a small (< 10) positive value.

`sign=\bool` requests (or not) a signed value (default to `true`).

`exposign=\bool` requests (or not) a signed value of the exponent (default to `true`).

`strict=\bool` if `true`, a box has to be ticked for every digit and for the sign. If `false`, if some digits has no ticked box, they will be set to zero. Defaults to `false`.

`vertical=\bool` if `true`, each digit is represented on one raw. If `false` (default), each digit is represented on one line.

`expovertical=\bool` if `true`, the mantissa is above the exponent. If `false` (default), the mantissa is beside the exponent.

`reverse=\bool` if `true`, place higher values of the digits on the top in vertical mode (defaults to `true`).

`vhead=\bool` if `true`, in vertical mode, a header is placed over all digits rows, made using the command `\AMCncontextVHead` that is originally defined as `\def\AMCncontextVHead#1{\emph{b#1}}`. This default value is useful to number the binary digits. Default value is `false`.

`hspace=\space` sets the horizontal space between boxes (defaults to `.5em`).

`vspace=\space` sets the vertical space between boxes (defaults to `1ex`).

`borderwidth=\space` sets the width of the frame around all the boxes (defaults to `1mm`).

`bordercol=\color` sets the color of the frame (defaults to `lightgray`).

`backgroundcol=\color` sets the background color (defaults to `white`).

`Tsign=\text` sets the text to print at the top of the boxes to set the sign (Can also be redefined by `\def\AMCncontextSign{\text}`), and defaults to be empty).

Tpoint= $\langle text \rangle$ sets the text for the period. Can also be redefined by `\def\AMCdecimalPoint{\langle text \rangle}`, and defaults to `\raisebox{1ex}{\bf .}`.

Texponent= $\langle text \rangle$ sets the text before the exponent. Can also be redefined by `\def\AMCexponent{\langle text \rangle}`, and defaults to `\times 10^{\textasciicircum}`.

scoring= $\langle bool \rangle$ if **true**, a scoring strategy is given to AMC for this question. Defaults to **true**.

scoreexact= $\langle num \rangle$ gives the score for an exact answer (defaults to 2).

exact= $\langle num \rangle$ sets the maximal distance to the correct integer value (value without the decimal point) for an answer to be said *exact* and be rewarded to **scoreexact** points (defaults to 0).

scoreapprox= $\langle num \rangle$ gives the score for an approximative answer (defaults to 1).

approx= $\langle num \rangle$ sets the maximal distance to the correct integer value (value without the decimal point) for an answer to be said *approximative* and be rewarded to **scoreapprox** points (defaults to 0).

scorewrong= $\langle num \rangle$ gives the score for a wrong answer (defaults to 0).

keepas= $\langle name \rangle$ keeps the value entered by the student in variable $\{\langle name \rangle\}$, for future use with *alsocorrect* in another question.

alsocorrect= $\langle expression \rangle$ gives another acceptable answer, that can be based on the values entered by the student in the previous questions.

The text added at the end of the questions using `\AMCnumericChoices` when not in the separate answer sheet (and when a separate answer sheet is requested by the `separateanswersheet` package option) can also be set redefining the `\AMCncontextGoto` command, as:

```
\def\AMCncontextGoto{\par{\bf\emph{Please code the answer on
the separate answer sheet.}}}
```

3.8 French command names

For backward compatibility, some of `automultiplechoice` commands, environments and package option have their French counterpart. You can always use either the English command or the French equivalent. See table 1 for details.

3.9 Customisation

3.9.1 Boxes

`\AMCboxStyle` The command `\AMCboxStyle{\langle style \rangle}` can be used to specify the shape, color and dimensions of the boxes to be ticked. The argument $\langle style \rangle$ is a coma-separated list of $\langle key \rangle = \langle value \rangle$ pairs, with the following possible $\langle key \rangle$ s:

shape for the shape to be used: either **square** or **oval**. Note that if **oval** is used, the L^AT_EX package **tikz** must be loaded.

width for the width of the boxes.

height for the height of the boxes.

`size` for the size of the boxes (sets `width` and `height`).

`down` for the length the boxes are to be moved down.

`rule` for the rule width.

`outsidesep` for the distance between the box and the letter when printed outside the box.

`color` for the color (only the box that are to be filled by the students and will be used for data capture). Use something that will be understood by the `xcolor` package.

Default values are

```
\AMCboxStyle{shape=square,size=2.5ex,down=.4ex,
             rule=.5pt,outsidesep=.1em,color=black}
```

Setting the box color allows to print the boxes with some color that won't disturb too much the data capture (for example red, but some light grey can also be considered).

Boxes styling	
Question 9 $2 + 2 =$ Ⓐ 1 Ⓑ 4 Ⓒ 10	<pre>\AMCboxStyle{shape=oval,color=red} \begin{question}{sum}\$2+2={}\$ \begin{choiceshoriz}[o] \wrongchoice{1}\correctchoice{4} \wrongchoice{10} \end{choiceshoriz} \end{question}</pre>

3.9.2 Codes

One may adapt the codes rendering from `\AMCcodeGrid` to one's needs modifying the following lengths:

- `\AMCcodeHspace` is the amount of horizontal space between two columns of digits,
- `\AMCcodeVspace` is the amount of vertical space between two rows of digits,

Default values are `\AMCcodeHspace=.5em` `\AMCcodeVspace=.5em`

3.9.3 Answers

Environment `choicescustom` will make use of the three commands `\AMCbeginAnswer` (before the first answer), `\AMCendAnswer` (after the last answer) and `\AMCanswer{<box>}{<text>}` (for each answer) to format the answers. Redefining them properly, some different answers formatting can be achieved. However, this does not seem to work with non-trivial settings...

Question 10 $2+2=$ $\left(\begin{array}{ccc} \square & \square & \square \end{array} \right)$ $\begin{array}{ccc} 4 & 3 & 2 \end{array}$

```
\begin{question}{add}
  \def\AMCbeginAnswer{\Big$}
  \def\AMCendAnswer{\Big$}
  \def\AMCanswer#1#2{#1 #2\hfill}
  2+2=
  \begin{choicescustom}
    \correctchoice{4}
    \wrongchoice{2}
    \wrongchoice{3}
  \end{choicescustom}
\end{question}
```

4 Implementation

This package uses the following other packages:

```
1 \RequirePackage{xcolor} % \fcolorbox to fill (or not) a box
2 \RequirePackage{fancyhdr} % \pagestyle{empty}
3 \RequirePackage{bophook} % \AtBeginPage
4 \RequirePackage{xkeyval} % \setkeys
5 \RequirePackage{rotating} % \rotatebox
6 \RequirePackage{fancybox} % \boxput
7 \RequirePackage{expl3}
8 \RequirePackage{csvsimple}
9 \RequirePackage{environ}
10 % \end{macrocode}
11 %
12 % First, we read the options that can be given by AMC through the
13 % |jobname-config.tex| file:
14 % \begin{macrocode}
15 \InputIfFileExists{\jobname-config.tex}%
16 {\message{Loading configuration file...^^J}}{}
```

`\AMC@amclog` Informations about questions and choices will be logged to a file with extension `amc`, to be parsed later. Macro `\AMCmessage` writes to this file.

```
17 \newwrite\AMC@logfile
18 \immediate\openout\AMC@logfile=\jobname.amc
19 \def\AMC@amclog#1{\immediate\write\AMC@logfile{#1}}
20 \def\AMCmessage#1{\AMC@amclog{AUTOQCM[#1]^^J}}
```

`\AMC@LR` Colours management can be faulty in right-to-left mode: in these situations, we will make use of `\LR` from package `bidi` to get back to left-to-right mode. `\AMC@LR` is `\LR` if `bidi` is loaded.

```
21 \AtBeginDocument{\@ifpackageloaded{bidi}{%
22   \PackageInfo{automultiplechoice}{Package bidi loaded: using LR for boxes.}%
23   \let\AMC@LR=\LR}%
24 {\let\AMC@LR=\relax}}%
```

4.1 Variables

Counters and boolean variables defined here are internal and should not be modified by the user.

The package defines the following counters:

`\AMCload@counter` number of choices already loaded for current question.

`\AMCid@quest` current question ID number (see section 4.7).

`\AMCid@etud` current student sheet number.

`\AMCid@etudstart` starting student sheet number of the current `onecopy` bloc.

`\AMCid@check` current page checking number.

`\AMCid@etudfin` last student sheet number for the exam.

`\AMCnum@copies` number of exam sheets to produce.

It also defines the following switches:

`\ifAMC@ordre` if choices are never to be shuffled.

`\ifAMC@shuffleG` if groups shuffling is allowed.

`\ifAMC@fullGroups` if groups are always fully inserted by `\insertgroup` and fully copied by `\copygroup`, irrespective to the optional parameter.

`\ifAMC@correthead` if some correction header is to be printed at the beginning.

`\ifAMC@affichekeys` if questions keys are to be printed.

`\ifAMC@keysline` if questions keys should be printed on a single line before the question text.

`\ifAMC@correc` if correct choices are to be checked on the produced document.

`\ifAMC@qbloc` if questions are to be included in \LaTeX boxes (so that they can't be splitted on two different pages).

`\ifAMC@asqbloc` if questions are to be included in \LaTeX boxes in the answer sheet (so that they can't be splitted on two different pages).

`\ifAMC@rbloc` if answers are to be included in \LaTeX boxes (so that they can't be splitted on two different columns for example).

`\ifAMC@textPos` if questions and answers positions are to be logged.

`\ifAMC@extractOnly` if the PDF is only built to extract questions and answers images.

`\ifAMCcomplete@multi` if a choice "None of these answers are correct." is to be added to every multiple question.

`\ifAMCquestionNumber` if AMC should step up the question number for each new question.

`\ifAMC@calibration` if this \LaTeX run is used to get page layouts.

`\ifAMC@plain` if `automultiplechoice` won't try to load useful packages (`etex`, `environ`) that extend `automultiplechoice` capabilities.

`\ifAMCune@bonne` if there is at least one correct answer for the current question.

`\ifAMCtype@multi` if the current question is a multiple question.

`\ifAMC@watermark` if the document is a draft, not to be used for exam.

`\ifAMC@ensemble` if answers are to be given on a separate answers sheet.

`\ifAMC@inside@box` if a letter or digit is to be printed inside all boxes.

`\ifAMC@inside@digit` if digits are to be written inside boxes instead of letters (when using a separate answer sheet for example).

`\ifAMC@outside@box` if labels for boxes are to be printed outside the box on the answer sheet.

`\ifAMCformulaire@dedans` is true for questions inside separate answer sheet.

`\ifAMC@zoneformulaire` is true for codes (made by `\AMCcodeGrid`) inside separate answer sheet.

`\ifAMC@pagelayout` is true if the AMC page layout, with signs for scan analysis, is to be used.

`\ifAMC@postcorrect` corresponds to the use of the `postcorrect` package option.

`\ifAMC@automarks` corresponds to the use of the `automarks` package option.

`\ifAMC@invisible` is true is the DVI/PDF output is not important (used for example for scoring strategy extraction).

`\ifAMC@pdfform` is true if the output is a PDF form. This PDF will not be printed but will be filled by the students with a PDF reader and sent back to the teacher.

```

25 \newcount\AMCload@counter
26 \newcount\AMCid@quest\AMCid@quest=-1
27 \newcount\AMCid@check
28 \newcount\AMCid@etud\AMCid@etud=0
29 \newcount\AMCid@etudstart\AMCid@etudstart=0
30 \newcount\AMCid@etudfin
31 \newcount\AMCnum@copies

32 \newif\ifAMC@ordre\AMC@ordrefalse
33 \newif\ifAMC@shuffle\AMC@shuffleGtrue
34 \newif\ifAMC@fullGroups\AMC@fullGroupsfalse
35 \newif\ifAMC@correthead\AMC@corretheadfalse
36 \newif\ifAMC@affichekeys\AMC@affichekeysfalse
37 \newif\ifAMC@keyline\AMC@keylinefalse
38 \newif\ifAMC@correc\AMC@correcfalse
39 \newif\ifAMC@textPos\AMC@textPosfalse
40 \newif\ifAMC@extractOnly\AMC@extractOnlyfalse
41 \newif\ifAMC@qbloc\AMC@qblocfalse
42 \newif\ifAMC@asqbloc\AMC@asqblocfalse
43 \newif\ifAMC@rbloc\AMC@rblocfalse
44 \newif\ifAMC@complete@multi\AMC@complete@multifalse
45 \newif\ifAMC@questionNumber\AMC@questionNumbertrue
46 \newif\ifAMC@calibration\AMC@calibrationfalse
47 \newif\ifAMC@catalog\AMC@catalogfalse
48 \newif\ifAMC@plain\AMC@plainfalse

```



```

49 \newif\ifAMCune@bonne
50 \newif\ifAMCtype@multi
51 \newif\ifAMC@watermark\AMC@watermarktrue
52 \newif\ifAMC@inside@box\AMC@inside@boxfalse
53 \newif\ifAMC@outside@box\AMC@outside@boxfalse
54 \newif\ifAMC@ensemble\AMC@ensemblefalse
55 \newif\ifAMC@inside@digit\AMC@inside@digitfalse
56 \newif\ifAMC@formulaire@dedans\AMC@formulaire@dedansfalse
57 \newif\ifAMC@zoneformulaire
58 \newif\ifAMC@pagelayout\AMC@pagelayouttrue
59 \newif\ifAMC@postcorrect\AMC@postcorrectfalse
60 \newif\ifAMC@automarks\AMC@automarksfalse
61 \newif\ifAMC@invisible\AMC@invisiblefalse
62 \newif\ifAMC@pdfform\AMC@pdfformfalse
63 \let\AMCcompleteMulti=\AMCcomplete@multitrue
64 \let\AMCnoCompleteMulti=\AMCcomplete@multifalse

```

`\AMCid@name` The package also defines command `\AMCid@name` to be the current question identifier key.

```
65 \def\AMCid@name{}
```

4.2 Dimensions

`\AMCformVSpace` The following dimensions can be modified by the user to adjust questions formatting:

`\AMCformHSpace` `\AMCformVSpace` is the amount of vertical space between two questions in a separate answer sheet.

`\AMCformHSpace` is the amount of horizontal space between two answers boxes in a separate answer sheet.

`\AMCinterIrep` is the amount of vertical space to be added between two answers.

`\AMCinterBrep` is the amount of vertical space between two boxed answers (see `\AMCBoxedAnswers` and `\ifAMC@rbloc`).

`\AMCinterIquest` is the amount of vertical space left after a question, in standard mode (without package option `box`).

`\AMCinterBquest` is the amount of vertical space left after a question, in 'boxed' mode (with package option `box`).

`\AMCpostOquest` is the amount of vertical space left after an open question.

```

66 \newdimen\AMCformVSpace\AMCformVSpace=1.2ex
67 \newdimen\AMCformHSpace\AMCformHSpace=.3em
68 \newdimen\AMCinterIrep\AMCinterIrep=\z@
69 \newdimen\AMCinterBrep\AMCinterBrep=.5ex
70 \newdimen\AMCinterIquest\AMCinterIquest=\z@
71 \newdimen\AMCinterBquest\AMCinterBquest=3ex
72 \newdimen\AMCpostOquest\AMCpostOquest=7mm

```

4.3 Human readable sheet ID position

`\AMCidsPosition` The position of the human readable sheet ID, near the corresponding binary boxes, is set with the `\AMCidsPosition` command, in the form `\AMCidsPosition{pos=<position>,width=<width>,height=<height>}`, where *<position>* is one of `side` (default), `top` and `none`, *<width>* is the width of the box enclosing the ID (default value is 4cm), and *<height>* is the height of the box enclosing the ID (default value is 3ex).

```
73 \newif\ifAMCids@top
74 \newif\ifAMCids@side
75 \newdimen\AMCids@width
76 \newdimen\AMCids@height
77 \define@choicekey*{AMCids}{pos}{\AMCidsVar\AMCidsVarN}{none,top,side}{%
78   \ifcase\AMCidsVarN\relax
79     \AMCids@topfalse\AMCids@sidefalse
80   \or
81     \AMCids@toptrue\AMCids@sidefalse
82   \or
83     \AMCids@topfalse\AMCids@sidesettrue
84   \fi
85 }
86 \define@key{AMCids}{width}{\AMCids@width=#1}
87 \define@key{AMCids}{height}{\AMCids@height=#1}
88 \def\AMCidsPosition#1{\setkeys{AMCids}{#1}}
89 \AMCidsPosition{pos=side,width=4cm,height=3ex}
```

4.4 Localisation

In this section, some localised strings or commands are defined, for English, French and Spanish languages.

`\AMCtext` To modify these texts, you can use command `\AMCtext`. For example, `\AMCtext{draft}{<text>}` sets the text to be printed behind each page of a draft exam.

```
90 \def\AMCtext#1#2{\expandafter\def\csname AMC@loc@#1\endcsname{#2}}
91 \def\AMClocalized#1{\csname AMC@loc@#1\endcsname}
```

4.4.1 English

Text indicating draft exams:

```
92 \def\AMC@loc@draft{DRAFT}
```

Message at page bottom when compiled out of AMC gui:

```
93 \def\AMC@loc@message{For your examination, preferably print
94   documents compiled from auto-multiple-choice.}
```

Announcing a question in a separate sheet (parameter #1 is the question number):

```
95 \def\AMC@loc@qf#1{\textbf{Question #1:}}
```

Announcing a question (parameter #1 is the question number and parameter #2 can be the multiple question symbol, or be empty):

```
96 \def\AMC@loc@q#1#2{\textbf{Question #1} #2}
```

Headers for corrected version and catalog:

```
97 \def\AMC@loc@corrected{Corrected}
98 \def\AMC@loc@catalog{Catalog}
```

Localization text for Explanation

```
99 \def\AMC@loc@explain{\textit{\textbf{Explanation: }}}}
```

Last choice added at the end for multiple questions when option `completemulti` is used:

```
100 \def\AMC@loc@none{None of these answers are correct.}
```

Word for 'question', singular and plural forms:

```
101 \def\AMC@loc@question{question}
102 \def\AMC@loc@questions{questions}
```

Default text to write in the students' name box:

```
103 \def\AMC@loc@namesurname{Name and surname:}
```

4.4.2 Catalan

Catalan localisation is called with option `lang=CA`.

```
104 \def\AMC@loc@CA{
105   \def\AMC@loc@draft{PROJECTE}
106   \def\AMC@loc@message{Pel vostre examen, imprimeu preferiblement
107     els documents compilats amb l'ajuda de auto-multiple-choice.}
108   \def\AMC@loc@qf##1{\textbf{Pregunta ##1 :}}
109   \def\AMC@loc@q##1##2{\textbf{Pregunta ##1} ##2}
110   \def\AMC@loc@corrected{Correcci\'}o}
111   \def\AMC@loc@catalog{Cat\'}aleg}
112   \def\AMC@loc@explain{\textit{\textbf{Explicaci\'}o : }}}
113   \def\AMC@loc@none{Cap de les respostes \'}es correcte.}
114   \def\AMC@loc@question{pregunta}
115   \def\AMC@loc@questions{preguntes}
116   \def\AMC@loc@namesurname{Nom i cognoms:}
117 }
```

4.4.3 Dutch

Dutch localisation is called with option `lang=NL`.

```
118 \def\AMC@loc@NL{
119   \def\AMC@loc@draft{Ontwerp}
120   \def\AMC@loc@message{Gebruik bij uw proefwerk bij voorkeur die
121     documenten welke door auto-multiple-choice zijn aangemaakt.}
122   \def\AMC@loc@qf##1{\textbf{Vraag ##1 :}}
123   \def\AMC@loc@q##1##2{\textbf{Vraag ##1} ##2}
124   \def\AMC@loc@corrected{Correctie}
125   \def\AMC@loc@catalog{Catalogus}
126   \def\AMC@loc@none{Geen van de antwoorden is juist.}
127   \def\AMC@loc@question{vraag}
128   \def\AMC@loc@questions{vragen}
129   \def\AMC@loc@namesurname{Achternaam en voornaam:}
130 }
```

4.4.4 French

French localisation is called with option `francais`, or `lang=FR`.

```
131 \def\AMC@loc@FR{
132   \def\AMC@loc@draft{PROJET}
133   \def\AMC@loc@message{Pour votre examen, imprimez de pr\'}ef\'}erence
```

```

134   les documents compil\’es \’a l’aide de auto-multiple-choice.}
135 \def\AMC@loc@qf##1{\textbf{Question ##1 :}}
136 \def\AMC@loc@q##1##2{\textbf{Question ##1} ##2}
137 \def\AMC@loc@corrected{Correction}
138 \def\AMC@loc@catalog{Catalogue}
139 \def\AMC@loc@explain{\textit{\textbf{Explication : }}}
140 \def\AMC@loc@none{Aucune de ces r’eponses n’est correcte.}
141 \def\AMC@loc@question{question}
142 \def\AMC@loc@questions{questions}
143 \def\AMC@loc@namesurname{Nom et pr’enom :}
144 }

```

4.4.5 German

German localisation is called with option `lang=DE`.

```

145 \def\AMC@loc@DE{
146   \def\AMC@loc@draft{ENTWURF}
147   \def\AMC@loc@message{Benutzen Sie f\'ur Ihre Pr\'ufung bevorzugt Dokumente die mit
148     auto-multiple-choice erstellt wurden.}
149   \def\AMC@loc@qf##1{\textbf{Frage ##1 :}}
150   \def\AMC@loc@q##1##2{\textbf{Frage ##1} ##2}
151   \def\AMC@loc@corrected{Korrektur}
152   \def\AMC@loc@catalog{Katalog}
153   \def\AMC@loc@explain{\textit{\textbf{Erkl\'arung : }}}
154   \def\AMC@loc@none{Keine dieser Antworten ist korrekt.}
155   \def\AMC@loc@question{Frage}
156   \def\AMC@loc@questions{Fragen}
157   \def\AMC@loc@namesurname{Vor- und Nachname:}
158 }

```

4.4.6 Italian

Italian localisation is called with option `lang=IT`.

```

159 \def\AMC@loc@IT{
160   \def\AMC@loc@draft{BOZZA}
161   \def\AMC@loc@message{Per l’esame, \’e preferibile stampare i documenti
162     a partire da auto-multiple-choice.}
163   \def\AMC@loc@qf##1{\textbf{Domanda ##1:}}
164   \def\AMC@loc@q##1##2{\textbf{Domanda ##1} ##2}
165   \def\AMC@loc@corrected{Correzione}
166   \def\AMC@loc@catalog{Catalogo}
167   \def\AMC@loc@none{Nessuna risposta \’e giusta.}
168   \def\AMC@loc@question{domanda}
169   \def\AMC@loc@questions{domande}
170   \def\AMC@loc@namesurname{Nome e cognome:}
171 }

```

4.4.7 Norwegian

Norwegian localisation is called with option `lang=NO`.

```

172 \def\AMC@loc@NO{
173   \def\AMC@loc@draft{UTKAST}
174   \def\AMC@loc@message{Det anbefales {\aa} skrive ut dokumentet

```

```

175 for gjennomgang \direkte fra auto-multiple-choice.}
176 \def\AMC@loc@qf##1{\textbf{Oppgave ##1 :}}
177 \def\AMC@loc@q##1##2{\textbf{Oppgave ##1} ##2}
178 \def\AMC@loc@corrected{Rettet}
179 \def\AMC@loc@catalog{Katalog}
180 \def\AMC@loc@none{Ingen svar er riktige.}
181 \def\AMC@loc@question{oppgave}
182 \def\AMC@loc@questions{oppgave}
183 \def\AMC@loc@namesurname{Etternavn og fornavn:}
184 }

```

4.4.8 Portuguese

Portuguese localisation is called with option `lang=PT`.

```

185 \def\AMC@loc@PT{
186   \def\AMC@loc@draft{RASCUNHO}
187   \def\AMC@loc@message{Para o seu exame, use preferencialmente documentos compilados do auto-multiple-choice.}
188   \def\AMC@loc@qf##1{\textbf{Quest\~ao ##1:}}
189   \def\AMC@loc@q##1##2{\textbf{Quest\~ao ##1} ##2}
190   \def\AMC@loc@corrected{Corrigido}
191   \def\AMC@loc@catalog{Cat\'alogo}
192   \def\AMC@loc@explain{\textit{\textbf{Justifique: }}}
193   \def\AMC@loc@none{Nenhuma das respostas apresentadas est\'a correta.}
194   \def\AMC@loc@question{Quest\~ao}
195   \def\AMC@loc@questions{Quest\~oes}
196   \def\AMC@loc@namesurname{Nome e apelido:}
197 }

```

4.4.9 Spanish

Spanish localisation is called with option `lang=ES`.

```

198 \def\AMC@loc@ES{
199   \def\AMC@loc@draft{BORRADOR}
200   \def\AMC@loc@message{Para revisi\'on, preferentemente imprimir documentos compilados
201     desde auto-multiple-choice.}
202   \def\AMC@loc@qf##1{\textbf{Pregunta ##1 :}}
203   \def\AMC@loc@q##1##2{\textbf{Pregunta ##1} ##2}
204   \def\AMC@loc@corrected{Correcci\'on}
205   \def\AMC@loc@catalog{Cat\'alogo}
206   \def\AMC@loc@none{Ninguna de estas preguntas son correctas.}
207   \def\AMC@loc@question{pregunta}
208   \def\AMC@loc@questions{preguntas}
209   \def\AMC@loc@namesurname{Nombre y apellidos:}
210 }

```

4.4.10 Japanese

Japanese localisation is called with option `lang=JA`. It includes UTF8 encoded Japanese characters which are shown as \diamond here (look at the `.sty` file to see them).

```

211 \def\AMC@loc@JA{
212   \def\AMC@loc@draft{\diamond\diamond\diamond\diamond}
213   \def\AMC@loc@message{\diamond\diamond\diamond\diamondauto-multiple-choice\diamond\diamond\diamond\diamond\diamond\diamond\diamond\diamond\diamond\diamond}
214   \def\AMC@loc@qf##1{\textbf{\diamond##1:}}

```

```

215 \def\AMC@loc@q##1##2{\textbf{\diamond##1} ##2}
216 \def\AMC@loc@corrected{\diamond}
217 \def\AMC@loc@catalog{\diamond\diamond}
218 \def\AMC@loc@explain{\textit{\textbf{\diamond: }}}
219 \def\AMC@loc@none{\diamond}
220 \def\AMC@loc@question{\diamond}
221 \def\AMC@loc@questions{\diamond}
222 }

```

4.4.11 Other languages

Other languages can be integrated to automultiplechoice package upon request to the author.

4.5 Interaction with other packages

4.5.1 cleveref

For references to questions:

```

223 \AtBeginDocument{\@ifpackageloaded{cleveref}{%
224   \message{AMC/cleveref integration loaded~J}%
225   \crefalias{AMCQuestionaff}{question}%
226   \crefname{question}{\AMC@loc@question}{\AMC@loc@questions}%
227 }{}}%

```

4.6 Random

4.6.1 Random pseudo-generator

The package uses the pseudo-random bit generator from *TuGBoat* 1994, vol 15:1:

```

228 \ifx\AMC@SR\undefined\newcount\AMC@SR\fi
229 \providecommand\AMC@SRconst{2097152}
230 \providecommand\AMC@SRset[1]{\global\AMC@SR#1 \ignorespaces}
231 \providecommand\AMC@SRadvance{%
232   \begingroup%
233     \ifnum\AMC@SR<\AMC@SRconst\relax\AMC@SR@count\z@else\AMC@SR@count\@ne\fi%
234     \ifodd\AMC@SR\advance\AMC@SR@count\@ne\fi%
235     \global\divide\AMC@SR\tw@%
236     \ifodd\AMC@SR@count\global\advance\AMC@SR\AMC@SRconst\relax\fi%
237   \endgroup}
238 \providecommand\AMC@SRbit{\AMC@SRadvance\ifodd\AMC@SR1\else0\fi}
239 \providecommand\AMC@SRtest[2]{\AMC@SRadvance%
240   \ifodd\AMC@SR#2\else#1\fi\ignorespaces}
241 \providecommand\AMC@SRvalue{\number\AMC@SR}

```

`\AMCrandomseed` The seed of this generator is set to 1515, but another value can be given using the command `\AMCrandomseed{<seed>}`.

```

242 \AMC@SRset{1515}
243 \def\AMCrandomseed#1{\AMC@SRset{#1}}

```

4.6.2 Uniform random deviates

`\AMC@SRnextByte` This generator is used to build first a 20-bit uniform integer generator (macro `\AMC@SRnextByte`).
`\AMC@SRmax` Then, using modulo, a (nearly) uniform generator on $\{0, \dots, n - 1\}$ is built: command `\AMC@SRmax{n}` puts in `\AMC@SR@count` the random deviate.

```

244 \newcount\AMC@SR@count
245 \def\AMC@SR@time{\AMC@SRset{\time}}
246 \newcount\AMC@SRnum
247 \def\AMC@SRnextByte{\AMC@SRnum=\z@%
248   \AMC@SR@count=20%
249   \loop\multiply\AMC@SRnum\tw@%
250     \AMC@SRtest{\advance\AMC@SRnum\@ne}\}%
251   \ifnum\AMC@SR@count>\@ne\advance\AMC@SR@count\m@ne\repeat%
252 }
253 \newcommand\AMC@SRmax[1]{\AMC@SRnextByte%
254   \AMC@SR@count=\AMC@SRnum%
255   \divide\AMC@SR@count by #1\relax%
256   \multiply\AMC@SR@count by #1\relax%
257   \advance\AMC@SRnum by -\AMC@SR@count%
258 }
```

4.6.3 Tokens shuffling

`\AMCsw@p` The package defines the macro `\AMCsw@p` to swap the values of two token registers given as
`\AMC@shuffletoks` parameters.

After defining n token registers `\foo@i`, `\foo@ii`, `\foo@iii`, `\foo@iv` and so on, you can shuffle them using `\AMC@shuffletoks[\langle a \rangle]{\langle n \rangle}{\langle foo \rangle}`. With optional argument $\langle a \rangle$, registers are shuffled from number $\langle a \rangle$ to $\langle n \rangle$ (default value for $\langle a \rangle$ is 1).

```

259 \newcount\AMC@sti
260 \newcount\AMC@stil
261 \newtoks\AMCsw@p@
262 \newcommand\AMCsw@p[2]{%
263   \global\AMCsw@p@=#1%
264   \global#1=#2%
265   \global#2=\AMCsw@p@}
266 \newcommand{\AMC@shuffletoks}[3][\@ne]{%
267   \AMC@sti=#2\relax%
268   \AMC@stil=#2\relax%
269   \advance\AMC@stil\@ne%
270   \advance\AMC@stil -#1\relax%
271   \@whilenum\AMC@sti>#1\do{%
272     \AMC@SRmax{\AMC@stil}\advance\AMC@SRnum #1\relax%
273     \AMCsw@p{\csname #3\romannumeral\AMC@SRnum\endcsname}%
274       {\csname #3\romannumeral\AMC@sti\endcsname}%
275     \advance\AMC@sti\m@ne\relax%
276     \advance\AMC@stil\m@ne\relax%
277   }}
```

4.7 Keys numbering

`\AMC@unnumero` This package allocates a unique integer ID to each question key from the questionnaire.
`\AMC@affecte` The counter `\AMC@numerotation` keeps track of the number of keys which already had an

ID. Command `\AMC@definitnumero{n}{key}` allocates ID *n* to the key *key*. Command `\AMC@prepare{key}` looks if an ID had already been associated to *key*, and, if not, makes a new ID allocation for *key*. Command `\AMC@unnumero{key}` returns the ID associated with *key* (creating one if necessary). Command `\AMC@affecte{key}{\cnt}` give to counter `\cnt` the value of the ID associated to *key* (creating one if necessary).

```

278 \newcount\AMC@numerotation\AMC@numerotation=\z@%
279 \def\AMC@definitnumero#1#2{\AMC@amclog{AUTOQCM[NUM=#1=#2]^^J}}%
280 \expandafter\global\expandafter\def\csname AMC@numtab@#2\endcsname{#1}%
281 \def\AMC@prepare#1{\expandafter\ifx\csname AMC@numtab@#1\endcsname\relax%
282 \global\advance\AMC@numerotation\@ne%
283 \expandafter\AMC@definitnumero\expandafter{\the\AMC@numerotation}{#1}\fi}
284 \def\AMC@unnumero#1{\AMC@prepare{#1}\csname AMC@numtab@#1\endcsname}%
285 \def\AMC@affecte#1#2{\AMC@prepare{#1}\global#2=\csname AMC@numtab@#1\endcsname}%

```

4.8 Boxes

4.8.1 Character logging

`\AMC@logchar` The command `\AMC@logchar{<char>}{<key>}` logs the character written in the box referenced as *<key>* in the .cs file. This is used in catalog mode, to get understandable references to answers from the statistics tables of the ODS export.

```

286 \def\AMC@logchar#1#2{%
287 \protected@write\AMC@CSFILE{}{%
288 \string\answer%
289 {\the\AMCid@etud/\thepage:#2}%
290 {#1}}%
291 }

```

4.8.2 Position logging

`\AMC@tracebox` Command `\AMC@tracebox{<trace>}{<key>}{<content>}` makes a L^AT_EX box around *<content>*, and, if *<trace>* is not empty, logs to the .xy file informations to be able to compute exact location of this box on the page, attached to the box identification *<key>*.

Command `\AMC@pagepos` logs page and page size informations at the beginning of each page.

```

292 \def\AMC@shapename@{\ifAMC@invisible none\else\AMC@shapename\fi}
293 \def\AMC@tracepos#1#2{%
294 \ifAMC@calibration\ifx\@empty#1\@empty\else%
295 \pdfsavepos\protected@write\AMC@XYFILE{}{%
296 \string\tracepos%
297 {\the\AMCid@etud/\thepage:#2}%
298 {\noexpand\number\pdflastxpos sp}%
299 {\noexpand\number\pdflastypos sp}%
300 {\AMC@shapename}}%
301 \fi\fi}
302 \def\AMC@traceposx#1#2{%
303 \ifAMC@calibration\ifx\@empty#1\@empty\else%
304 \pdfsavepos\protected@write\AMC@XYFILE{}{%
305 \string\tracepos%
306 {\the\AMCid@etud/\thepage:#2}%
307 {\noexpand\number\pdflastxpos sp}%
308 {0sp}%
309 {\AMC@shapename}}%

```



```

310 \fi\fi}
311 \def\AMC@traceposy#1#2{%
312 \ifAMC@calibration\ifx\@empty#1\@empty\else%
313 \pdfsavepos\protected@write\AMC@XYFILE{}{%
314 \string\tracepos%
315 {\the\AMCid@etud/\thepage:#2}%
316 {0sp}%
317 {\noexpand\number\pdfastypos sp}%
318 {\AMC@shapename}}}%
319 \fi\fi}
320 \newcommand\AMC@tracebox[3]{%
321 \vbox{\AMC@traceposy{#1}{#2}%
322 \hbox{\AMC@traceposx{#1}{#2}#3\AMC@traceposx{#1}{#2}}}%
323 \AMC@traceposy{#1}{#2}}
324 \def\AMC@pagepos{%
325 \ifAMC@calibration\protected@write\AMC@XYFILE{}{%
326 \string\page%
327 {\the\AMCid@etud/\thepage/\the\AMCid@check}%
328 {\the\paperwidth}{\the\paperheight}%
329 {\the\pdfpagewidth}{\the\pdfpageheight}}\fi}

```

`\AMCdontScan` The commands `\AMCdontScan` and `\AMCdontAnnotate` write into the xy file instructions related to the current question.

```

330 \newcommand{\AMCdontScan}{\ifAMC@calibration\immediate\write\AMC@XYFILE{\string\dontscan{\the\AMCid@etud}}}%
331 \newcommand{\AMCdontAnnotate}{\ifAMC@calibration\immediate\write\AMC@XYFILE{\string\dontannotate{\the\AMCid@etud}}}%
332 %

```

`\AMC@tracechar` The macro `\AMC@tracechar{<char>}{<unused>}{<trace>}{<key>}` is used to log (for further processing with AMC), into to .xy file, the character used to identify the box.

```

333 \newcommand\AMC@tracechar[4]{%
334 \ifAMC@calibration\ifx\@empty#3\@empty\else%
335 \protected@write\AMC@XYFILE{}{%
336 \string\boxchar{\the\AMCid@etud/\thepage:#4}{#1}%
337 }%
338 \fi\fi%
339 }

```

`amcxyfile (env.)` The following lines defines an environment to use a particular file for positions outputs. This is used mainly for documentation or testing.

```

340 \newwrite\AMC@XYspecial
341 \newwrite\AMC@tmpXY
342 \newenvironment{amcxyfile}[1]{%
343 \openout\AMC@XYspecial#1%
344 \let\AMC@tmpXY=\AMC@XYFILE%
345 \let\AMC@XYFILE=\AMC@XYspecial%
346 }{\let\AMC@XYFILE=\AMC@tmpXY\closeout\AMC@XYspecial}

```

`\namefield` The `\namefield{<name field content>}` is a simple call to `\AMC@tracebox`:

```

347 \newcommand{\namefield}[1]{\AMC@tracebox{1}{nom}{#1}}

```

It is used to enclose the page region where students are to write their names, so as to retrieve it easily from the scans.

`\namefielddots` The command `\namefielddots` can be used to fill a line with dots (printed sheets) or use a text field in PDF forms:

```

348 \newcommand{\namefielddots}{%
349   \noindent%
350   \ifAMC@pdfform%
351     \hspace*{\fill}%
352     \TextField[name={\the\AMCid@etud:namefield},width=.95\linewidth,bordercolor=0 0 0]{}%
353     \hspace*{\fill}
354   \else%
355     \dotfill
356   \fi%
357 }
```

As an example,

```

\namefield{\fbox{%
  \begin{minipage}{5cm}
    Name:

    \vspace*{.5cm}
    \namefielddots
    \vspace{2mm}
  \end{minipage}}}
```

produces the following box:

Name:

and outputs information about the position of the box in the `.xy` file, as seen in section 5.1.

4.8.3 Boxes to be checked by students

`\AMC@answerBox@` There are two styles for boxes to be checked by the students. The first one is an empty box, printed beside the answer. The second is a box with a character in it. It is mainly used when answers are to be given on a separate answer sheet.

These boxes can be drawn using command `\AMC@answerBox@{<char>}{<answer>}{<trace>}{<key>}`: `<char>` is the character to print inside the box, `<trace>` is non-empty if you want to log the box position in the `.xy` file, `<key>` is the box identification, and `<answer>` is an answer to be written in the box (or `\AMC@checkbox` for filling the box).

Depending on the required shape for the boxes, the corresponding

`\AMC@shape@xxx{<char>}{<answer>}{<trace>}{<key>}`

command is used.

- `\AMC@answerBox@{K}{1}{test}` produce the box K, writing the lines in the `.xy` file shown in section 5.2.
- `\AMC@answerBox@{K}{\AMC@checkbox}{}` produces
- `\AMC@answerBox@{}{8}{}` produces 8

- `\AMC@answerBox@{K}{8}{1}{testb}` produces  with `\AMC@boxStyle{shape=oval,color=red}`

```

358 \def\AMC@checkedbox{}
359 \let\AMC@new@savebox=\newsavebox
360 \let\AMC@save@box=\savebox
361 \let\AMC@use@box=\usebox
362 \newif\ifAMC@draw@cross

```

The `\AMC@smashcentered{<text>}` command shows the `<text>` centered at point.

```

363 \newbox\AMC@smashbox
364 \newdimen\AMC@smashboxheight
365 \newcommand\AMC@smashcentered}[1]{%
366   \setbox\AMC@smashbox\hbox{#1}%
367   \AMC@smashboxheight=\ht\AMC@smashbox%
368   \advance\AMC@smashboxheight by \dp\AMC@smashbox%
369   \vfuzz=\AMC@smashboxheight\hfuzz=\wd\AMC@smashbox%
370   \hspace*{-.5\wd\AMC@smashbox}\hbox to .5\wd\AMC@smashbox{%
371     \vbox to 0pt{%
372       \vspace*{-.5\AMC@smashboxheight}\vbox to .5\AMC@smashboxheight{%
373         \box\AMC@smashbox}}}%
374 }%

```

`\AMC@setcolors@{<trace>}{<answer>}` sets colours `\AMC@boxcolor@` and `\AMC@fillcolor@` according to its arguments. It also sets the `\ifAMC@draw@cross` switch if AMC should draw a cross instead of filling the box.

```

375 \newcommand\AMC@setcolors@[2]{%
376   \def\AMC@boxcolor@{\AMC@boxcolor}%
377   \ifx\@empty#1\@empty \def\AMC@boxcolor@{black}\fi%
378   \ifAMC@correc\def\AMC@boxcolor@{black}\fi%
379   \def\AMC@fillcolor@{\ifx #2\AMC@checkedbox%
380     \AMC@boxcolor@\else white\fi}%
381   \AMC@draw@crossfalse%
382   \ifKV@AMCdim@cross\ifx #2\AMC@checkedbox%
383     \AMC@draw@crosstrue\fi\fi%
384 }%
385 \newcommand\AMC@answerBox@[4]{%
386   \ifAMC@catalog%
387     \AMC@logchar{#1}{#4}%
388     \fi%
389     \AMC@LR{\hspace{0pt}%
390       \lower\AMC@boxeddown\hbox{\csname AMC@shape@\AMC@shapename@\endcsname%
391         {\AMCchoiceLabelFormat{#1}}{#2}{#3}{#4}}}%
392 }%
393 \newcommand\AMC@shapeprepare@square{}
394 \newcommand\AMC@shape@square[4]{%
395   \fboxsep=\z@\fboxrule=\AMC@boxedrule%
396   \AMC@setcolors@{#3}{#2}%
397   \ifKV@AMCdim@cross\def\AMC@fillcolor@{white}\fi%
398   \fcolorbox{\AMC@boxcolor@}{\AMC@fillcolor@}%
399   {%
400     \boxput*(0,0){%
401       \ifAMC@draw@cross\AMC@crosschar\fi%
402     }%
403     \vbox to \AMC@boxedheight{%

```

```

404 \AMC@tracepos{#3}{#4}%
405 \vfill%
406 \hbox to \AMC@boxedwidth{\hfill%
407 \AMC@smashcentered{\textcolor{\AMC@boxcolor@}{#1}}%
408 \AMC@smashcentered{#2}%
409 \hfill}\vfill}%
410 \AMC@tracepos{#3}{#4}}%
411 }

```

`\AMC@makeovalbox{<trace>}{<answer>}{<box>}` prepares an oval frame in the L^AT_EX box `<box>`.

```

412 \newcommand\AMC@makeovalbox[3]{%
413 \AMC@setcolors@{#1}{#2}%
414 \ifKV@AMCdim@cross\def\AMC@fillcolor@{white}\fi%
415 \AMC@save@box{#3}{%
416 \begin{tikzpicture}%
417 \useasboundingbox (-0.5\AMC@boxedwidth-0.5\AMC@boxedrule,0.5\AMC@boxedheight+0.5\AMC@boxedrule)
418 rectangle (0.5\AMC@boxedwidth+0.5\AMC@boxedrule,-0.5\AMC@boxedheight-0.5\AMC@boxedrule);
419 \draw[\AMC@boxcolor@,fill=\AMC@fillcolor@,line width=\AMC@boxedrule,rounded corners=\AMC@oval@radi
420 (-0.5\AMC@boxedwidth,0.5\AMC@boxedheight)
421 rectangle (0.5\AMC@boxedwidth,-0.5\AMC@boxedheight);
422 \ifAMC@draw@cross
423 \draw[\AMC@boxcolor@,line width=\AMC@crossrule]
424 (-0.5\AMC@boxedwidth,0.5\AMC@boxedheight) -- (0.5\AMC@boxedwidth,-0.5\AMC@boxedheight)
425 (0.5\AMC@boxedwidth,0.5\AMC@boxedheight) -- (-0.5\AMC@boxedwidth,-0.5\AMC@boxedheight);
426 \fi
427 \end{tikzpicture}}%
428 }
429 \newcommand\AMC@shapeprepare@oval{%
430 \ifx\AMC@ovalbox@R\undefined\else%
431 \AMC@makeovalbox{1}{\AMC@ovalbox@R}%
432 \AMC@makeovalbox{1}{\AMC@checkedbox}{\AMC@ovalbox@RF}%
433 \AMC@makeovalbox{}{\AMC@ovalbox@}%
434 \AMC@makeovalbox{}{\AMC@checkedbox}{\AMC@ovalbox@F}%
435 \fi%
436 }
437 \newcommand\AMC@shape@oval[4]{%
438 \AMC@setcolors@{#3}{#2}%
439 \AMC@tracebox{#3}{#4}{\boxput*(0,0){%
440 \AMC@smashcentered{\textcolor{\AMC@boxcolor@}{#1}}%
441 \AMC@smashcentered{#2}%
442 }{%
443 \ifx\@empty#3\@empty%
444 \ifx #2\AMC@checkedbox%
445 \AMC@use@box{\AMC@ovalbox@F}%
446 \else%
447 \AMC@use@box{\AMC@ovalbox@}%
448 \fi%
449 \else%
450 \ifx #2\AMC@checkedbox%
451 \AMC@use@box{\AMC@ovalbox@RF}%
452 \else%
453 \AMC@use@box{\AMC@ovalbox@R}%
454 \fi%
455 \fi%

```

```

456   }}%
457 }
458 \newcommand\AMC@shapeprepare@form{}
459 \newcommand\AMC@shape@form@base[5]{%
460   \ifx #2\AMC@checkbox%
461     \def\AMC@shape@form@ticked{true}%
462   \else%
463     \def\AMC@shape@form@ticked{false}%
464   \fi%
465   \AMC@tracebox{#3}{#4}{%
466     \CheckBox[checked=\AMC@shape@form@ticked,%
467       checkboxsymbol=\ding{110},name={#5},%
468       bordercolor=0 0 0,
469       width=\AMC@boxedwidth,height=\AMC@boxedheight]{#5}}%
470   }%
471 }
472 \newcommand\AMC@shape@form[4]{%
473   \AMC@shape@form@base{#1}{#2}{#3}{#4}{\the\AMCid@etud:#4}%
474 }
475 \newcommand\AMC@shapeprepare@none{}
476 \newcommand\AMC@shape@none[4]{ #1 }

```

\AMC@answerBox Command \AMC@answerBox is the same as \AMC@answerBox@, but if $\langle char \rangle$ is empty, it is replaced by an arabic or alphabetical counter, depending on the use of the `digits` package option.

\AMCchoiceLabel To use another way to label the choices boxes, the user can redefine the \AMCchoiceLabel macro, which takes as argument the name of the counter used to number the choices. One can for example use `\def\AMCchoiceLabel#1{\alph{#1}}` to ask for lowercase letters.

To write these labels with another font, size, or so, the user can redefine the \AMCchoiceLabelFormat macro, which takes as argument the label. One can for example get sans serif bold labels with `\def\AMCchoiceLabelFormat#1{\textsf{\textsf{#1}}}`.

```

477 \def\AMCchoiceLabel#1{%
478   \ifAMC@inside@digit\arabic{#1}%
479   \else\Alph{#1}\fi%
480 }
481 \def\AMCchoiceLabelFormat#1{#1}
482 \newcounter{AMC@ncase}
483 \setcounter{AMC@ncase}{0}
484 \newcommand\AMC@answerBox[4]{%
485   \AMC@answerBox@{\ifx\@empty#1\@empty%
486     \AMCchoiceLabel{AMC@ncase}%
487     \else #1\fi}{#2}{#3}{#4}}

```

\AMCboxStyle The dimensions of these box are managed by \AMCboxDimensions{ $\langle sizes \rangle$ }, where $\langle sizes \rangle$ is a coma separated list of $\langle name \rangle = \langle dimension \rangle$ constructs. Here, $\langle name \rangle$ can be `size` for the box size, `rule` for the box rule width, `down` for moving the box down, `color` for the box color and `outsidessep` for the distance between the box and the letter (when outside the box).

The $\langle color \rangle$ value given to `color` is a color that should be defined for the `xcolor` package. This color is used only in the case the box will be used for data capture: it is not used on the corrected answer sheet (`answers` or `indivanswers` package option), and not used on the subject part of an exam with a separate answer sheet (`separateanswersheet` package option).

The `\AMCboxColor{ $\langle color \rangle$ }` command is defined as an alias to `\AMCboxStyle{color= $\langle color \rangle$ }`, and `\AMCboxDimensions` as an alias to `\AMCboxStyle`, for backward compatibility.

```

488 \newlength\AMC@boxedrule
489 \newlength\AMC@crossrule
490 \newlength\AMC@boxeddown
491 \newlength\AMC@boxedwidth
492 \newlength\AMC@boxedheight
493 \newlength\AMC@oval@radius
494 \newlength\AMC@outside@sep
495 \define@choicekey{AMCdim}{shape}{square,oval,form,none}{\def\AMC@shapename{#1}}
496 \define@key{AMCdim}{size}{\AMC@boxedwidth=#1\AMC@boxedheight=#1}
497 \define@key{AMCdim}{height}{\AMC@boxedheight=#1}
498 \define@key{AMCdim}{width}{\AMC@boxedwidth=#1}
499 \define@key{AMCdim}{rule}{\AMC@boxedrule=#1}
500 \define@key{AMCdim}{outsidesep}{\AMC@outside@sep=#1}
501 \define@key{AMCdim}{down}{\AMC@boxeddown=#1}
502 \define@key{AMCdim}{color}{\def\AMC@boxcolor{#1}}
503 \define@boolkey{AMCdim}{cross}[false]{}
504 \define@key{AMCdim}{crosschar}[\textbf{\textsf{X}}]{\def\AMC@crosschar{#1}}
505 \define@key{AMCdim}{crossrule}[1.5pt]{\AMC@crossrule=#1}
506 \def\AMC@shapeprepare{\csname AMC@shapeprepare@\AMC@shapename@ \endcsname}
507 \def\AMCboxStyle#1{%
508   \setkeys{AMCdim}{#1}%
509   \ifnum\AMC@boxedwidth<\AMC@boxedheight%
510     \AMC@oval@radius=\AMC@boxedwidth\divide\AMC@oval@radius\tw@%
511   \else%
512     \AMC@oval@radius=\AMC@boxedheight\divide\AMC@oval@radius\tw@%
513   \fi%
514   \AMC@shapeprepare%
515 }
516 \AMCboxStyle{shape=square,size=2.5ex,down=.4ex,rule=.5pt,outsidesep=.1em,color=black,cross,crosschar,crossrule}
517 \newcommand\AMCboxColor[1]{\AMCboxStyle{color=#1}}
518 \let\AMCboxDimensions=\AMCboxStyle

```

\AMCboxOutsideLetter Command `\AMC@box{<char>}{<answer>}` prints a box with character `<char>` inside, showing an answer `<answer>` (`\AMC@checkbox` to get a filled box), using global variables to identify the box (`\AMC@formBox@` (question and choice).

\AMC@formBox It calls `\AMC@formBox@{<char>}{<answer>}{<trace>}{<key>}` to actually render the box.

outsideLabelFormat Command `\AMC@formBox` simply sets the first argument when empty before calling `\AMC@formBox@`. The command `\AMCboxOutsideLetter{<box>}{<char>}` is called to print the box *and* the character `<char>` outside (and next to) it. The character is formatted using `\AMCoutsideLabelFormat` first: if you need bold characters, redefine it with `\def\AMCoutsideLabelFormat#1{\textbf{#1}}`

`\AMC@keyBox@` is used instead of `\AMCformBox@` when the text that corresponds to the answer is the letter/character inside the box itself (see `\AMCcodeGrid` and `\AMCnumericChoices`.

```

519 \def\AMCoutsideLabelFormat#1{#1}
520 \newcommand\AMCboxOutsideLetter[2]{#1\nobreak\hspace{.1em}\AMCoutsideLabelFormat{#2}}
521 \newif\ifAMC@printformoutside@%
522 \newcommand\ifAMC@printformoutside{%
523   \AMC@printformoutside@false%
524   \ifAMC@ensemble\ifAMC@outside@box%
525     \ifAMCformulaire@dedans\AMC@printformoutside@true\fi%
526     \ifAMC@zoneformulaire\AMC@printformoutside@true\fi%
527   \fi\fi%
528   \ifAMC@printformoutside@%

```

```

529 }
530 \newcommand\AMC@formBox@[4]{%
531   \ifAMC@printformoutside% letter to be written outside the box
532     \AMCboxOutsideLetter{\AMC@answerBox@{#2}{#3}{#4}}{#1}%
533   \else%
534     \AMC@answerBox@{#1}{#2}{#3}{#4}%
535   \fi%
536   \AMC@tracechar{#1}{#2}{#3}{#4}%
537 }
538 \newif\ifAMC@printkeyoutside%
539 \newcommand\ifAMC@printkeyoutside{%
540   \AMC@printkeyoutside@false%
541   \ifAMC@ensemble%
542     \ifAMC@outside@box\AMC@printkeyoutside@true\fi%
543   \else%
544     \ifAMC@inside@box\else\AMC@printkeyoutside@true\fi%
545   \fi%
546   \ifAMC@printkeyoutside@%
547 }
548 \newcommand\AMC@keyBox@[4]{%
549   \ifAMC@printkeyoutside%
550     \AMCboxOutsideLetter{\AMC@answerBox@{#2}{#3}{#4}}{#1}%
551   \else%
552     \AMC@answerBox@{#1}{#2}{#3}{#4}%
553   \fi%
554   \AMC@tracechar{#1}{#2}{#3}{#4}%
555 }
556 \newcommand\AMC@formBox[4]{%
557   \AMC@formBox@{\ifx\@empty#1\@empty%
558     \AMCchoiceLabel{\AMC@ncase}%
559     \else #1\fi}{#2}{#3}{#4}%
560 }
561 \newcommand{\AMC@box}[2]{%
562   \ifAMC@ensemble%
563     \ifAMC@zoneformulaire% for codes inside form sheet
564       \protect\AMC@formBox{#1}{#2}{1}{case:\AMCid@name:\the\AMCid@quest,\the\AMCrep@count}%
565     \else%
566       \ifAMCformulaire@dedans% for answer boxes inside form sheet
567         \protect\AMC@formBox{#1}{#2}{1}{case:\AMCid@name:\the\AMCid@quest,\the\AMCrep@count}%
568       \else% outside form sheet: not to be read during data capture
569         \AMC@formBox{#1}{#2}{1}{casequestion:\AMCid@name:\the\AMCid@quest,\the\AMCrep@count}%
570       \fi\fi%
571   \else% no separate sheet for answers: always read
572     \ifAMC@inside@box%
573       \AMC@formBox{#1}{#2}{1}{case:\AMCid@name:\the\AMCid@quest,\the\AMCrep@count}%
574     \else%
575       \AMC@formBox@{#2}{1}{case:\AMCid@name:\the\AMCid@quest,\the\AMCrep@count}%
576     \fi%
577   \fi%
578 }

```

4.8.4 Scoring zones

`\AMCscoreZone` The source file can define zones that will be used to print scores when annotating the completed answer sheets. The command `\AMCscoreZone{<zone>}` logs these zones positions on the page.

```

579 \newif\ifAMCsz@logged\AMCsz@loggedfalse
580 \newcommand{\AMCscoreZone}[1]{%
581   \ifAMC@ensemble%
582     \ifAMCformulaire@dedans%
583       \AMC@tracebox{1}{score::\the\AMCid@quest,-1}{#1}%
584     \else%
585       \AMC@tracebox{1}{scorequestion::\the\AMCid@quest,-1}{#1}%
586     \fi%
587   \else%
588     \AMC@tracebox{1}{score::\the\AMCid@quest,-1}{#1}%
589   \fi%
590   \ifAMCsz@logged\else%
591     \AMC@amclog{AUTOQCM[VAR:scorezones=1]^^J}%
592     \global\AMCsz@loggedtrue%
593   \fi%
594 }
```

4.8.5 Binary boxes

The package prints on each page some boxes that code (like binary digits) student sheet number, page number and a check number, so as to be read easily from scans after exam.

`\AMCid@checkmax` The check number is just decreased each page. Its maximum value is `\AMCid@checkmax`.
`\AMC@NCBetud` The number of binary digits used to print student sheet number, page and check number are `\AMC@NCBetud`, `\AMC@NCBpage` and `\AMC@NCBcheck`. The number of the first page is `\AMC@NCBcheck`.
`\AMC@premierecopie`

The length of zone reserved for binary boxes is `\AMC@CBtaille`.

```

595 \def\AMCid@checkmax{60}
596 \def\AMC@NCBetud{12}
597 \def\AMC@NCBpage{6}
598 \def\AMC@NCBcheck{6}
599 \newlength{\AMC@CBtaille}\setlength{\AMC@CBtaille}{5cm}
600 \def\AMC@premierecopie{1}
```

`\AMC@binaryCode` The command `\AMC@binaryCode{<options>}{<n>}` prints boxes to represent the number `<n>` in its binary form. Options from `<options>` include:

`ndigits=<ndigits>` for the number of digits to be shown.

`id=<id>` for an ID of the number role (1 for the student number, 2 for the page number, 3 for the checking value).

`hsep=<hsep>` for the space between boxes.

`style=<style>` for some box style options.

`\AMCbin@one` and `\AMCbin@zero` print individual digit-boxes.

For example, `\AMC@binaryCode{ndigits=12}{367}` shows $367 = 000101101111_2$ using 12 boxes:



```

601 \newtoks\AMCbin@sequence
602 \newcount\AMCbin@number
603 \newcount\AMCbin@digit
604 \newcount\AMCbin@id
605 \newcount\AMCbin@did
606 \newcount\AMCbin@endigits
607 \newdimen\AMCbin@hsep
608 \define@key{AMCbin}{ndigits}{\AMCbin@endigits=#1}
609 \define@key{AMCbin}{id}{\AMCbin@id=#1}
610 \define@key{AMCbin}{hsep}{\AMCbin@hsep=#1}
611 \define@key{AMCbin}{style}[]{\def\AMCbin@style{#1}}
612 \def\AMCbin@one{%
613   \ifnum\AMCbin@did>\z@%
614     \hspace{\AMCbin@hsep}%
615     \fi%
616     \advance\AMCbin@did\@ne%
617     \ifnum\AMCbin@id>0%
618       \AMC@ansBox@{\AMC@checkbox}{1}{chiffre:\the\AMCbin@id,\the\AMCbin@did}%
619       \else%
620       \AMC@ansBox@{\AMC@checkbox}{1}{}%
621       \fi}
622 \def\AMCbin@zero{%
623   \ifnum\AMCbin@did>\z@%
624     \hspace{\AMCbin@hsep}%
625     \fi%
626     \advance\AMCbin@did\@ne%
627     \ifnum\AMCbin@id>0%
628       \AMC@ansBox@{}{1}{chiffre:\the\AMCbin@id,\the\AMCbin@did}%
629       \else%
630       \AMC@ansBox@{}{1}{}%
631       \fi}
632 \newcommand{\AMC@binaryCode}[2]{%
633 \setkeys{AMCbin}{ndigits=1,hsep=0pt,style}\setkeys{AMCbin}{#1}%
634 \AMCbin@did=\z@%
635 {\AMCboxDimensions{shape=square,size=.32cm,down=0pt,rule=.2pt,cross=false}\expandafter\AMCboxDimensions}%
636 \AMCbin@digit=\z@%
637 \loop%
638 \ifnum\AMCbin@number>\z@%
639 \advance\AMCbin@digit\@ne%
640 \ifodd\AMCbin@number\AMCbin@sequence=\expandafter{\expandafter\AMCbin@one\the\AMCbin@sequence}%
641 \else\AMCbin@sequence=\expandafter{\expandafter\AMCbin@zero\the\AMCbin@sequence}\fi%
642 \divide\AMCbin@number\tw@%
643 \repeat%
644 \loop\relax%
645 \ifnum\AMCbin@digit<\AMCbin@endigits\advance\AMCbin@digit\@ne%
646 \AMCbin@sequence=\expandafter{\expandafter\AMCbin@zero\the\AMCbin@sequence}\repeat%
647 \the\AMCbin@sequence%
648 \ifnum\AMCbin@digit>\AMCbin@endigits\PackageError{automultiplechoice}{Too low AMC@NCB value (got \the\AMCbin@digit)}{}
649 }

```

The commands `\AMCbin@begin` and `\AMC@binaryBoxes` are now unused and are defined for backward compatibility.

```

650 \def\AMCbin@begin#1{\setkeys{AMCbin}{id=#1}}
651 \newcommand{\AMC@binaryBoxes}[2][1]{%
652 \AMC@binaryCode{ndigits=#1}{#2}%
653 }

```

4.9 Checking Environment

`\AMCcurrentenv` Sets the current environment as document.

```

654 \def\AMCcurrentenv{document}

```

`\AMCif@env` Checks for the current environment.

```

655 \def\AMCif@env#1{
656   \def\AMC@tempenv{#1}%
657   \ifx\AMC@tempenv\AMCcurrentenv
658     \expandafter\@firstoftwo
659   \else
660     \expandafter\@secondoftwo
661   \fi
662 }

```

4.10 Handling groups of questions

The package allows to handle groups of questions, so as to be able to shuffle them before printing them to the sheets.

`\nouveaugroupe` Command `\nouveaugroupe{<group-name>}{<n>}` creates a new (empty) group with name `<group-name>` (argument `<n>` is present only for compatibility reasons and is ignored). Command `\element{<group-name>}{<text>}` adds to group `<group-name>` a new element that contains `<text>`. `<text>` can be a `question` environment, ore two successive `questions` to be kept together, or anything else. Calling command `\nouveaugroupe` is not compulsory, as `\element` calls it if necessary.

```

663 \newcount\AMCtok@k
664 \newcount\AMCtok@max
665 \newcount\AMCtok@size
666 \newcommand{\nouveaugroupe}[2]{%
667   \expandafter\ifx\csname #1@k\endcsname\relax%
668     \expandafter\newcount\csname #1@k\endcsname%
669     \expandafter\newcount\csname AMC#1@j\endcsname%
670     \csname #1@k\endcsname=\z@\relax%
671     \csname AMC#1@j\endcsname=\z@\relax%
672     \setgroupmode{#1}{\AMCdefault@groupmode}%
673   \fi%
674 }
675 \newcommand\AMC@prepare@element[1]{%
676   \nouveaugroupe{#1}{}%
677   \global\advance\csname #1@k\endcsname\@ne\relax%
678   \AMCtok@k=\csname #1@k\endcsname%
679   \expandafter\ifx\csname #1@romannumeral\AMCtok@k\endcsname\relax%
680     \expandafter\newtoks\csname #1@romannumeral\AMCtok@k\endcsname\fi%
681 }
682 \newcommand{\element}[2]{%
683   \AMC@prepare@element{#1}%

```

```

684 \global\csname #1@\romannumeral\AMCtok@k\endcsname={#2}%
685 }

```

`\setgroupmode` Command `\setgroupmode{<group-name>}{<mode>}` sets the group mode to `<mode>` for group `<group-name>`. This mode setup the behaviour of `\insertgroup` and `\copygroup` for this group:

1. With mode **fixed**, group's elements will be taken from the beginning.
2. With mode **cyclic**, the elements will be taken from the group following the last call group's use, recycling if necessary.
3. Mode **withreplacement** is the same as **fixed**, but the group is shuffled before each use.
4. Mode **withoutreplacement** is like **cyclic**, adding some shuffling when coming back to the beginning of the group.

The command `\setdefaultgroupmode{<mode>}` sets the group mode to be used for the following created groups (a group is created at the first `\element{<group>}` call). When no `\setdefaultgroupmode` is used, **fixed** is the default mode.

```

686 \def\AMCdefault@groupmode{fixed}
687 \newcommand{\setdefaultgroupmode}[1]{\def\AMCdefault@groupmode{#1}}
688 \newcommand{\setgroupmode}[2]{%
689   \expandafter\ifx\csname AMCgrouppre@#2\endcsname\relax%
690     \PackageError{automultiplechoice}{Unknown group mode for #1 : #2}%
691     {You asked to set group '#1' mode to '#2',
692      but '#2' is not a valid group mode}%
693   \else%
694     \expandafter\global\expandafter\def\csname AMC#1@mode\endcsname{#2}%
695   \fi%
696 }

```

The functions `\AMCgrouppre@xxx{<group-name>}{<n>}{<i>}` are called before using `<n>` elements from group `<group-name>` starting from index `<i>` (negative value for `<i>` stands for the current value of the group index), either with `\insertgroup` or `\copygroup`.

For mode **fixed**, the group index is set to `<i>`, or 0 if `<i>` is negative (take elements from the beginning).

```

697 \newcommand{\AMCgrouppre@fixed}[3]{%
698   \ifnum#3<\z@%
699     \csname AMC#1@j\endcsname=\z@%
700   \else%
701     \csname AMC#1@j\endcsname=#3%
702   \fi%
703 }

```

For mode **withreplacement**, the group is shuffled and the group index is set to `<i>` or 0 (take elements from the beginning) if negative.

```

704 \newcommand{\AMCgrouppre@withreplacement}[3]{%
705   \ifnum#3<\z@%
706     \csname AMC#1@j\endcsname=\z@%
707   \else%
708     \csname AMC#1@j\endcsname=#3%
709   \fi%
710   \shufflegroup{#1}%
711 }

```

For mode **withoutreplacement**, the group index is set to $\langle i \rangle$, or left unchanged if $\langle i \rangle$ is negative. If there is not enough elements left in the group, the elements before the index and the elements after the index are shuffled.

```

712 \newcount\AMC@imax
713 \newcommand{\AMCgrouppre@withoutreplacement}[3]{%
714   \ifnum#3<\z@%
715   \else%
716     \csname AMC#1@j\endcsname=#3%
717   \fi%
718   \ifnum\AMCtok@ik=\AMCloop@k%
719     \AMCtok@ik=\z@%
720   \fi%
721   \ifnum\AMCtok@ik=\z@%
722     \shufflegroup{#1}%
723   \else%
724     \AMC@imax=\AMCloop@k%
725     \advance\AMC@imax -#2\relax%
726     \ifnum\AMCtok@ik>\AMC@imax%
727       \shufflegroupslice{#1}{\@ne}{\AMCtok@ik}%
728       \ifnum\AMCtok@ik<\AMCloop@k%
729         \advance\AMCtok@ik\@ne%
730         \shufflegroupslice{#1}{\AMCtok@ik}{\AMCloop@k}%
731       \fi%
732     \fi%
733   \fi%
734 }
```

For mode **cyclic**, nothing has to be done, except setting the group index if non-negative.

```

735 \newcommand{\AMCgrouppre@cyclic}[3]{%
736   \ifnum#3<\z@%
737   \else%
738     \csname AMC#1@j\endcsname=#3%
739   \fi%
740 }
```

The function `\AMCgroup@pre{<mode>}{<group-name>}{<n>}{<i>}` calls the right `\AMCgrouppre@xxx` command.

```

741 \newcommand{\AMCgroup@pre}[4]{%
742   \csname AMCgrouppre@#1\endcsname{#2}{#3}{#4}%
743 }
```

`\shufflegroup` Command `\shufflegroup{<group-name>}` shuffles the elements of group $\langle group-name \rangle$, and `\insertgroup` `\shufflegroupslice{<group-name>}{<a>}{}` shuffles elements $\langle a \rangle$ to $\langle b \rangle$ from group $\langle group-name \rangle$. `\insertgroupfrom` It can be called at each student sheet in order to get different student sheets and avoid cheating.

Command `\insertgroup[<n>]{<groupname>}` inserts all the elements of group $\langle groupname \rangle$, or only the first $\langle n \rangle$ elements if $\langle n \rangle$ is given. `\insertgroupfrom[<n>]{<groupname>}{<i>}` inserts all the elements of group $\langle groupname \rangle$ starting from index $\langle i \rangle$ (the index of the first element is 0), or only the first $\langle n \rangle$ elements if $\langle n \rangle$ is given.

```

744 \newcommand{\shufflegroup}[1]{%
745   \ifAMC@shuffleG{\AMC@shuffletoks{\number\csname #1@k\endcsname}{#1@}}\fi%
746 }
747 \newcommand{\shufflegroupslice}[3]{%
748   \ifAMC@shuffleG{\AMC@shuffletoks[#2]{#3}{#1@}}\fi%
```

```

749 }
750 \newcount\AMCtok@ik
751 \newcount\AMCloop@k
752 \newcommand{\AMCgrouploop@prep}[3]{%
753   \AMCtok@size=#1\relax%
754   \ifAMC@fullGroups\AMCtok@size=\z@\fi%
755   \ifnum\AMCtok@size<\@ne%
756     \AMCtok@size=\csname #2@k\endcsname%
757   \fi%
758   \AMCtok@ik=\csname AMC#2@j\endcsname%
759   \AMCloop@k=\csname #2@k\endcsname%
760   \expandafter\ifx\csname AMC#2@mode\endcsname\relax%
761     \PackageError{automultiplechoice}{No group mode for #2}%
762     {No mode has been defined for group '#2'. This should not occur...}%
763   \fi%
764   \AMCgroup@pre{\csname AMC#2@mode\endcsname}{#2}{\the\AMCtok@size}{#3}%
765 }
766 \newcommand{\AMCgrouploop@next}[1]{%
767   \global\advance\csname AMC#1@j\endcsname\@ne\relax%
768   \expandafter\ifnum\csname AMC#1@j\endcsname>\AMCloop@k\relax%
769     \global\csname AMC#1@j\endcsname=\@ne%
770   \fi%
771   \AMCtok@ik=\csname AMC#1@j\endcsname%
772   \advance\AMCtok@size\m@ne%
773 }
774 \newcommand{\insertgroupfrom}[3][0]{%
775   \AMCgrouploop@prep{#1}{#2}{#3}%
776   {\loop%
777     \AMCgrouploop@next{#2}%
778     {\the\csname #2@romannumeral\AMCtok@ik\endcsname}%
779     \ifnum\AMCtok@size>\z@\repeat}%
780 }
781 \newcommand{\insertgroup}[2][0]{%
782   \insertgroupfrom{#1}{#2}{-1}%
783 }

```

\cleargroup The commands **\cleargroup** and **\copygroup** can also be used to make more complex questions combinations in the exams, allowing for example to ask the package to shuffle 3 questions taken at random from group **groupa** and 5 questions taken at random from group **groupb**.

\cleargroup{<group>} clears the group **<group>**, erasing all of its elements.

\copygroup[<n>]{<from>}{<to>} copies **<n>** elements from group **<from>** to group **<to>**. If optional parameter **<n>** is not given, all the questions from group **<from>** are copied.

\copygroupfrom[<n>]{<from>}{<to>}{<i>} copies **<n>** elements from group **<from>** to group **<to>**, starting from element at index **<i>** (the index of the first element is 0). If optional parameter **<n>** is not given, all the questions from group **<from>** are copied.

See section 3.4 for an illustration for these commands.

```

784 \newcommand{\cleargroup}[1]{%
785   \nouveaugroupe{#1}{}%
786   \csname #1@k\endcsname=\z@\relax%
787   \csname AMC#1@j\endcsname=\z@\relax%
788 }
789 \newcommand{\copygroupfrom}[4][0]{%
790   \AMCgrouploop@prep{#1}{#2}{#4}%

```

```

791 {\loop%
792   \AMCgrouploop@next{#2}%
793   \AMC@prepare@element{#3}%
794   \global\csname #3@\romannumeral\AMCtok@k\endcsname=\csname #2@\romannumeral\AMCtok@ik\endcsname%
795   \ifnum\AMCtok@size>\z@\repeat}%
796 }
797 \newcommand{\copygroup}[3][0]{%
798   \copygroupfrom[#1]{#2}{#3}{-1}%
799 }

```

4.11 Questions

To manage multiple choice questions, first set some counters and token registers to handle answers. Token registers `\reponse@i`, `\reponse@ii` and so on will be used for answers – we restrict the number of answers of a single questions to `\AMCload@counter = 199`.

```

800 \newcount\AMCrep@count
801 \AMCload@counter=199
802 \@whilenum\AMCload@counter>0\do{%
803   \expandafter\newtoks\csname reponse@\romannumeral\AMCload@counter\endcsname%
804   \advance\AMCload@counter@m@ne%
805 }

```

`\AMCload@reponse` Command `\AMCload@reponse{<n>}{<text>}` will be used to add answer number `<n>` with text `<text>` (`<text>` will include the box to be ticked and all the layout commands) to the set of answers (in a token register `\reponse@xxx` – counter `\AMCload@counter` keeps track of the number of answers), in order to shuffle them when all answers will be loaded.

When answers are not to be shuffled, command `\AMCrien@deux{<n>}{<text>}` will be used instead, only printing `<text>`.

```

806 \newcommand\AMCload@reponse[2]{%
807   \global\advance\AMCload@counter\@ne\relax%
808   \global\csname reponse@\romannumeral\AMCload@counter\endcsname%
809   =\expandafter{\expandafter\AMCrep@count\expandafter=#2 #1}%
810 }
811 \newcommand\AMCrien@deux[2]{#1}

```

`\shuffle@it` After loading all answers, commands `\shuffle@it` will be used to shuffle them, and `\AMCdump@reponses` to print them.

```

812 \def\shuffle@it{\AMC@shuffletoks{\number\AMCload@counter}{reponse@}}
813 \newcount\AMCnum@questions
814 \newcommand\AMCdump@reponses{%
815   \global\AMCnum@questions=\AMCload@counter%
816   \@whilenum\AMCload@counter>0\do{%
817     \the\csname reponse@\romannumeral\AMCload@counter\endcsname%
818     \advance\AMCload@counter@m@ne}}

```

4.11.1 Managing answers

`\lastchoices` Command `\AMCrep@init{<mode>}` is called for each question before reading answers. `<mode>` `\AMCrep@init` is `r` for suffled answers, and `o` if answers are not to be shuffled. It sets the number of answers counter to zero, and calls `\AMCrep@o` or `\AMCrep@r` depending on `<mode>`. These commands sets `\AMCload@@reponse` and `\AMCrep@fini` that will be called for each answer and after the last answer respectively, depending on `<mode>`:

- If $\langle mode \rangle = r$, $\backslash\text{AMCload}@\text{reponse}$ is $\backslash\text{AMCload}@\text{reponse}$ (loads answer to token register) and $\backslash\text{AMCrep}@\text{fini}$ calls $\backslash\text{shuffle}@\text{it}$ and $\backslash\text{AMCdump}@\text{reponses}$;
- If $\langle mode \rangle = o$, $\backslash\text{AMCload}@\text{reponse}$ is $\backslash\text{AMCrien}@\text{deux}$ (prints answer directly) and $\backslash\text{AMCrep}@\text{fini}$ does nothing.

Command $\backslash\text{lastchoices}$ is called before giving answers that are to be printed at the end (even when shuffling answers). It closes the answers list calling $\backslash\text{AMCrep}@\text{fini}$ and opens another one in ordered mode. Note that it also saves the value of $\backslash\text{AMCrep}@\text{count}$, which is the number of the current answer among all answers given in the subject source for the current question.

Command $\backslash\text{AMC}@\text{fin}@\text{rep}$ is to be called after the last answer: it adds a “None of these answers are correct.” answer if necessary (package option `completemulti`) with answer number zero, and calls $\backslash\text{AMCrep}@\text{fini}$.

```

819 \newcommand\AMCrep@init[1]{%
820   \ifAMC@ordre\AMCrep@o\else%
821     \csname AMCrep@#1\endcsname\fi\AMCload@counter=\z@}
822 \newcommand\AMCrep@o{%
823   \def\AMCload@reponse{\AMCrien@deux}\def\AMCrep@fini{}}
824 \newcommand\AMCrep@r{%
825   \def\AMCload@reponse{\AMCload@reponse}%
826   \def\AMCrep@fini{\shuffle@it\AMCdump@reponses}}
827 \newcount\AMCrep@count
828 \newcommand\lastchoices{%
829   \AMCrep@count=\AMCrep@count%
830   \AMCrep@fini\AMCrep@init{o}%
831   \AMCrep@count=\AMCrep@count}
832 \newcommand\@aucune{\emph{\AMC@loc@none}}
833 \newcommand\AMC@fin@rep{%
834   \ifAMCcomplete@multi\ifAMCtype@multi%
835     \lastchoices\AMCrep@count=-1%
836     \ifAMCune@bonne\wrongchoice{\@aucune}\else%
837       \ifAMC@postcorrect\wrongchoice{\@aucune}\else\correctchoice{\@aucune}\fi%
838     \fi\fi\fi\AMCrep@fini}

```

4.11.2 Separate answer sheet

This package needs some memory to print questions/answers boxes again on a separate answer sheet.

$\backslash\text{AMCformQuestion}$ First define commands that will announce questions and answers on the separate answer sheet
 $\backslash\text{AMCformAnswer}$ (these commands can be modified by the user): $\backslash\text{AMCformQuestion}\{\langle number \rangle\}$ is responsible for announcing question, and $\backslash\text{AMCformAnswer}\{\langle box \rangle\}$ is responsible for printing the box to be ticked, given as argument $\langle box \rangle$.

Commands $\backslash\text{AMCformQuestionA}$ and $\backslash\text{AMCformAnswerA}$ set up counter $\backslash\text{AMC}@\text{ncase}$ value before calling their counterparts.

```

839 \def\AMCformBeforeQuestion{\vspace{\AMCformVSpace}\par}
840 \def\AMCformAfterQuestion{\ifAMC@asqbloc\egroup\fi}
841 \def\AMCformQuestion#1{\AMC@loc@qf{#1}}
842 \def\AMCformQuestionN{\AMCformQuestion{\AMC@qaff}}
843 \def\AMCformQuestionA{%
844   \setcounter{AMC@ncase}{0}%
845   \AMCformBeforeQuestion%

```

```

846 \ifAMC@asqbloc\vbox\bgroup\fi%
847 \ifx\@empty\AMC@sza@callout\@empty\else%
848 \csname\AMC@sza@callout\endcsname%
849 \fi%
850 \AMCformQuestionN%
851 \ifx\@empty\AMC@sza@callin\@empty\else%
852 \csname\AMC@sza@callin\endcsname%
853 \fi%
854 }
855 \def\AMCformAnswer#1{\hspace{\AMCformHSpace} #1}
856 \def\AMCformAnswerA#1{\addtocounter{AMC@ncase}{1}\AMCformAnswer{#1}}

```

`C@mem@add@ifneeded` These are commands to manage memory for separate answer sheet. `\AMC@mem@add@ifneeded{<code>}`

`\AMCformBegin` adds `<code>` to this memory. `\AMC@mem@answer{<code>}` adds to memory answer code `<code>`, and

`\AMCform` `\AMC@mem@openQuestion` adds to memory question code to announce current question.

`\AMCformS` The command `\AMCformBegin` defines the beginning of the separate answer sheet for the current student sheet, and `\AMCform` prints the whole memory: questions and answers boxes.

`\AMCformS` is a `\AMCform` variant that does not clear the list of answer boxes. It can be used to make the same exact subject for all students, displaying the questions before (outside) `onecopy`, so that `onecopy` contains only the answer sheet.

```

857 \ExplSyntaxOn
858
859 \prg_set_conditional:Nnn \amc_if_separate_question: { p , T } {
860 \ifAMC@ensemble
861 \ifAMC@zoneformulaire
862 \prg_return_false:
863 \else
864 \prg_return_true:
865 \fi
866 \else
867 \prg_return_false:
868 \fi
869 }
870 \cs_new_eq:NN \AMC@if@separate@question \amc_if_separate_question:T
871
872 \int_new:N \amc_memory_elts_count
873
874 \cs_new:Nn \amc_clear_memory: { \int_gzero:N \amc_memory_elts_count }
875 \cs_new_eq:NN \AMC@mem@clear \amc_clear_memory:
876
877 \cs_new:Npn \amc_memory_elt_i:n #1 {
878 amc_memory_elts_ \int_to_alph:n { #1 }
879 }
880 \cs_new:Nn \amc_memory_current_elt: {
881 \amc_memory_elt_i:n \amc_memory_elts_count
882 }
883 \cs_new:Npn \amc_memory_vars_i:n #1 {
884 amc_memory_vars_ \int_to_alph:n { #1 }
885 }
886 \cs_new:Nn \amc_memory_current_vars: {
887 \amc_memory_vars_i:n \amc_memory_elts_count
888 }

```



```

889
890 \cs_new:Nn \amc_add_memory_elt: {
891   \int_gincr:N \amc_memory_elts_count
892   \tl_gclear_new:c { \amc_memory_current_elt: }
893   \tl_gclear_new:c { \amc_memory_current_vars: }
894 }
895 \cs_new_eq:NN \AMC@mem@next \amc_add_memory_elt:
896
897 \cs_new:Npn \amc_add_to_memory:n #1 {
898   \tl_gput_right:cn { \amc_memory_current_elt: } { #1 }
899 }
900 \cs_new_eq:NN \AMC@mem@add \amc_add_to_memory:n
901
902 \cs_new:Npn \amc_add_to_vars:n #1 {
903   \tl_gput_right:cn { \amc_memory_current_vars: } { #1 }
904 }
905 \cs_new_eq:NN \AMC@mem@addvar \amc_add_to_vars:n
906
907 \cs_new:Npn \amc_add_qidaffname:nnn #1#2#3 {
908   \amc_add_to_vars:n {\AMCid@quest=#1\setcounter{AMCquestionaff}{#2}%
909     \global\def\AMCid@name{#3}}
910 }
911 \cs_generate_variant:Nn \amc_add_qidaffname:nnn { xxx }
912 \cs_new_eq:NN \AMC@mem@qidaffname \amc_add_qidaffname:xxx
913
914 \cs_new:Npn \amc_mem_elt_cat:n #1 {
915   \amc_add_to_vars:n { \def\AMCmem@elt@cat{ #1 } }
916 }
917 \cs_generate_variant:Nn \amc_mem_elt_cat:n { x }
918 \cs_new_eq:NN \AMC@mem@category \amc_mem_elt_cat:x
919
920 \cs_new:Npn \amc_add_aid:n #1 {
921   \amc_add_to_memory:n {\AMCrep@count=#1}
922 }
923 \cs_generate_variant:Nn \amc_add_aid:n { x }
924 \cs_new_eq:NN \AMC@mem@aid \amc_add_aid:x
925
926 \cs_new:Npn \amc_if_category_is_p:n #1 {
927   \str_if_eq_p:on { \AMCmem@elt@cat } { #1 }
928 }
929 \cs_new:Npn \amc_use_memory:n #1 {
930   \int_step_inline:nnnn { 1 } { 1 } \amc_memory_elts_count {
931     \def\AMCmem@elt@cat{ plain }
932     \tl_use:c { \amc_memory_vars_i:n { ##1 } }
933     \bool_if:nTF { #1 } {
934       \tl_use:c { \amc_memory_elt_i:n { ##1 } }
935     } { }
936   }
937 }
938 \cs_new:Nn \amc_use_memory: { \amc_use_memory:n { \c_true_bool } }
939 \cs_new_eq:NN \AMC@mem@show \amc_use_memory:
940 \cs_new_eq:NN \AMC@mem@show@filter \amc_use_memory:n
941 \cs_new_eq:NN \AMCifcategory \amc_if_category_is_p:n

```

```

942
943 \ExplSyntaxOff
944 \newcommand\AMC@mem@add@ifneeded[1]{%
945   \AMC@if@separate@question{%
946     \AMC@mem@add{#1}%
947   }%
948 }
949 \newcommand\AMC@mem@addsingle@ifneeded[2]{%
950   \AMC@if@separate@question{%
951     \AMC@mem@next%
952     \AMC@mem@category{#2}%
953     \AMC@mem@add{#1}%
954   }%
955 }
956 \newcommand\AMC@mem@answer[1]{%
957   \addtocounter{AMC@ncase}{1}%
958   \AMC@if@separate@question{%
959     \AMC@mem@aid{\the\AMC@rep@count}%
960     \AMC@mem@add{\AMCformAnswerA{#1}}%
961   }%
962 }
963 \newcommand\AMC@mem@openQuestion{%
964   \AMC@if@separate@question{%
965     \AMC@mem@next%
966     \AMC@mem@qidaffname{\the\AMC@id@quest}{\arabic{AMC@questionaff}}{\AMC@id@name}%
967     \AMC@mem@add{\AMCformQuestionA}%
968   }%
969 }
970 \def\AMCformBegin{%
971   \AMC@zone@formulaire@true\setcounter{section}{0}%
972   \ifAMC@ensemble\ifAMC@automarks\pagestyle{AMC@pageFull}\fi\fi%
973 }
974 \newcommand\AMCform{%
975   \ifAMC@ensemble\AMC@formulaire@dedan@true%
976     \AMC@mem@show%
977   \fi}
978 \newcommand\AMCformFilter[1]{%
979   \ifAMC@ensemble\AMC@formulaire@dedan@true%
980     \AMC@mem@show@filter{#1}%
981   \fi}
982 \newif\ifAMC@keepmemory
983 \newcommand\AMCformS{%
984   \ifAMC@ensemble\AMC@formulaire@dedan@true%
985     \AMC@amclog{AUTOQCM[BR=0]^^J}\AMC@mem@show%
986     \global\AMC@keepmemorytrue%
987   \fi}

```

`\AMCsection` The `\AMCsection` and `\AMCsubsection` commands issue their standard counterparts (`\section` and `\subsection` with the same argument, both in the subject *and* in the separate answer sheet.

```

988 \newcommand{\AMCsectionNumbered}[1]{%
989   \section{#1}\AMC@mem@addsingle@ifneeded{\section{#1}}{section}}
990 \newcommand{\AMCsubsectionNumbered}[1]{%
991   \subsection{#1}\AMC@mem@addsingle@ifneeded{\subsection{#1}}{subsection}}

```

```

992 \newcommand{\AMCsectionStar}[1]{%
993   \section*{#1}\AMC@mem@addsingle@ifneeded{\section*{#1}}{section}}
994 \newcommand{\AMCsubsectionStar}[1]{%
995   \subsection*{#1}\AMC@mem@addsingle@ifneeded{\subsection*{#1}}{subsection}}
996 \def\AMCsection{\@ifstar\AMCsectionStar\AMCsectionNumbered}
997 \def\AMCsubsection{\@ifstar\AMCsubsectionStar\AMCsubsectionNumbered}

```

4.11.3 Formatting answers

`choices` (*env.*) Answers have to be included in an environment `choices` (standard), `choiceshoriz` (answers on one line) or `choicescustom` (user defined) depending on the desired formatting.

`choicescustom` (*env.*) Use `\AMCBoxedAnswers` to request all answers to be included in L^AT_EX boxes; this can be useful for example when using multicolumn answers formatting.

```

tikz-multi (env.) 998 \def\AMCBoxedAnswers{\AMC@rbloctrue}
\AMCBoxedAnswers 999 \newenvironment{choices}[1][r]{%
1000   \AMCrep@count=\z@\def\une@rep{\AMCrep@itemize}%
1001   \ifAMC@rbloc\def\une@rep{\AMCrep@bloc}%
1002   \else\begin{itemize}\setlength{\itemsep}{\AMCinterIrep}\fi%
1003   \AMCrep@init{#1}}%
1004   {\AMC@fin@rep\ifAMC@rbloc\else\end{itemize}\fi}
1005 \newenvironment{choiceshoriz}[1][r]{%
1006   \AMCrep@count=\z@\def\une@rep{\AMCrep@ligne}\AMCrep@init{#1}%
1007   \par\begin{center}}%
1008   {\AMC@fin@rep\end{center}}
1009 \newenvironment{choicescustom}[1][r]{%
1010   \AMCrep@count=\z@\def\une@rep{\AMCrep@perso}\AMCrep@init{#1}%
1011   \AMCbeginAnswer\ignorespaces}%
1012   {\AMC@fin@rep\AMCendAnswer}
1013 \newenvironment{tikz-single}[1][r]{
1014   \AMCrep@count=\z@\def\une@rep{\AMCrep@tikz}\AMCrep@init{#1}%
1015   \begin{tikzpicture}}{\AMC@fin@rep\end{tikzpicture}}
1016 \newenvironment{tikz-multi}[1][r]{
1017   \AMCrep@count=\z@\def\une@rep{\AMCrep@tikzmat}\AMCrep@init{#1}%
1018   \begin{tikzpicture}[remember picture]}{\AMC@fin@rep\end{tikzpicture}}

```

`\AMCrep@bloc` For each of these styles, a corresponding `\AMCrep@xxx{⟨box⟩}{⟨text⟩}` is defined, which will format the answer with a box given in `⟨box⟩` and text `⟨text⟩`. `\AMCrep@bloc` is also defined and used in standard formatting when the user wants to put answers inside a L^AT_EX box.

```

\AMCrep@itemize 1019 \newcommand\AMCrep@bloc[2]{\AMC@mem@answer{#1}%
\AMCrep@ligne 1020   \par%
\AMCrep@perso 1021   \ifAMC@textPos\vbox\bgroup\AMC@tracepos{1}{atext:\AMCid@name:\the\AMCid@quest,\the\AMCrep@count}\hbox{
1022     \noindent\begin{minipage}{\linewidth}%
1023     \begin{itemize}\item[1] #2\end{itemize}\end{minipage}%
1024     \ifAMC@textPos\AMC@tracepos{1}{atext:\AMCid@name:\the\AMCid@quest,\the\AMCrep@count}\egroup\AMC@tra
1025     \vspace{\AMCinterBrep}}
1026   \newcommand\AMCrep@tikz[5]{\AMC@mem@answer{#1}\node[#4] (lab\thecsvrow) at (#3) {#2} node[#5] (box\thecsvrow)
1027   \newcommand\AMCrep@tikzmat[5]{\AMC@mem@answer{#1}\node[#5] (box\thecsvrow) at (#3) {#1} node[#4] (lab\thecsvrow)
1028   \newcommand\AMCrep@itemize[2]{\AMC@mem@answer{#1}\item[1] #2}
1029   \newlength\AMChorizAnswerSep
1030   \setlength{\AMChorizAnswerSep}{3em plus 4em}
1031   \newlength\AMChorizBoxSep
1032   \setlength{\AMChorizBoxSep}{1em}
1033   \newcommand\AMCrep@ligne[2]{\AMC@mem@answer{#1}%

```

```

1034 \ifAMC@textPos%
1035 \mbox{\AMC@tracebox{1}{atext:\AMCid@name:\the\AMCid@quest,\the\AMCrep@count}{#1\hspace*\AMChorizBoxSep}}
1036 \else%
1037 \mbox{#1\hspace*\AMChorizBoxSep}#2}%
1038 \fi\hspace*\AMChorizAnswerSep}}
1039 \newcommand\AMCrep@perso[2]{\AMC@mem@answer{#1}\AMCanswer{#1}{#2}}

```

`\AMCbeginAnswer` The custom style will use user-defined commands to format answers: `\AMCbeginAnswer` is called once before answers, `\AMCanswer{<box>}{<text>}` is called for each answer (`<box>` being the box to be ticked and `<text>` the text associated with the proposed answer), and `\AMCendAnswer` is called after all answers.

```

1040 \def\AMCbeginAnswer{}
1041 \def\AMCanswer#1#2{#1 #2}
1042 \def\AMCendAnswer{}

```

`\answer` The commands `\correctchoice` and `\wrongchoice` are used inside `choices`-like environments to give the proposed answers and specify if they are to be ticked by the students or not.

```

\wrongchoice
1043 \newcommand{\correctchoice}[2][]{\global\advance\AMCrep@count\@ne\relax%
1044 \ifAMC@calibration\AMC@amclog{AUTOQCM[REP=\the\AMCrep@count:B]^^J}\fi%
1045 \global\AMCune@bonnettrue%
1046 \AMCload@@reponse{\une@rep{\ifAMC@correc\AMC@box{#1}{\AMC@checkedbox}%
1047 \else\AMC@box{#1}{\fi}{#2}}{\the\AMCrep@count}\ignorespaces}
1048 \newcommand{\wrongchoice}[2][]{\global\advance\AMCrep@count\@ne\relax%
1049 \ifAMC@calibration\AMC@amclog{AUTOQCM[REP=\the\AMCrep@count:M]^^J}\fi%
1050 \AMCload@@reponse{\une@rep{\AMC@box{#1}{\fi}{#2}}{\the\AMCrep@count}%
1051 \ignorespaces}

```

4.11.4 Score zones

`\AMCscoreZone` The position of the scores on the annotated answer sheets can be defined in the L^AT_EX source file using `\AMCsetScoreZone{<options>}` (or `\AMCsetScoreZoneAnswerSheet{<options>}` for the answer sheets when the separate answer sheet option is used).

First begin with some helpers: `\AMCemptybox{<width>}{<height>}{<depth>}` draws an empty box with specified dimensions, and `\AMCmarginNote{<note>}` (code from one of [sgmoye's](http://tex.stackexchange.com) comments on tex.stackexchange.com) prints a marginal note in the left or right margin, depending on current the position (usefull in `multicols` environment).

```

1052 \newcommand{\AMCemptybox}[3]{%
1053 \sbox0{\wd0=#1\ht0=#2\dp0=#3\relax\box0}}
1054 \newlength\AMC@mn@test
1055 \newlength\AMC@mn@sep\AMC@mn@sep=4mm
1056 \newlength\AMC@mn@leftmargin
1057 \newlength\AMC@mn@rightmargin
1058 \newcommand\AMCmarginNote[1]{%
1059 \begin{tikzpicture}[remember picture,overlay]%
1060 \coordinate (here) at (0,0);%
1061 \pgfextractx{\AMC@mn@test}{\pgfpointdiff{\pgfpointorigin}%
1062 {\pgfpointanchor{current page}{center}}}%
1063 \ifodd\thepage%
1064 \AMC@mn@leftmargin=\oddsidemargin%
1065 \AMC@mn@rightmargin=\evensidemargin%
1066 \else
1067 \AMC@mn@leftmargin=\evensidemargin%

```

```

1068     \AMC@mn@rightmargin=\oddsidemargin%
1069   \fi
1070   \ifdim\AMC@mn@test < 1cm%
1071     \draw (current page.east |- here)+(-\AMC@mn@rightmargin-1in+\AMC@mn@sep,0pt) node[anchor=text,align=right]{\AMC@mn@score}%
1072   \else%
1073     \draw (current page.west |- here)+(0cm,0pt) node[anchor=text,align=right,text width=\AMC@mn@leftmargin]{\AMC@mn@score}%
1074   \fi%
1075   \end{tikzpicture}%
1076 }

```

Define now different ways to place the score zone:

`none` nowhere

`question` right after the question heading

`margin` in the margin, using `marginpar` (this does not work with `multicols` environment)

`margins` in the left or right margin, depending on the current position (needs `tikz` package)

```

1077 \newcommand{\AMC@sz@box}{\AMCemptybox{\AMC@sz@width}{\AMC@sz@height}{\AMC@sz@depth}}
1078 %
1079 \newcommand{\AMC@sz@callin@question}{\AMCscoreZone{\AMC@sz@box}}
1080 %
1081 \newcommand{\AMC@sz@callout@margin}{\hspace{0pt}\marginpar{\AMCscoreZone{\AMC@sz@box}}}
1082 %
1083 \newcommand{\AMC@sz@init@margins}{\PackageWarning{automultiplechoice}{Please run twice to get proper margins}}
1084 \newcommand{\AMC@sz@callout@margins}{\hspace{0pt}\AMCmarginNote{\AMCscoreZone{\AMC@sz@box}}}

```

Let us now set up options handling.

```

1085 \newlength\AMC@sz@width
1086 \newlength\AMC@sz@height
1087 \newlength\AMC@sz@depth
1088 \def\AMC@sz@callout{}
1089 \def\AMC@sz@callin{}
1090 \define@key{AMCsz}{width}{\AMC@sz@width=#1}
1091 \define@key{AMCsz}{height}{\AMC@sz@height=#1}
1092 \define@key{AMCsz}{depth}{\AMC@sz@depth=#1}
1093 \define@key{AMCsz}{calloutsideside}{\def\AMC@sz@callout{#1}}
1094 \define@key{AMCsz}{callinsideside}{\def\AMC@sz@callin{#1}}
1095 \define@choicekey{AMCsz}{position}{none,question,margin,margins}{%
1096   \ifcsname AMC@sz@callout@#1\endcsname%
1097     \def\AMC@sz@callout{\AMC@sz@callout@#1}%
1098   \else%
1099     \def\AMC@sz@callout{}%
1100   \fi%
1101   \ifcsname AMC@sz@callin@#1\endcsname%
1102     \def\AMC@sz@callin{\AMC@sz@callin@#1}%
1103   \else%
1104     \def\AMC@sz@callin{}%
1105   \fi%
1106   \ifcsname AMC@sz@init@#1\endcsname%
1107     \csname AMC@sz@init@#1\endcsname%
1108   \fi%
1109 }

```

```

1110 \newcommand{\AMCsetScoreZone}[1]{\setkeys{AMCsz}{#1}}
1111 \AMCsetScoreZone{width=1.5em,height=1.5ex,depth=.5ex,position=none}

```

And do the same for \AMCsetScoreZoneAnswerSheet...

```

1112 \newcommand{\AMC@sza@box}{\AMCemptybox{\AMC@sza@width}{\AMC@sza@height}{\AMC@sza@depth}}
1113 %
1114 \newcommand{\AMC@sza@init@none}{}
1115 \newcommand{\AMC@sza@callout@none}{}
1116 \newcommand{\AMC@sza@callin@none}{}
1117 %
1118 \newcommand{\AMC@sza@init@question}{}
1119 \newcommand{\AMC@sza@callout@question}{}
1120 \newcommand{\AMC@sza@callin@question}{\AMCscoreZone{\AMC@sza@box}}
1121 %
1122 \newcommand{\AMC@sza@init@margin}{}
1123 \newcommand{\AMC@sza@callout@margin}{\hspace{Opt}\marginpar{\AMCscoreZone{\AMC@sza@box}}}
1124 \newcommand{\AMC@sza@callin@margin}{}
1125 %
1126 \newcommand{\AMC@sza@init@margins}{\PackageWarning{automultiplechoice}{Please run twice to get proper ma}}
1127 \newcommand{\AMC@sza@callout@margins}{\hspace{Opt}\AMCmarginNote{\AMCscoreZone{\AMC@sz@box}}}
1128 \newcommand{\AMC@sza@callin@margins}{}
1129 %
1130 \newlength\AMC@sza@width
1131 \newlength\AMC@sza@height
1132 \newlength\AMC@sza@depth
1133 \def\AMC@sza@callout{}
1134 \def\AMC@sza@callin{}
1135 \define@key{AMC@sza}{width}{\AMC@sza@width=#1}
1136 \define@key{AMC@sza}{height}{\AMC@sza@height=#1}
1137 \define@key{AMC@sza}{depth}{\AMC@sza@depth=#1}
1138 \define@key{AMC@sza}{calloutside}{\def\AMC@sza@callout{#1}}
1139 \define@key{AMC@sza}{callinside}{\def\AMC@sza@callin{#1}}
1140 \define@choicekey{AMC@sza}{position}{none,question,margin,margins}{%
1141   \ifcsname AMC@sza@callout@#1\endcsname%
1142     \def\AMC@sza@callout{\AMC@sza@callout@#1}%
1143   \else%
1144     \def\AMC@sza@callout{}%
1145   \fi%
1146   \ifcsname AMC@sza@callin@#1\endcsname%
1147     \def\AMC@sza@callin{\AMC@sza@callin@#1}%
1148   \else%
1149     \def\AMC@sza@callin{}%
1150   \fi%
1151   \ifcsname AMC@sza@init@#1\endcsname%
1152     \csname AMC@sza@init@#1\endcsname%
1153   \fi%
1154 }
1155 \newcommand{\AMCsetScoreZoneAnswerSheet}[1]{\setkeys{AMC@sza}{#1}}
1156 \AMCsetScoreZoneAnswerSheet{width=1.5em,height=1.5ex,depth=.5ex,position=none}
1157 \newcommand{\AMCnoScoreZone}{\AMCsetScoreZone{position=none}\AMCsetScoreZoneAnswerSheet{position=none}}

```

4.11.5 Formatting questions

`\AMCquestionaff` The counter `\AMCquestionaff` keeps track of the current question number. It can be redefined by the user, for example to print several questions without a number, and then print questions with a number starting at one.

`\AMC@stepQuestion` will increase this counter and `\AMC@qaff` will format the question number out.

```
1158 \newcounter{AMCquestionaff}
1159 \newcommand{\AMCnumero}[1]{\setcounter{AMCquestionaff}{#1}\addtocounter{AMCquestionaff}{-1}}
1160 \AtBeginDocument{%
1161   \ifx\@skiphyperreftrue\@undefined%
1162     \expandafter\newif\csname if@skiphyperref\endcsname%
1163   \fi%
1164 }
1165 \newcommand\AMC@stepQuestion{\ifAMCquestionNumber\@skiphyperreftrue\refstepcounter{AMCquestionaff}\@skip
1166 \newcommand\AMC@qaff{\arabic{AMCquestionaff}}
```

`\AMCbeforeQuestion` The command `\AMCbeforeQuestion` opens a new question. The command `\AMCbeginQuestion{<n>}{<sign>}` will format the question header, where `<n>` is the question number and `<sign>` being `\multiSymbole` in case of a multiple question, and empty in case of a simple one. `\AMCbeforeQuestion`, `\AMCbeginQuestion` and `\multiSymbole` can be user-redifined.

```
1167 \def\AMCbeforeQuestion{\ifAMC@qbloc\else\par\noindent\fi}
1168 \def\AMCbeginQuestion#1#2{\noindent\AMC@loc@q{#1}{#2}%
1169   \ifx\@empty\AMC@sz@callin\@empty\hspace*{1em}\fi%
1170 }
1171 \def\multiSymbole{$\clubsuit$}
```

`question (env.)` Environment `{question}{<key>}` encloses a simple question (with one and only one correct choice) with associated unique key `<key>` and the proposed answers.

`variable-single (env.)` Environment `{questionmult}{<key>}` is the same for multiple questions (with none, one or several correct choices).

`questionouverte (env.)` Environment `{questionmultx}{<key>}` is the same as `questionmult`, but with no use of `\multiSymbole`.

Environment `{questionouverte}[<width>]` is used for open questions (that won't be marked automatically!), with width given as an optional argument (defaults to 3 cm).

```
1172 \ifx\question\undefined\else\let\question\undefined\fi
1173 \def\AMCnobloc{\AMC@qblocfalse}
1174 \def\AMCbloc{\AMC@qbloctrue}
1175 \newenvironment{question}[2][{}]{%
1176   \def\AMCcurrentenv{question}%
1177   \AMC@stepQuestion%
1178   \global\def\AMCid@name{#2}\AMC@affecte{#2}{\AMCid@quest}%
1179   \ifAMC@calibration\AMCmessage{Q=\the\AMCid@quest}\fi%
1180   \AMCbeforeQuestion%
1181   \ifx\@empty\AMC@sz@callout\@empty\else%
1182     \csname\AMC@sz@callout\endcsname%
1183   \fi%
1184   \AMCtype@multifalse\ifAMC@qbloc\ifAMC@textPos\vbox\bgroup\AMC@tracepos{1}{qtext:#2:\the\AMCid@quest,0}
1185   \ifAMC@affichekeys\index{\texttt{#2}}\ifAMC@keyline[\texttt{#2}]\newline\fi\fi%
1186   \AMCbeginQuestion{\ifAMC@affichekeys\ifAMC@ensemble\AMC@qaff\ \fi\ifAMC@keyline\else[\texttt{#2}]\fi%
1187   \ifx\@empty\AMC@sz@callin\@empty\else%
1188     \csname\AMC@sz@callin\endcsname%
```

```

1189 \fi%
1190 \AMCformulaire@dedansfalse\setcounter{AMCncase}{0}%
1191 \AMC@mem@openQuestion}%
1192 {\ifAMC@qbloc\end{minipage}\ifAMC@textPos\AMC@tracepos{1}{qtext:\AMCid@name:\the\AMCid@quest,0}\egroup\A
1193 \newenvironment{questionmult}[1]{%
1194 \AMC@bonnefalse\begin{question}[{\multiSymbole}]{#1}%
1195 \AMCtype@multitrue\ifAMC@calibration%
1196 \AMC@amclog{AUTOQCM[MULT]^~J}\fi}%
1197 {\end{question}}
1198 \newenvironment{variable-single}[2]
1199 {\def\AMCbeginQuestion##1##2{}
1200 \begin{questionmult}{#1}\scoring{v=#2}
1201 \begin{tikz-single}[o]}
1202 {\end{tikz-single}
1203 \end{questionmult}}
1204 \newenvironment{variable-multi}[4]
1205 {\def\AMCbeginQuestion##1##2{}
1206 \begin{questionmult}{#1}\scoring{v=#4}
1207 \begin{tikz-multi}[o]
1208 \node[#3] (var) at (0,0) {#2};}
1209 {\end{tikz-multi}
1210 \end{questionmult}}
1211 \newenvironment{questionmultx}[1]{%
1212 \begin{group}\def\multiSymbole{\begin{questionmult}{#1}}%
1213 {\end{questionmult}}\end{group}
1214 \newdimen\ouverte@vs
1215 \newenvironment{questionouverte}[1][3cm]{%
1216 \AMC@stepQuestion%
1217 \AMCtype@multifalse\ouverte@vs=#1%
1218 \ifAMC@qbloc\noindent\begin{minipage}{\linewidth}\fi%
1219 \AMCbeginQuestion{\AMC@qaff}{}}%
1220 {\vspace*{\ouverte@vs}\ifAMC@qbloc\end{minipage}\vspace{3ex}\fi}

```

4.11.6 Explanations

`\explain` The command `\explain` is used inside question-like environments to give the explanation for the answers of a question.

```

1221 \newcommand{\explain}[1]{%
1222 \ifAMC@correthead%
1223 \AMCif@env{question}{\par\noindent{\AMC@loc@explain #1}}{\AMC@error@explain}\vspace{1ex}%
1224 \else%
1225 \AMCif@env{question}{}{\AMC@error@explain}%
1226 \fi%
1227 }

```

4.12 Scoring

`\scoring` Scoring strategies are simply transmitted to the `.amc` file for later analysis.

`\scoringDefaultS` `\scoring{\score}` details the scoring strategy for current question or current answer,
`\scoringDefaultM` `\scoringDefaultS{\score}` and `\scoringDefaultM{\score}` gives default scoring strategy for
`QuestionIndicative` simple and multiple questions, and `\QuestionIndicative` tells that the current question is not
no be taken into account in the global mark.


```

1228 \def\scoring#1{\ifAMC@calibration\AMC@amclog{AUTOQCM[B=#1]^^J}\fi}
1229 \def\scoringDefaultS#1{\ifAMC@calibration\AMC@amclog{AUTOQCM[BDS=#1]^^J}\fi}
1230 \def\scoringDefaultM#1{\ifAMC@calibration\AMC@amclog{AUTOQCM[BDM=#1]^^J}\fi}
1231 \def\QuestionIndicative{\ifAMC@calibration\AMC@amclog{AUTOQCM[INDIC]^^J}\fi}

```

4.13 Numerical data

4.13.1 Codes

`\AMCcodeGrid` Students can code some numerical information (such as student number) through special questions, which can be formatted easily with the command `\AMCcodeGrid[opts]{key}{descr}`, where *key* is a key prefix and *descr* is a coma-separated list of character pools to offer. The characters entered by the student will be available through the questions *key*[1], ..., *key*[*length(descr)*]. As an example, `\AMCcodeGrid{code}{ABCD,012345,012345,012345,012345}` produces the opposite boxes (two results are show here: without or with `separateanswersheet` option), and trace positions of all the boxes in the .xy file with the `code` identifier: the first digit is represented by question with key `code[6]`, the second by question with key `code[5]`, and so on. Positions of the boxes are logged in the .xy file, as shown in section 5.3 for the first set of boxes (without `separateanswersheet`, with digits outside boxes).

	<input type="text"/>	0	<input type="text"/>	0	<input type="text"/>	0	<input type="text"/>	0	<input type="text"/>
	<input type="text"/>	1	<input type="text"/>	1	<input type="text"/>	1	<input type="text"/>	1	<input type="text"/>
<input type="text"/>	A	<input type="text"/>	2	<input type="text"/>	2	<input type="text"/>	2	<input type="text"/>	2
<input type="text"/>	B	<input type="text"/>	3	<input type="text"/>	3	<input type="text"/>	3	<input type="text"/>	3
<input type="text"/>	C	<input type="text"/>	4	<input type="text"/>	4	<input type="text"/>	4	<input type="text"/>	4
<input type="text"/>	D	<input type="text"/>	5	<input type="text"/>	5	<input type="text"/>	5	<input type="text"/>	5

	<input type="text"/>	0	<input type="text"/>	0	<input type="text"/>	0	<input type="text"/>	0	<input type="text"/>
	<input type="text"/>	1	<input type="text"/>	1	<input type="text"/>	1	<input type="text"/>	1	<input type="text"/>
<input type="text"/>	A	<input type="text"/>	2	<input type="text"/>	2	<input type="text"/>	2	<input type="text"/>	2
<input type="text"/>	B	<input type="text"/>	3	<input type="text"/>	3	<input type="text"/>	3	<input type="text"/>	3
<input type="text"/>	C	<input type="text"/>	4	<input type="text"/>	4	<input type="text"/>	4	<input type="text"/>	4
<input type="text"/>	D	<input type="text"/>	5	<input type="text"/>	5	<input type="text"/>	5	<input type="text"/>	5

The “horizontal” version can also be considered using option `h`, especially with a small number of digits. See opposite for the result of

`\AMCcodeGrid[h]{code}{ABCDEF,0123456789,0123456789}`.

The `\AMCcodeGridInt[opts]{key}{n}` is a shortcut for calling `\AMCcodeGrid` with *n* digits from 0 to 9. This allows to create grids for *n*-digits integers easily.

These two commands supports the following options (given as a comma-separated list optional argument *opts*):

- `vertical=true` or `false` to indicate the direction to be used (default is `true`);
- `h` is a shortcut for `vertical=false`;
- `v` is a shortcut for `vertical=true`;
- `top` to request top-aligned columns in vertical direction.

```

1232 \newcount\AMC@chiffres
1233 \newdimen\AMCcodeHspace\AMCcodeHspace=.5em
1234 \newdimen\AMCcodeVspace\AMCcodeVspace=.5em
1235 \newcommand\AMCcodeID@squarebrackets[2]{#1[#2]}
1236 \newcommand\AMCcodeID@dot[2]{#1.#2}

```

```

1237 \newcommand\AMCcodeID@[1]{%
1238   \expandafter\def\expandafter\AMCcodeID\expandafter{\csname AMCcodeID@#1\endcsname}%
1239 }
1240 \AMCcodeID@[squarebrackets]
1241 \ExplSyntaxOn
1242
1243 \clist_new:N \amc_code_descr_clist
1244 \seq_new:N \amc_code_digits_seq
1245 \int_new:N \amc_code_digit_n_int
1246 \bool_new:N \amc_code_vertical_bool
1247 \bool_new:N \amc_code_top_bool
1248
1249 \cs_new:Npn \amc_code_init:N #1 {
1250   \def\AMCbeginQuestion##1##2{}
1251   \def\AMCbeforeQuestion{}
1252   \AMCnoScoreZone
1253   \AMCquestionNumberfalse
1254   \setlength{\parindent}{0pt}
1255   \AMCnobloc
1256   \int_set:Nn \amc_code_digit_n_int { \clist_count:N #1 }
1257 }
1258
1259 \cs_new:Nn \amc_code_digit_init: {
1260   \QuestionIndicative
1261   \global\AMCrep@count=\z@
1262 }
1263
1264 \cs_new:Npn \amc_code_digit:n #1 {
1265   \global\advance\AMCrep@count\@ne\relax
1266   \ifAMC@calibration\AMC@amclog{AUTOQCM[ REP = \the\AMCrep@count : M ]^^J}\fi
1267   \hbox{\AMC@keyBox@{#1}{1}{case : \AMCid@name : \the\AMCid@quest , \the\AMCrep@count}}
1268   \bool_if:NTF \amc_code_vertical_bool {
1269     \vspace{\AMCcodeVspace}
1270   }{
1271     \hspace{\AMCcodeHspace}
1272   }
1273 }
1274
1275 \keys_define:nn { amccode } {
1276   vertical .bool_set:N = \amc_code_vertical_bool,
1277   vertical .initial:n = { true },
1278   vertical .default:n = { true },
1279   v .code:n = { \bool_set_true:N \amc_code_vertical_bool },
1280   h .code:n = { \bool_set_false:N \amc_code_vertical_bool },
1281   top .bool_set:N = \amc_code_top_bool,
1282   top .initial:n = { false },
1283   top .default:n = { true }
1284 }
1285
1286 \cs_new:Npn \amc_code_generate:nNn #1#2#3 {
1287   { \keys_set:nn { amccode } { #3 }
1288     \amc_code_init:N #2
1289     \clist_map_inline:Nn #2 { % iterates over 'digits'

```

```

1290 \begin{question}{\AMCcodeID{#1}{ \int_use:N \amc_code_digit_n_int }}
1291 \amc_code_digit_init:
1292 \seq_set_split:Nnn \amc_code_digits_seq {} { ##1 }
1293 \bool_if:NTF \amc_code_vertical_bool {
1294 \hspace{0pt}
1295 \bool_if:NTF \amc_code_top_bool { \vtop } { \vbox }
1296 \bgroup
1297 }{
1298 \hbox\bgroup
1299 }
1300 \seq_map_inline:Nn \amc_code_digits_seq {
1301 % iterates over available characters for 'digit'
1302 \amc_code_digit:n { ####1 }
1303 }
1304 \bool_if:NTF \amc_code_vertical_bool {
1305 \vspace{-\AMCcodeVspace}\egroup
1306 \hspace{\AMCcodeHspace}
1307 }{
1308 \egroup\vspace{\AMCcodeVspace}
1309 \par
1310 }
1311 \end{question}
1312 \int_decr:N \amc_code_digit_n_int
1313 }
1314 }
1315 }
1316
1317 \cs_new:Npn \amc_code_generate:nnn #1#2#3 {
1318 \clist_set:Nn \amc_code_descr_clist { #2 }
1319 \amc_code_generate:nNn { #1 } \amc_code_descr_clist { #3 }
1320 }
1321 \cs_generate_variant:Nn \amc_code_generate:nnn { xxx }
1322 \newcommand{\AMCcodeGrid}[3][]{
1323 \amc_code_generate:xxx { #2 } { #3 } { #1 }
1324 }
1325
1326 \cs_new:Npn \amc_code_generate_integer:nnn #1#2#3 {
1327 \clist_clear:N \amc_code_descr_clist
1328 \prg_replicate:nn { #2 } { \clist_put_right:Nn \amc_code_descr_clist { 0123456789 } }
1329 \amc_code_generate:nNn { #1 } \amc_code_descr_clist { #3 }
1330 }
1331 \cs_generate_variant:Nn \amc_code_generate_integer:nnn { xxx }
1332 \newcommand{\AMCcodeGridInt}[3][]{
1333 \amc_code_generate_integer:xxx { #2 } { #3 } { #1 }
1334 }
1335
1336 \cs_new:Npn \amc_code_generate_integer_v:nn #1#2 {
1337 \amc_code_generate_integer:nnn { #1 } { #2 } { v }
1338 }
1339 \cs_new:Npn \amc_code_generate_integer_h:nn #1#2 {
1340 \amc_code_generate_integer:nnn { #1 } { #2 } { h }
1341 }
1342 \cs_generate_variant:Nn \amc_code_generate_integer_v:nn { xx }

```

```

1343 \cs_generate_variant:Nn \amc_code_generate_integer_h:nn { xx }
1344 \cs_new_eq:NN \AMCcode \amc_code_generate_integer_v:xx
1345 \cs_new_eq:NN \AMCcodeH \amc_code_generate_integer_h:xx
1346
1347 \ExplSyntaxOff

```

4.13.2 Numerical questions

`\AMCnumericChoices` The command `\AMCnumericChoices{<correct>}{<options>}` can be used as a replacement for the `choices` environment when the questions asks for a numeric value to code on the answer sheet.

As an example,

```

\begin{question}{product}
  What is the value of  $7 \times 5$ ?
  \AMCnumericChoices{35}{digits=2,sign=false}
\end{question}

```

produces (in correction mode):

Question 11 What is the value of 7×5 ?
<div style="display: flex; justify-content: space-between; margin-bottom: 5px;"> <input type="checkbox"/>0 <input type="checkbox"/>1 <input type="checkbox"/>2 <input checked="" type="checkbox"/>3 <input type="checkbox"/>4 <input type="checkbox"/>5 <input type="checkbox"/>6 <input type="checkbox"/>7 <input type="checkbox"/>8 <input type="checkbox"/>9 </div> <div style="display: flex; justify-content: space-between;"> <input type="checkbox"/>0 <input type="checkbox"/>1 <input type="checkbox"/>2 <input type="checkbox"/>3 <input type="checkbox"/>4 <input checked="" type="checkbox"/>5 <input type="checkbox"/>6 <input type="checkbox"/>7 <input type="checkbox"/>8 <input type="checkbox"/>9 </div>

and these boxes are only shown on the separate answer sheet if the `separateanswersheet` option is used.

This command uses the `\AMCformatChoices{<showcommand>}{<hidecommand>}{<arg1>}{<arg2>}` command, that calls either `<hidecommand>{<arg1>}{<arg2>}` if the `separateanswersheet` option is used and if we are currently in the question part (not in the answer sheet), or `<showcommand>{<arg1>}{<arg2>}` when all the boxes are to be produced.

```

1348 \newcommand\AMCformatChoices[4]{%
1349   \global\AMCrep@count=\z@%
1350   \AMC@if@separate@question{%
1351     \AMC@mem@add{\global\AMCrep@count=\z@%
1352       #1{#3}{#4}}%
1353   }%
1354   \ifAMC@ensemble%
1355     #2{#3}{#4}%
1356     \AMC@amclog{AUTOQCM[QPART]^^J}%
1357   \else%
1358     #1{#3}{#4}%
1359   \fi%
1360 }

```

Some computation commands are now defined. The command `\amc_fp_decompose:NNn{<fp var>}{<int var>}{<x>}` sets `<fp var>` to be the *mantissa* and `<int var>` the *exponent* of the floating point number `<x>`. For example, `\amc_fp_decompose:NNn\mant_fp\expo_int{123.456}` give the value 1.23456 to `\mant_fp` and 2 to `\expo_int` (because $123.456 = 1.23456 \times 10^2$).

The command `\amc_fp_to_digits:Nnnn{<clist>}{<x>}{<n digits>}{<base>}` rounds the floating point number `<x>` and populates the comma separated list `<clist>` with its `<n digits>` digits in base `<base>`. An error is issued if `<x>` would have required more digits.

```

1361 \ExplSyntaxOn
1362
1363 \cs_generate_variant:Nn \tl_replace_once:Nnn { Nxn }
1364
1365 \tl_new:N \amc_ee_tl
1366 \seq_new:N \amc_ee_seq

```

Note that with some versions of l3fp-convert (prior to 2017-09-18), \fp_to_scientific leads to a ‘e’ with catcode 12 (*other*). We convert it to catcode *letter* before splitting.

```

1367 \group_begin:
1368 \char_set_catcode_other:N E
1369 \tex_lowercase:D
1370 {
1371   \cs_new:Npn \amc_read_scientific:NNn #1 #2 #3 {
1372     \tl_set:Nn \amc_ee_tl { #3 }
1373     \tl_replace_once:Nxn \amc_ee_tl { E } { e }
1374     \seq_set_split:NnV \amc_ee_seq e \amc_ee_tl
1375     \fp_set:Nn #1 { \seq_item:Nn \amc_ee_seq 1 }
1376     \int_set:Nn #2 { \seq_item:Nn \amc_ee_seq 2 }
1377   }
1378 }
1379 \group_end:
1380
1381 \cs_generate_variant:Nn \amc_read_scientific:NNn { NNf, NNx }
1382
1383 \fp_new:N \amc_fulls_fp
1384 \cs_new:Npn \amc_fp_decompose:NNn #1 #2 #3 {
1385   \fp_set:Nn \amc_fulls_fp { #3 }

```

Note that with some versions of l3fp-convert, the exponent part is omitted for some values, so that we add e 0.

```

1386   \amc_read_scientific:NNx #1 #2
1387   { \fp_to_scientific:N \amc_fulls_fp e 0 }
1388 }
1389 \cs_generate_variant:Nn \amc_fp_decompose:NNn { NNx }
1390
1391 \fp_new:N \amc_num_mantissa_fp
1392 \int_new:N \amc_num_exponent_int
1393 \cs_new:Npn \amc_fp_n_significant_digits:NNn #1 #2 #3 {
1394   \amc_fp_decompose:NNn \amc_num_mantissa_fp \amc_num_exponent_int
1395   { #2 }
1396   \fp_set:Nn #1
1397   { round(\amc_num_mantissa_fp * 10^((#3)-1)) }
1398   \fp_compare:nTF { abs(#1) >= 10^(#3) }
1399   {
1400     \fp_set:Nn #1 { #1 / 10 }
1401   } { }
1402 }
1403
1404 \fp_new:N \amc_num_nsig_fp
1405 \cs_new:Npn \amc_fp_show_n_significant_digits:nn #1 #2 {
1406   \amc_fp_n_significant_digits:NNn \amc_num_nsig_fp { #1 } { #2 }
1407 }
1408 \cs_new_eq:NN \AMCsignificantDigits \amc_fp_show_n_significant_digits:nn

```

```

1409
1410 \cs_new:Npn \amc_fp_show_significant_digits: {
1411   \fp_use:N \amc_num_nsig_fp
1412 }
1413 \cs_new_eq:NN \AMCshowSignificantDigits \amc_fp_show_significant_digits:
1414
1415 \cs_new:Npn \amc_fp_n_digits:Nnn #1 #2 #3 {
1416   \fp_set:Nn #1
1417     { round((#2) * 10^(#3)) }
1418 }
1419
1420 \int_new:N \amc_todigits_int
1421 \cs_new:Npn \amc_fp_to_digits:Nnnn #1 #2 #3 #4 {
1422   \clist_clear:N #1
1423   \int_set:Nn \amc_todigits_int { \fp_eval:n { abs(round(#2)) } }
1424   \prg_replicate:nn { #3 } {
1425     \clist_put_left:Nx #1 { \int_mod:nn \amc_todigits_int { #4 } }
1426     \int_set:Nn \amc_todigits_int
1427       { \int_div_truncate:nn \amc_todigits_int { #4 } }
1428   }
1429   \int_compare:nNnTF \amc_todigits_int = 0 { } {
1430     \message{^^J!~Error:~number~too~large,
1431       ~some~digits~will~be~discarded^^J}
1432   }
1433 }
1434
1435 \cs_new:Npn \amc_invalid_digits:Nn #1 #2 {
1436   \clist_clear:N #1
1437   \prg_replicate:nn { #2 } { \clist_put_left:Nx #1 { -1 } }
1438 }
1439
1440 \cs_new:Npn \amc_get_fp_sign:Nn #1 #2 {
1441   \fp_compare:nNnTF #2 < 0 {
1442     \int_set:Nn #1 { -1 }
1443   }{
1444     \fp_compare:nNnTF #2 > 0 {
1445       \int_set:Nn #1 { 1 }
1446     }{
1447       \int_set:Nn #1 { 0 }
1448     }
1449   }
1450 }
1451
1452 \cs_new:Npn \amc_get_int_sign:Nn #1 #2 {
1453   \int_compare:nNnTF #2 < 0 {
1454     \int_set:Nn #1 { -1 }
1455   }{
1456     \int_compare:nNnTF #2 > 0 {
1457       \int_set:Nn #1 { 1 }
1458     }{
1459       \int_set:Nn #1 { 0 }
1460     }
1461   }

```

```

1462 }
1463
1464 \ExplSyntaxOff

```

The command `\AMCnumericShow{<value>}{<opts>}` is called to draw all necessary boxes to code a numerical value `<value>` with options given as a comma separated list `<opts>`. `\AMCnumericOpts{<opts>}` can be used to set some default values for these options.

Begin with the available options:

```

1465 \def\AMCnntextGoto{}
1466 \def\AMCnntextVHead#1{\emph{b#1}}
1467 \newdimen\AMCnumeric@Hspace\AMCnumeric@Hspace=.5em
1468 \newdimen\AMCnumeric@Vspace\AMCnumeric@Vspace=1ex
1469 \ExplSyntaxOn
1470
1471 \keys_define:nn { amcnumeric } {
1472   Tsign .code:n = {\def\AMCnntextSign{#1}},
1473   Tsign .initial:n = {},
1474   Tpoint .code:n = {\def\AMCdecimalPoint{#1}},
1475   Tpoint .initial:n = { \raisebox{1ex}{\bf .} },
1476   Texponent .code:n = {\def\AMCexponent{#1}},
1477   Texponent .initial:n = { $\times 10$ \textasciicircum },
1478   vspace .code:n = {\AMCnumeric@Vspace=#1},
1479   hspace .code:n = {\AMCnumeric@Hspace=#1},
1480   bordercol .code:n = {\def\AMCncol@Border{#1}},
1481   bordercol .initial:n = { lightgray },
1482   borderwidth .code:n = {\def\AMCncol@BorderWidth{#1}},
1483   borderwidth .initial:n = { 1mm },
1484   backgroundcol .code:n = {\def\AMCncol@Background{#1}},
1485   backgroundcol .initial:n = { white },
1486   digits .int_set:N = \amc_num_ndigits_int,
1487   digits .initial:n = { 3 },
1488   decimals .int_set:N = \amc_num_decd_int,
1489   decimals .initial:n = { 0 },
1490   exponent .int_set:N = \amc_num_expo_int,
1491   exponent .initial:n = { 0 },
1492   base .int_set:N = \amc_num_base_int,
1493   base .initial:n = { 10 },
1494   sign .bool_set:N = \amc_num_sign_bool,
1495   sign .initial:n = { true },
1496   sign .default:n = { true },
1497   exposign .bool_set:N = \amc_num_exposign_bool,
1498   exposign .initial:n = { true },
1499   exposign .default:n = { true },
1500   strict .bool_set:N = \amc_num_strict_bool,
1501   strict .initial:n = { false },
1502   strict .default:n = { true },
1503   scoring .bool_set:N = \amc_num_scoring_bool,
1504   scoring .initial:n = { true },
1505   scoring .default:n = { true },
1506   vertical .bool_set:N = \amc_num_vertical_bool,
1507   vertical .initial:n = { false },
1508   vertical .default:n = { true },
1509   expovertical .bool_set:N = \amc_num_expovertical_bool,
1510   expovertical .initial:n = { false },

```

```

1511   expovertical .default:n = { true },
1512   reverse .bool_set:N = \amc_num_reverse_bool,
1513   reverse .initial:n = { false },
1514   reverse .default:n = { true },
1515   vhead .bool_set:N = \amc_num_vhead_bool,
1516   vhead .initial:n = { false },
1517   vhead .default:n = { true },
1518   nozero .bool_set:N = \amc_num_nzero_bool,
1519   nozero .initial:n = { false },
1520   nozero .default:n = { true },
1521   significant .bool_set:N = \amc_num_significant_bool,
1522   significant .initial:n = { false },
1523   significant .default:n = { true },
1524   scoreexact .code:n = {\def\AMC@numeric@scoreexact{#1}},
1525   scoreexact .initial:n = { 2 },
1526   scoreapprox .code:n = {\def\AMC@numeric@scoreapprox{#1}},
1527   scoreapprox .initial:n = { 1 },
1528   scorewrong .code:n = {\def\AMC@numeric@scorewrong{#1}},
1529   scorewrong .initial:n = { 0 },
1530   exact .int_set:N = \amc_num_exact_int,
1531   exact .initial:n = { 0 },
1532   approx .int_set:N = \amc_num_approx_int,
1533   approx .initial:n = { 0 },
1534   keepas .code:n = {\def\AMC@numeric@keepas{#1}},
1535   keepas .initial:n = {},
1536   alsocorrect .code:n = {\def\AMC@numeric@alsocorrect{#1}},
1537   alsocorrect .initial:n = {}
1538 }
1539
1540 \cs_new:Npn \amc_num_setopts #1 {
1541   \keys_set:nn { amcnumeric } { #1 }
1542 }
1543
1544 \cs_new_eq:NN \AMCnumericOpts \amc_num_setopts
1545

```

The command `\amc_num_char:nn{<inside>}{<answer>}` draw a box with content `<inside>` (only if needed), where `<answer>` is `\AMC@checkbox` if the corresponding choice is correct and empty if not.

```

1546 \cs_new:Npn \amc_num_char:nn #1 #2 {
1547   \global\advance\AMCrep@count\@ne\relax
1548   \AMC@amclog{AUTOQCM[REP= \the\AMCrep@count :
1549     \ifx#2\AMC@checkbox B\else M\fi ]^^J}
1550   \ifAMC@correc
1551     \protect\AMC@keyBox@{#1}{#2}{1}{case : \AMCid@name :
1552       \the\AMCid@quest , \the\AMCrep@count}
1553   \else
1554     \protect\AMC@keyBox@{#1}{#2}{1}{case : \AMCid@name :
1555       \the\AMCid@quest , \the\AMCrep@count}
1556   \fi
1557 }

```

The command `\amc_num_digit_box:nn{<i>}{<j>}` draws a box for current digit value `<i>`, where `<j>` is the correct value for the current digit. If `<i>` is greater than 9, it is converted to a character

from the English alphabet (A for 10, B for 11...)

```

1558 \int_new:N \amc_num_digit_value_int
1559 \tl_new:N \amc_num_digit_value_tl
1560 \cs_new:Npn \amc_num_digit_box:nn #1 #2 {
1561   \int_set:Nn \amc_num_digit_value_int { #1 }
1562   \tl_set:Nn \amc_num_digit_value_tl {
1563     \int_compare:nNnTF { \amc_num_digit_value_int } < { 10 }
1564     { \int_to_arabic:n { \amc_num_digit_value_int } }
1565     { \int_to_Alph:n { \amc_num_digit_value_int - 9 } }
1566   }
1567   \int_compare:nNnTF { #1 } = { #2 } {
1568     \amc_num_char:nn{ \tl_use:N \amc_num_digit_value_tl }
1569     {\AMC@checkbox}
1570   } {
1571     \amc_num_char:nn{ \tl_use:N \amc_num_digit_value_tl }
1572     {}
1573   }
1574 }

```

The command `\amc_num_sign_boxes:Nn{<sign>}{<prefix>}` draws two boxes for the students to code the sign (with a right value given by the boolean `<negative>`).

```

1575 \cs_new:Npn \amc_num_sign_boxes:Nn #1 #2 {
1576   \int_case:nn { #1 } {
1577     { -1 } {
1578       \hbox{\amc_num_char:nn{+}{}}
1579       \vspace{\AMCnumeric@Vspace}
1580       \AMC@amclog{AUTOQCM[B=set. sign #2 =1]^^J}
1581       \hbox{\amc_num_char:nn{-}{\AMC@checkbox}}
1582       \AMC@amclog{AUTOQCM[B=set. sign #2 =-1]^^J}
1583     }
1584     { 1 } {
1585       \hbox{\amc_num_char:nn{+}{\AMC@checkbox}}
1586       \vspace{\AMCnumeric@Vspace}
1587       \AMC@amclog{AUTOQCM[B=set. sign #2 =1]^^J}
1588       \hbox{\amc_num_char:nn{-}{}}
1589       \AMC@amclog{AUTOQCM[B=set. sign #2 =-1]^^J}
1590     }
1591     { 0 } {
1592       \hbox{\amc_num_char:nn{+}{}}
1593       \vspace{\AMCnumeric@Vspace}
1594       \AMC@amclog{AUTOQCM[B=set. sign #2 =1]^^J}
1595       \hbox{\amc_num_char:nn{-}{}}
1596       \AMC@amclog{AUTOQCM[B=set. sign #2 =-1]^^J}
1597     }
1598   }
1599 }

```

The command `\amc_num_digit_boxes_h:nnn{<varname>}{<correct>}{<maxdigit>}` draws a serie of boxes for all possible values of a digit (from 0 to `<maxdigit>`), where the correct value is `<correct>`, transmitting scoring data to AMC so that the variable `<varname>` will be set to the value chosen by the student.

```

1600 \cs_new:Npn \amc_num_digit_boxes_h:nnn #1 #2 #3 {
1601   \int_step_inline:nnn
1602   { \bool_if:NTF \amc_num_nozero_bool { 1 } { 0 } }

```

```

1603 { 1 } { #3 - 1 } {
1604   \amc_num_digit_box:nn { ##1 }{ #2 }
1605   \AMC@amclog{AUTOQCM[B= set. #1 = ##1 ]^^J}
1606   \hspace{\AMCnumeric@Hspace}
1607 }
1608 \hspace{-\AMCnumeric@Hspace}
1609 }
1610
1611 \cs_new:Npn \amc_num_digit_boxes_v:nnn #1 #2 #3 {
1612   \int_step_inline:nnnn
1613   { \bool_if:NTF \amc_num_nozero_bool { 1 } { 0 } }
1614   { 1 } { #3 - 1 } {
1615     \vbox{\hbox{
1616       \amc_num_digit_box:nn { ##1 }{ #2 }
1617     }}
1618     \AMC@amclog{AUTOQCM[B= set. #1 = ##1 ]^^J}
1619     \int_compare:nNnTF { ##1 } < { #3 - 1 } {
1620       \vspace{\AMCnumeric@Vspace}
1621     } {}
1622   }
1623 }
1624
1625 \int_new:N \amc_num_first_digit_int
1626 \cs_new:Npn \amc_num_digit_boxes_vr:nnn #1 #2 #3 {
1627   \int_set:Nn \amc_num_first_digit_int
1628   { \bool_if:NTF \amc_num_nozero_bool { 1 } { 0 } }
1629   \int_step_inline:nnnn { #3 - 1 } { -1 }
1630   \amc_num_first_digit_int {
1631     \vbox{\hbox{
1632       \amc_num_digit_box:nn { ##1 }{ #2 }
1633     }}
1634     \AMC@amclog{AUTOQCM[B= set. #1 = ##1 ]^^J}
1635     \int_compare:nNnTF { ##1 } > \amc_num_first_digit_int {
1636       \vspace{\AMCnumeric@Vspace}
1637     } {}
1638   }
1639 }

```

The command `\amc_num_integer_boxes_v:Nnn{<correct digits>}{<prefix>}{<decimals>}` draws boxes for integer entry, without the sign.

```

1640 \cs_new:Npn \amc_num_integer_boxes_v:Nnn #1 #2 #3 {

```

begin a loop over all digits,

```

1641   \int_set_eq:NN \amc_num_digit_int { \clist_count:N #1 }
1642   \clist_map_inline:Nn #1 {

```

place the decimal point if necessary,

```

1643     \int_compare:nNnTF \amc_num_digit_int = { #3 } {
1644       \hbox{ \AMCdecimalPoint } \hspace{\AMCnumeric@Hspace}
1645     } {}

```

draw the box for this digit,

```

1646     \hbox{\vbox{
1647       \bool_if:NTF \amc_num_vhead_bool {
1648         \vbox{\hbox{\AMCtextVHead{ \int_eval:n

```

```

1649         { \amc_num_digit_int - 1 } } } }
1650     \vspace{\AMCnumeric@Vspace}
1651 } { }
1652 \bool_if:NTF \amc_num_reverse_bool {
1653     \amc_num_digit_boxes_vr:nnn { #2
1654         \int_to_Alph:n \amc_num_digit_int }
1655     { ##1 } { \amc_num_base_int }
1656 } {
1657     \amc_num_digit_boxes_v:nnn { #2
1658         \int_to_Alph:n \amc_num_digit_int }
1659     { ##1 } { \amc_num_base_int }
1660 }
1661 }}

```

and end the loop over digits, adding space if this is not the last one.

```

1662     \int_compare:nNnTF \amc_num_digit_int > 1 {
1663         \hspace{\AMCnumeric@Hspace}
1664     } { }
1665     \int_decr:N \amc_num_digit_int
1666 }
1667 }
1668

```

The command `\amc_num_integer_boxes_h:Nnn{<correct digits>}{<prefix>}{<decimals>}` does the same, in horizontal mode.

```

1669
1670 \cs_new:Npn \amc_num_integer_boxes_h:Nnn #1 #2 #3 {
1671     \vbox{
1672         \int_set_eq:NN \amc_num_digit_int { \clist_count:N #1 }
1673         \clist_map_inline:Nn #1 {
1674             \int_compare:nNnTF
1675             \amc_num_digit_int = { #3 } {
1676                 \hbox{ \AMCdecimalPoint }
1677             } { }
1678             \hbox{
1679                 \amc_num_digit_boxes_h:nnn { #2
1680                     \int_to_Alph:n \amc_num_digit_int }
1681                 { ##1 } \amc_num_base_int
1682             }
1683             \int_compare:nNnTF \amc_num_digit_int > 1 {
1684                 \vspace{\AMCnumeric@Vspace}
1685             } { }
1686             \int_decr:N \amc_num_digit_int
1687         } }
1688     }
1689

```

Finally, `\amc_num_integer_boxes:NnnNN{<correct digits>}{<prefix>}{<decimals>}{<sign bool>}{<sign>}` draws boxes for integer entry, including the sign if `<sign bool>` is true.

```

1690
1691 \cs_new:Npn \amc_num_integer_boxes:NnnNN #1 #2 #3 #4 #5 {
1692     \hbox{
1693         \bool_if:NTF { #4 } {
1694             \vbox{
1695                 \ifx\AMCtextSign\@empty\@empty\else

```

```

1696     \hbox{\AMCtextSign}\vspace{\AMCnumeric@Vspace}\fi
1697     \amc_num_sign_boxes:Nn { #5 } { #2 }
1698   }
1699   \hspace{.5em}
1700   \vrule
1701   \hspace{.5em}
1702 } { }
1703 \hbox{
1704   \bool_if:NTF \amc_num_vertical_bool
1705   \amc_num_integer_boxes_v:Nnn \amc_num_integer_boxes_h:Nnn
1706   #1 { #2 } { #3 }
1707 }
1708 }
1709 }
1710

```

The command `\amc_num_build_integer_scoring:Nnnn{<tl var>}{<sign bool>}{<prefix>}{<n>}` builds a scoring to compute an integer from a serie of $\langle n \rangle$ -digits boxes, with name prefix $\langle prefix \rangle$, using a sign variable if $\langle sign bool \rangle$ is true.

```

1711
1712 \cs_new:Npn \amc_num_build_integer_scoring:Nnnn #1 #2 #3 #4 {
1713   \tl_clear:N #1
1714   \int_set_eq:NN \amc_num_digit_int { #4 }
1715   \int_while_do:nNnn \amc_num_digit_int > 0 {
1716     \bool_if:NTF \amc_num_strict_bool {
1717       \AMC@amclog{AUTOQCM[B=requires. #3
1718         \int_to_Alph:n \amc_num_digit_int = 1]^J}
1719     } {
1720       \AMC@amclog{AUTOQCM[B=default. #3
1721         \int_to_Alph:n \amc_num_digit_int = 0]^J}
1722     }
1723     \int_compare:nNnTF \amc_num_digit_int = #4 { } {
1724       \tl_put_left:Nn #1 { ( }
1725       \tl_put_right:Nx #1 { ) *
1726         \int_use:N \amc_num_base_int + }
1727     }
1728     \tl_put_right:Nx #1
1729     { #3 \int_to_Alph:n \amc_num_digit_int }
1730     \int_decr:N \amc_num_digit_int
1731   }
1732   \tl_put_left:Nn #1 { ( }
1733   \tl_put_right:Nn #1 { ) }
1734   \bool_if:NTF { #2 } {
1735     \bool_if:NTF \amc_num_strict_bool {
1736       \AMC@amclog{AUTOQCM[B=requires. sign #3 =1]^J}
1737     } {
1738       \AMC@amclog{AUTOQCM[B=default. sign #3 =1]^J}
1739     }
1740     \tl_put_right:Nx #1 { * ( sign #3 ) }
1741   } { }
1742 }
1743

```

Then the command `\AMCnumericShow{<x>}{<options>}` itself:

```

1744
1745 \fp_new:N \amc_num_result_fp
1746 \fp_new:N \amc_num_correct_fp
1747 \clist_new:N \amc_num_digits_clist
1748 \clist_new:N \amc_num_expo_digits_clist
1749 \int_new:N \amc_num_digit_int
1750 \int_new:N \amc_num_sign_int
1751 \int_new:N \amc_num_expo_sign_int
1752 \tl_new:N \amc_num_compute_tl
1753 \tl_new:N \amc_num_expo_tl
1754 \int_new:N \amc_num_correct_expo_int
1755
1756 \cs_new:Npn \amc_numeric_show:nn #1 #2 {

```

We have to tell AMC that the scoring we will give concerns this question:

```

1757 \ifAMC@ensemble\ifAMCformulaire@dedans
1758 \AMC@amclog{AUTOQCM[Q=\the\AMCid@quest]^J}
1759 \fi\fi

```

Then we parse the options from *<opts>*:

```

1760 {\keys_set:nn { amcnumeric } { #2 }
1761 \bool_if:nTF { \bool_if_p:N\amc_num_significant_bool
1762 && \int_compare_p:n { \amc_num_base_int != 10 } } {
1763 \message{^^J!~AMCnumeric~Error:~significant=true~can't~be~used~with~base!=10.^^J}
1764 } {}
1765 \bool_if:nTF { \int_compare_p:n { \amc_num_expo_int != 0 }
1766 && \int_compare_p:n { \amc_num_base_int != 10 } } {
1767 \message{^^J!~AMCnumeric~Error:~scientific~notation~can't~be~used~with~base!=10.^^J}
1768 } {}

```

Convert the floating point correct value to integer, taking into account the parameters significant, exponent and decimals:

```

1769 \ifx\@empty#1\@empty
1770 \fp_set:Nn \amc_num_correct_fp { 0 }
1771 \fp_set:Nn \amc_num_mantissa_fp { 0 }
1772 \int_set:Nn \amc_num_correct_expo_int { 0 }
1773 \else
1774 \bool_if:NTF \amc_num_significant_bool {
1775 \amc_fp_n_significant_digits:Nnn \amc_num_correct_fp { #1 } \amc_num_ndigits_int
1776 } {
1777 \int_compare:nNnTF \amc_num_expo_int > 0 {
1778 \amc_fp_decompose:NNn \amc_num_mantissa_fp \amc_num_correct_expo_int { #1 }
1779 \int_compare:nNnTF { \amc_num_ndigits_int - \amc_num_decd_int } > 1 {
1780 \fp_set:Nn \amc_num_mantissa_fp {
1781 \amc_num_mantissa_fp * 10^( \amc_num_ndigits_int - \amc_num_decd_int - 1 )
1782 }
1783 \int_set:Nn \amc_num_correct_expo_int {
1784 \amc_num_correct_expo_int - ( \amc_num_ndigits_int - \amc_num_decd_int - 1 )
1785 }
1786 } {}
1787 \amc_fp_n_digits:Nnn \amc_num_correct_fp \amc_num_mantissa_fp \amc_num_decd_int
1788 } {
1789 \amc_fp_n_digits:Nnn \amc_num_correct_fp { #1 } \amc_num_decd_int
1790 }
1791 }

```

1792 \fi

Now extracts the required digits:

```

1793 \ifx\@empty#1\@empty
1794   \amc_invalid_digits:Nn \amc_num_digits_clist \amc_num_ndigits_int
1795   \amc_invalid_digits:Nn \amc_num_expo_digits_clist \amc_num_expo_int
1796   \int_set:Nn \amc_num_sign_int { 0 }
1797   \int_set:Nn \amc_num_expo_sign_int { 0 }
1798 \else
1799   \amc_fp_to_digits:Nnnn \amc_num_digits_clist \amc_num_correct_fp
1800   \amc_num_ndigits_int \amc_num_base_int
1801   \amc_get_fp_sign:Nn \amc_num_sign_int \amc_num_correct_fp
1802   \int_compare:nNnTF \amc_num_expo_int > 0 {
1803     \amc_fp_to_digits:Nnnn \amc_num_expo_digits_clist \amc_num_correct_expo_int
1804     \amc_num_expo_int \amc_num_base_int
1805     \amc_get_int_sign:Nn \amc_num_expo_sign_int \amc_num_correct_expo_int
1806   } {}
1807 \fi

```

The question scoring is given to AMC (if requested by the `scoring=true` option). Note that the variable `intV` refers to the correct value, and `intX` to the value entered by the student.

```

1808 \fp_set:Nn \amc_num_result_fp { #1 }
1809 \AMC@amclog{AUTOQCM[B=numval=\fp_to_scientific:N \amc_num_result_fp ,
1810   numex=\int_use:N \amc_num_exact_int,
1811   numapp=\int_use:N \amc_num_approx_int,
1812   numsex=\AMC@numeric@scoreexact,
1813   numsapp=\AMC@numeric@scoreapprox
1814 ]}
1815 \bool_if:NTF \amc_num_scoring_bool {
1816   \AMC@amclog{AUTOQCM[B=haut=mz=,
1817     formula=(Vdifference <= \int_use:N \amc_num_exact_int ?
1818     \AMC@numeric@scoreexact :
1819     \int_compare:nNnTF \amc_num_approx_int = 0 {
1820       \AMC@numeric@scorewrong
1821     } {
1822       (Vdifference <= \int_use:N\amc_num_approx_int ?
1823       \AMC@numeric@scoreapprox : \AMC@numeric@scorewrong)
1824     }
1825   )]^^J}
1826 } {}
1827 \amc_num_build_integer_scoring:Nnnn
1828   \amc_num_compute_tl \amc_num_sign_bool { digit } \amc_num_ndigits_int
1829 \int_compare:nNnTF \amc_num_expo_int > 0 {
1830   \amc_num_build_integer_scoring:Nnnn
1831   \amc_num_expo_tl \amc_num_exposign_bool { expo } \amc_num_expo_int
1832   \AMC@amclog{AUTOQCM[B= set. intE = \amc_num_expo_tl ]^^J}
1833 } {}
1834 \AMC@amclog{AUTOQCM[B= set.intV = \fp_to_int:N\amc_num_correct_fp ,
1835   set.intXX = \amc_num_compute_tl ]^^J}
1836 \int_compare:nNnTF \amc_num_expo_int > 0 {
1837   \AMC@amclog{AUTOQCM[B= set.intX = intXX * \int_use:N\amc_num_base_int ** ( intE - (\int_use:N\amc_nu
1838   )}
1839   \AMC@amclog{AUTOQCM[B= set.intX = intXX]^^J}
1840 }

```

```

1841 \int_compare:nNnTF \amc_num_expo_int > 0 {
1842   \AMC@amclog{AUTOQCM[B= set.valueX = intXX * \int_use:N\amc_num_base_int ** (intE - \int_use:N\amc_r
1843 }{
1844   \AMC@amclog{AUTOQCM[B= set.valueX = intXX * \int_use:N\amc_num_base_int ** (- \int_use:N\amc_num_de
1845 }
1846 \ifx\@empty\AMC@numeric@keepas\@empty\else
1847 \AMC@amclog{AUTOQCM[B= setglobal.\AMC@numeric@keepas = valueX ]^^J}
1848 \fi
1849 \ifx\@empty#1\@empty
1850 \bool_if:NTF \amc_num_significant_bool {
1851   \AMC@amclog{AUTOQCM[B=set.Vdifference=0]^^J}
1852 }{
1853   \ifx\@empty\AMC@numeric@alsocorrect\@empty
1854     \AMC@amclog{AUTOQCM[B=set.Vdifference=0]^^J}
1855   \else
1856     \AMC@amclog{AUTOQCM[B="set.Vdifference =
1857       amcvdifference( \AMC@numeric@alsocorrect, valueX, \int_use:N\amc_num_decd_int, \int_use:N\amc_r
1858       "]"^^J}
1859   \fi
1860 }
1861 \else
1862 \bool_if:NTF \amc_num_significant_bool {
1863   \AMC@amclog{AUTOQCM[B=set.Vdifference="min( abs((intV)-(intX)) ,
1864     abs(\int_use:N\amc_num_base_int * (intV) - (intX)) ,
1865     abs((intV) - \int_use:N\amc_num_base_int * (intX)) )" ]^^J}
1866 } {
1867   \ifx\@empty\AMC@numeric@alsocorrect\@empty
1868     \AMC@amclog{AUTOQCM[B=set.Vdifference=abs((intV)-(intX))]^^J}
1869   \else
1870     \AMC@amclog{AUTOQCM[B="set.Vdifference =
1871       min( amcvdifference( \AMC@numeric@alsocorrect, valueX, \int_use:N\amc_num_decd_int, \int_use:N\amc_r
1872       abs((intV)-(intX)) )" ]^^J}
1873   \fi
1874 }
1875 \fi

```

Begin now with the frame around all the boxes:

```

1876 \ifAMC@extractOnly\else
1877 \vspace{1.5ex}\par{
1878   \fboxrule=\AMCncol@BorderWidth
1879   \fcolorbox{\AMCncol@Border}{\AMCncol@Background}{
1880     \bool_if:NTF \amc_num_expovertical_bool {
1881       \hbox{\vbox{
1882         \vbox{\amc_num_integer_boxes:NnnNN
1883           \amc_num_digits_clist { digit } \amc_num_decd_int \amc_num_sign_bool
1884           \amc_num_sign_int}
1885         \int_compare:nNnTF \amc_num_expo_int > 0 {
1886           \vspace{\AMCnumeric@Vspace}
1887           \vbox{\hbox{\AMCexponent}}
1888           \vspace{\AMCnumeric@Vspace}
1889           \vbox{\amc_num_integer_boxes:NnnNN
1890             \amc_num_expo_digits_clist { expo } { 0 } \amc_num_exposign_bool
1891             \amc_num_expo_sign_int}
1892         } {}

```

```

1893     }}
1894   } {
1895     \amc_num_integer_boxes:NnnNN
1896     \amc_num_digits_clist { digit } \amc_num_decd_int \amc_num_sign_bool
1897     \amc_num_sign_int
1898     \int_compare:nNnTF \amc_num_expo_int > 0 {
1899       \hspace{\AMCnumeric@Hspace}\AMCexponent\hspace{\AMCnumeric@Hspace}
1900       \amc_num_integer_boxes:NnnNN
1901       \amc_num_expo_digits_clist { expo } { 0 } \amc_num_exposign_bool
1902       \amc_num_expo_sign_int
1903     } {}
1904   }
1905 }
1906 }
1907 \fi

```

And tell AMC that we finished with this question:

```

1908 \ifAMC@ensemble\else\vspace{1.5ex}\par\fi
1909 \ifAMC@ensemble\ifAMC@formulaire@dedans
1910   \AMC@amclog{AUTOQCM[FQ]^^J}
1911 \fi\fi
1912 }
1913 }
1914
1915 \cs_new_eq:NN \AMCnumericShow \amc_numeric_show:nn
1916

```

`\AMCnumericHide` is called when the boxes are not to be drawn (in the question sheets for separate answer sheet layout), and `\AMCnumericChoices{⟨value⟩}{⟨options⟩}` is the function to be used in the LaTeX source code of the exam.

```

1917 \cs_new:Npn \amc_numeric_hide:nn #1 #2 {
1918   \keys_set:nn { amcnumeric } { #2 }
1919   \AMCncontextGoto
1920   \ifAMC@qbloc\else\vspace{1.5ex}\par\fi
1921 }
1922
1923 \cs_new_eq:NN \AMCnumericHide \amc_numeric_hide:nn
1924
1925 \ExplSyntaxOff
1926 \def\AMCnumericChoicesPlain{%
1927   \AMC@if@separate@question{\AMC@mem@category{numeric}}{%
1928     \AMCformatChoices{\AMCnumericShow}{\AMCnumericHide}%
1929 }

```

The `{⟨value⟩}` argument is often given as a macro, that is to be expanded before calling `\AMCnumericChoicesPlain`, so that its value will be the same in the separate answer sheet...

```

1930 \ExplSyntaxOn
1931
1932 \cs_new:Npn \amc_numeric_choices:nn #1#2 {
1933   \AMCnumericChoicesPlain{#1}{#2}
1934 }
1935 \cs_generate_variant:Nn \amc_numeric_choices:nn { xn }
1936 \cs_new_eq:NN \AMCnumericChoices \amc_numeric_choices:xn
1937
1938 \ExplSyntaxOff

```


4.13.3 Intervals

`\AMCIntervals` The command `\AMCIntervals{\langle x \rangle}{\langle x0 \rangle}{\langle x1 \rangle}{\langle \delta \rangle}` can be used to present answers as intervals $[x_i, x_i + \delta[$ covering $[\langle x0 \rangle, \langle x1 \rangle]$, such that the only interval containing $\langle x \rangle$ is declared as `\correctchoice`, and the other as `\wrongchoice`.

For this command to work, one has to load package `fp`.

As an example,

```
\begin{question}{quarter}
  In which interval falls  $1/4$ ?
  \begin{multicols}{5}
    \begin{choices}[o]
      \AMCIntervals{0.25}{0}{1}{0.1}
    \end{choices}
  \end{multicols}
\end{question}
```

produces (in correction mode):

Question 12 In which interval falls $1/4$?

☐ $[0, 0.1[$
☒ $[0.2, 0.3[$
☐ $[0.4, 0.5[$
☐ $[0.6, 0.7[$
☐ $[0.8, 0.9[$
☐ $[0.1, 0.2[$
☐ $[0.3, 0.4[$
☐ $[0.5, 0.6[$
☐ $[0.7, 0.8[$
☐ $[0.9, 1[$

Note that the interval formatting can be changed redefining the `\AMCIntervalFormat` command, which is originally defined as

```
1939 \def\AMCIntervalFormat#1#2{[#1,\,#2]}
```

to follow local conventions (writting $[a, b)$ instead of $[a, b[$ is for example a common usage).

```
1940 \ExplSyntaxOn
```

```
1941
```

```
1942 \fp_new:N \amc_interv_a
```

```
1943 \fp_new:N \amc_interv_b
```

```
1944 \cs_new:Npn \amc_intervals:nnnn #1 #2 #3 #4 {
```

```
1945   \fp_set:Nn \amc_interv_a { #2 }
```

```
1946   \fp_do_while:nn { \amc_interv_a < #3 } {
```

```
1947     \fp_set:Nn \amc_interv_b { \amc_interv_a + #4 }
```

```
1948     \fp_compare:nTF { \amc_interv_a <= #1 < \amc_interv_b }
```

```
1949       \correctchoice \wrongchoice
```

```
1950     {\AMCIntervalFormat{\fp_use:N \amc_interv_a}{\fp_use:N \amc_interv_b}}
```

```
1951     \fp_set:Nn \amc_interv_a \amc_interv_b
```

```
1952   }
```

```
1953 }
```

```
1954 \cs_new_eq:NN \AMCIntervals \amc_intervals:nnnn
```

```
1955
```

```
1956 \ExplSyntaxOff
```

4.14 Open questions

`\AMCOpen` The command `\AMCOpen{\langle options \rangle}{\langle choices \rangle}` can be used as a replacement for the `choices` environment when asking the student to write some answer by hand. The teacher will correct and mark this answer either on the paper before scanning, or with manual data capture, thanks to the scoring boxes.

As an example,

```

\begin{question}{Linux}
  What is the first name of the person who started working on the Linux kernel?
  \AMCOpen{}{\wrongchoice[w]{w}\scoring{0}\correctchoice[c]{c}\scoring{2}}
\end{question}

```

shows:

Question 13 What is the first name of the person who started working on the Linux kernel?

☐ w ☐ c

.....

The teacher will have to tick the ‘w’ box for wrong answers, and the ‘c’ box for correct answers.

Begin with the options definitions:

```

1957 \def\AMCotextGoto{}
1958 \def\AMCotextReserved{}
1959 \def\AMCocol@Background{lightgray}
1960 \def\AMCocol@BoxFrameRule{white}
1961 \def\AMCocol@FrameRule{black}
1962 \def\AMCocol@Foreground{}
1963 \def\AMCopen@answer{}
1964 \def\AMCopen@question{}
1965 \def\AMCopen@lineuptext{}
1966 \define@key{AMCOpen}{backgroundcol}{\def\AMCocol@Background{#1}}
1967 \define@key{AMCOpen}{foregroundcol}{\def\AMCocol@Foreground{#1}}
1968 \define@key{AMCOpen}{Treserved}{\def\AMCotextReserved{#1}}
1969 \define@key{AMCOpen}{question}{[\AMCid@name]{\def\AMCopen@question{#1}}
1970 \define@key{AMCOpen}{answer}{\def\AMCopen@answer{#1}}
1971 \define@key{AMCOpen}{contentcommand}{[AMCopen@lines]{\def\AMCopen@contentcommand{#1}}
1972 \newdimen\AMCopen@Hspace\AMCopen@Hspace=.5em
1973 \define@key{AMCOpen}{hspace}{\AMCopen@Hspace=#1}
1974 \def\AMCopen@Width{.95\linewidth}
1975 \define@key{AMCOpen}{width}{\def\AMCopen@Width{#1}}
1976 \newdimen\AMCopen@LineHeight\AMCopen@LineHeight=1cm
1977 \define@key{AMCOpen}{lineheight}{\AMCopen@LineHeight=#1}
1978 \newcount\AMCopen@Lines\AMCopen@Lines=1
1979 \define@key{AMCOpen}{lines}{\AMCopen@Lines=#1}
1980 \newdimen\AMCopen@boxmargin\AMCopen@boxmargin=3pt
1981 \define@key{AMCOpen}{boxmargin}{\AMCopen@boxmargin=#1}
1982 \newdimen\AMCopen@boxframerule\AMCopen@boxframerule=1pt
1983 \define@key{AMCOpen}{boxframerule}{\AMCopen@boxframerule=#1}
1984 \define@key{AMCOpen}{boxframerulecol}{\def\AMCocol@BoxFrameRule{#1}}
1985 \define@key{AMCOpen}{framerulecol}{\def\AMCocol@FrameRule{#1}}
1986 \newdimen\AMCopen@framerule\AMCopen@framerule=1pt
1987 \define@key{AMCOpen}{framerule}{\AMCopen@framerule=#1}
1988 \define@key{AMCOpen}{lineuptext}{\def\AMCopen@lineuptext{#1}}
1989 \define@boolkey{AMCOpen}{dots}[true]{}
1990 \define@boolkey{AMCOpen}{scan}[true]{}
1991 \define@boolkey{AMCOpen}{annotate}[false]{}

```

```

1992 \define@boolkey{AMCOpen}{lineup}[false]{}
1993 \setkeys{AMCOpen}{dots,scan,annotate,lineup,contentcommand}
1994 \newcommand\AMCOpenOpts[1]{\setkeys{AMCOpen}{#1}}

```

The command \AMCOpen is similar to \AMCnumericChoices, calling either \AMCOpenShow or \AMCOpenHide.

```

1995 \newcommand\AMCOpen@lines{%
1996   \begin{minipage}{\AMCOpen@Width}%
1997     \loop\vspace{\AMCOpen@LineHeight}
1998     \hspace*{.5em}\ifAMC@correc\smash{\AMCOpen@answer}\def\AMCOpen@answer{}\fi%
1999     \ifKV@AMCOpen@dots%
2000       \dotfill\hspace*{.5em}
2001     \fi
2002     \ifnum\AMCOpen@Lines>\@ne\par\advance\AMCOpen@Lines\m@ne\repeat%
2003   \end{minipage}
2004 }
2005 \newcommand\AMCOpenShow[2]{
2006   \ifAMC@ensemble\ifAMCformulaire@dedans%
2007     \AMC@amclog{AUTOQCM[Q=\the\AMCid@quest]^^J}%
2008     \fi\fi%
2009   {\setkeys{AMCOpen}{#1}%
2010     \ifKV@AMCOpen@lineup%
2011       \ifAMC@ensemble\else%
2012         \ifx\@empty\AMCOpen@lineuptext\@empty\fi%
2013         \fi%
2014         \ifAMC@correc\smash{\AMCOpen@answer}\fi%
2015         \ifx\@empty\AMCOpen@lineuptext\@empty%
2016           \dotfill%
2017         \else%
2018           \AMCOpen@lineuptext\hfill%
2019         \fi%
2020       \else%
2021         \hspace*{.5em}\linebreak[1]\hspace*{\fill}%
2022       \fi%
2023     {\AMCnoCompleteMulti%
2024       \def\AMCbeginAnswer{}\def\AMCendAnswer{}%
2025       \def\AMCanswer##1##2{\ifAMC@ensemble ##1\else%
2026         \ifAMC@inside@box ##1\else\AMCboxOutsideLetter{##1}{##2}}\fi\fi%
2027       \hspace{\AMCOpen@Hspace}}%
2028       \fboxsep=\AMCOpen@boxmargin%
2029       \fboxrule=\AMCOpen@boxframerule%
2030       \fcolorbox{\AMCocol@BoxFrameRule}{\AMCocol@Background}{%
2031         \ifAMC@ensemble\AMCOpen@question%
2032           \ifx\@empty\AMCOpen@question\@empty\else\hspace{\AMCOpen@Hspace}\fi%
2033         \fi%
2034         \begin{choicescustom}[o]%
2035           \ifx\AMCocol@Foreground\@empty\@empty\else%
2036             \def\AMC@boxcolor{\AMCocol@Foreground}%
2037           \fi%
2038           #2%
2039           \ifKV@AMCOpen@scan\else\AMCdontScan\fi%
2040           \ifKV@AMCOpen@annotate\else\AMCdontAnnotate\fi%
2041         \end{choicescustom}%
2042         \ifx\@empty\AMCotextReserved\@empty%

```

```

2043         \hspace{-\AMCopen@Hspace}%
2044     \else%
2045         \ifx\AMCocol@Foreground\@empty\@empty%
2046             \AMCotextReserved%
2047         \else%
2048             \textcolor{\AMCocol@Foreground}{\AMCotextReserved}%
2049         \fi%
2050     \fi%
2051 }}%
2052 \ifKV@AMCOpen@lineup\else%
2053     \par\nobreak\noindent%
2054     \hspace*{\fill}{%
2055         \fboxrule=\AMCopen@framerule%
2056         \fcolorbox{\AMCocol@FrameRule}{white}{%
2057             \csname\AMCopen@contentcommand\endcsname
2058         }%
2059     \vspace{\AMCpost@quest}\par%
2060 \fi%
2061 }%
2062 \ifAMC@ensemble\ifAMCformulaire@dedans%
2063 \AMC@amclog{AUTOQCM[FQ]^^J}%
2064 \fi\fi%
2065 }
2066 \newcommand\AMCOpenHide[2]{%
2067     \AMCotextGoto%
2068     \ifAMC@qbloc\else\vspace{1.5ex}\par\fi%
2069 }
2070 \def\AMCOpen{%
2071     \AMC@if@separate@question{\AMC@mem@category{open}}%
2072     \AMCformatChoices{\AMCopenShow}{\AMCopenHide}%
2073 }

```

4.15 Boxes with letters only

`\AMCBoxOnly` Sometimes the letters printed in the boxes (or just after them) are enough to describe the answers. In such cases, printing the boxes both on the question and on the answer sheet is not necessary. The `\AMCBoxOnly{<options>}{<choices>}` can be used as a replacement for the `choices` environment:

```

\begin{question}{arm}
    Which letter shows the \textit{arm} on the diagram?
    \AMCBoxOnly{ordered=true}{\wrongchoice[A]{}\correctchoice[B]{}%
        \wrongchoice[C]{}\wrongchoice[D]{}%
    }
\end{question}

2074 \def\AMCbotextGoto{}
2075 \def\AMCbo@help{}
2076 \define@key{AMCBoxOnly}{help}{\def\AMCbo@help{#1}}
2077 \define@boolkey{AMCBoxOnly}{ordered}[false]{}
2078 \setkeys{AMCBoxOnly}{ordered}
2079 \newcommand\AMCboOpts[1]{\setkeys{AMCBoxOnly}{#1}}
2080 \newcommand\AMCboShow[2]{%
2081     \ifAMC@ensemble\ifAMCformulaire@dedans%

```

```

2082 \AMC@amclog{AUTOQCM[Q=\the\AMCid@quest]^~J}%
2083 \fi\fi%
2084 {\setkeys{AMCBoxOnly}{#1}%
2085 \def\AMCbeginAnswer{}\def\AMCendAnswer{}%
2086 \def\AMCanswer##1##2{\hspace{\AMCformHSpace} \ifAMC@ensemble ##1\else%
2087 \ifAMC@inside@box ##1\else{\AMCboxOutsideLetter{##1}{##2}}\fi\fi%
2088 }%
2089 \ifAMC@ensemble\AMCbo@help\fi%
2090 \ifKV@AMCBoxOnly@ordered%
2091 \begin{choicescustom}[o]%
2092 \else%
2093 \begin{choicescustom}%
2094 \fi%
2095 #2
2096 \end{choicescustom}%
2097 }%
2098 \ifAMC@ensemble\ifAMCformulaire@dedans%
2099 \AMC@amclog{AUTOQCM[FQ]^~J}%
2100 \fi\fi%
2101 }
2102 \newcommand\AMCboHide[2]{
2103 \AMCbotextGoto%
2104 \ifAMC@qbloc\else\vspace{1.5ex}\par\fi%
2105 }
2106 \def\AMCBoxOnly{%
2107 \AMC@if@separate@question{\AMC@mem@category{box}}}%
2108 \AMCformatChoices{\AMCboShow}{\AMCboHide}%
2109 }

```

4.16 Page formatting

4.16.1 Watermark

`\AMCw@termark` These commands are used to print a grey “DRAFT” under each page, so as to prevent from
`\AMCw@terprint` printing old versions of the subject.

```

2110 \DeclareFontShape{OT1}{cmr}{b}{n}{<35->cmr17}{-}
2111 \def\AMC@watertext{\AMC@loc@draft}
2112 \newcommand\AMCw@termark{%
2113 \setlength{\@tempdimb}{.5\paperwidth}%
2114 \setlength{\@tempdimc}{-.5\paperheight}%
2115 \put(\strip@pt\@tempdimb,\strip@pt\@tempdimc){%
2116 \makebox(0,0){\rotatebox{45}{\AMC@LR{%
2117 \textcolor[gray]{0.8}{
2118 \fontencoding{OT1}\fontfamily{cmr}
2119 \fontseries{b}\fontshape{n}
2120 \fontsize{90pt}{120pt}
2121 \selectfont
2122 \AMC@watertext}}}}}}
2123 \newcommand\AMCw@terprint[1]{%
2124 \setbox\@tempboxa\vbox to \z@{%
2125 \vbox{%
2126 \hbox to \z@{%
2127 #1\hss}}\vss}

```

```

2128 \dp\@tempboxa\z@
2129 \box\@tempboxa}

```

4.16.2 Signs for scan analysis

The following code sets up all the signs to be printed on the pages so as to be able to recognize the position of the boxes on the scans. Four circles ● are printed on the corners (see \m@rqueCalage), and binary boxes show the student sheet number (see \AMCIDBoxesA), the page (see \AMCIDBoxesB) and a checking number (see \AMCIDBoxesC).

\AMC@intituleHead is the title to be printed at the beginning (used for corrected sheet, and empty on subject). \AMC@note is printed at the bottom of each page. You can change its value using \AMCsetFoot{\foot}.

```

2130 \def\AMCccircle#1#2{%
2131   {\setlength{\unitlength}{1mm}%
2132     \begin{picture}(\#1,\#1)(-#2,-#2)\thinlines\circle*{\#1}\end{picture}}
2133 \def\m@rqueCalage{\AMCccircle{3.6}{1.8}}
2134 \def\m@rque#1{\AMC@tracebox{1}{\#1}{\m@rqueCalage}}
2135 \def\he@dtaille#1{\par\vbox to 1cm{\#1}}
2136 \def\he@dbas#1{\he@dtaille{\vspace*{\fill}\#1}}
2137 \def\he@dhaut#1{\he@dtaille{\#1\vspace*{\fill}}}
2138 \def\AMC@intituleHead{\AMC@loc@corrected}
2139 \def\AMC@note{}
2140 \def\AMCsetFoot#1{\def\AMC@note{\#1}}
2141 \newcommand\AMCStudentNumber{\the\AMCid@etud}
2142 \newcommand\AMCIDBoxesA{\AMC@binaryCode{id=1,ndigits=\AMC@NCBetud}{\the\AMCid@etud}}
2143 \newcommand\AMCIDBoxesB{\AMC@binaryCode{id=2,ndigits=\AMC@NCBpage}{\thepage}}
2144 \newcommand\AMCIDBoxesC{\AMC@binaryCode{id=3,ndigits=\AMC@NCBcheck}{\the\AMCid@check}}
2145 \newcommand\AMCIDBoxesABC{%
2146   \hbox{\vbox{\noindent\AMCIDBoxesA\
2147     \noindent\AMCIDBoxesB\AMCIDBoxesC}}}%
2148 }
2149 \AtBeginPage{\ifAMC@pagelayout\global\advance\AMCid@check\m@ne%
2150   \ifnum\AMCid@check<1\global\AMCid@check=\AMCid@checkmax\fi%
2151   \AMC@pagepos%
2152   \ifAMC@watermark\ifAMC@correcthead\else\AMCw@terprint{\AMCw@termark}%
2153   \fi\fi\fi}
2154 \fancypagestyle{AMCpageHeadOnly}{%
2155   \fancyhf{}\fancyhead[C]{\textsc{\AMC@intituleHead}}%
2156   \renewcommand{\headrulewidth}{0pt}%
2157   \renewcommand{\footrulewidth}{0pt}%
2158 }
2159 \fancypagestyle{AMCpageFull}{%
2160   \fancyhf{}%
2161   \fancyhead[L]{\AMC@LR{\he@dbas{\leavevmode\m@rque{positionHG}}}}%
2162   \fancyhead[R]{\AMC@LR{\he@dbas{\leavevmode\m@rque{positionHD}}}}%
2163   \fancyfoot[L]{\AMC@LR{\leavevmode\m@rque{positionBG}}}%
2164   \fancyfoot[R]{\AMC@LR{\leavevmode\m@rque{positionBD}}}%
2165   \fancyhead[C]{\AMC@LR{\he@dhaut{%
2166     \begin{minipage}[b]{\AMC@CBtaille}\AMCboxColor{black}%
2167       \ifAMCids@top\vbox to \AMCids@height{\texttt{+\the\AMCid@etud/\thepage/\the\AMCid@check+}}\fi%
2168       \AMCIDBoxesABC
2169     \end{minipage}}}%

```

```

2170         \ifAMCids@side\hbox to \AMCids@width{\hspace*{\fill}}%
2171         \texttt{+\the\AMCid@etud/\thepage/\the\AMCid@check+}}\fi%
2172     }}}}
2173     \fancyhfoffset[EOLR]{5mm}%
2174     \fancyfoot[C]{\AMC@note}%
2175     \renewcommand{\headrulewidth}{0pt}%
2176     \renewcommand{\footrulewidth}{0pt}%
2177 }
2178 \newcommand\AMCsubjectPageTag{%
2179     \fbox{\texttt{\the\AMCid@etud:\thepage}}%
2180 }
2181 \fancypagestyle{AMCpageNoMarks}{%
2182     \fancyhf{}%
2183     \fancyhead[R]{\AMCsubjectPageTag}%
2184     \fancyfoot[C]{\AMC@note}%
2185     \renewcommand{\headrulewidth}{0pt}%
2186     \renewcommand{\footrulewidth}{0pt}%
2187 }
2188 \fancypagestyle{AMCpageEmpty}{%
2189     \fancyhf{}%
2190     \renewcommand{\headrulewidth}{0pt}%
2191     \renewcommand{\footrulewidth}{0pt}%
2192 }
2193 \AtBeginDocument{%
2194     \ifAMC@pagelayout%
2195         \ifAMC@correthead
2196             \pagestyle{AMCpageHeadOnly}
2197         \else
2198             \pagestyle{AMCpageFull}
2199         \fi
2200     \fi
2201 }

```

4.17 Defining a single exam copy content

`\onecopy` The command `\onecopy[$\langle n \rangle$]{ $\langle code \rangle$ }` generates $\langle n \rangle$ copies of the subject that is described in $\langle code \rangle$. The L^AT_EX code $\langle code \rangle$ that generates a single copy can be a little long, so that the environment `examcopy` is often preferred.

```

2202 \newcommand{\onecopy}[2]{%
2203     \ifx\AMCNombreCopies\undefined\AMCnum@copies=#1%
2204     \else\AMCnum@copies=\AMCNombreCopies\fi%
2205     \AMC@amclog{AUTOQCM[TOTAL=\the\AMCnum@copies]^^J}%
2206     \AMCid@etud=\AMCid@etudstart%
2207     \ifnum\AMCid@etud=0\AMCid@etud=\AMC@premierecopie\fi%
2208     \AMCid@etudfin=\AMCnum@copies%
2209     \advance\AMCid@etudfin\AMCid@etud\relax%
2210     \ifAMC@correthead\AMCid@etudfin=\AMC@premierecopie\fi
2211     \ifAMC@pdfform\begin{Form}\fi%
2212     \loop{%
2213         \ifAMC@calibration\protected@write\AMC@XYFILE{}{%
2214             \string\rngstate{\the\AMCid@etud}{\the\AMC@SR}%
2215         }\fi%
2216         \AMC@zoneformulairefalse\setcounter{page}{1}\setcounter{section}{0}%

```

```

2217 \ifAMC@ensemble\ifAMC@automarks\pagestyle{AMCpageNoMarks}\fi\fi%
2218 \AMCnumero{1}%
2219 \ifAMC@calibration\AMC@amclog{AUTOQCM[ETU=\the\AMCid@etud]^~J}\fi%
2220 \global\AMC@keepmemoryfalse%
2221 #2%
2222 \ifAMC@keepmemory\else\AMC@mem@clear\fi%
2223 \clearpage}%
2224 \advance\AMCid@etud\@ne\ifnum\AMCid@etud<\AMCid@etudfin\repeat%
2225 \global\AMCid@etudstart=\AMCid@etud%
2226 \ifAMC@pdfform\end{Form}\fi%
2227 }

```

\AMCaddpagesto In some situations, one needs all question sheets to have the same number of pages. The command **\AMCaddpagesto{<n>}** adds enough (white) pages to get at least <n> pages in the current question sheet.

```

2228 \newcount\AMC@addpages
2229 \newcommand{\AMCaddpagesto}[1]{%
2230 \AMC@addpages=#1\advance\AMC@addpages\@ne%
2231 \clearpage%
2232 \@whilenum\thepage<\AMC@addpages\do{%
2233 \ifAMC@automarks\pagestyle{AMCpageEmpty}\fi%
2234 \hbox{}\clearpage%
2235 }%
2236 }

```

\AMCcleardoublepage If you want to print the subject all at one time in duplex mode, it is necessary to end each subject with an even number of pages. This can be achieved using **\AMCcleardoublepage** at the end of the copy definition. This command is also useful inserted before the separate answer sheet (if any).

```

2237 \def\AMCcleardoublepage{%
2238 \clearpage%
2239 \ifodd\thepage\else%
2240 \ifAMC@automarks\pagestyle{AMCpageEmpty}\fi%
2241 \hbox{}\clearpage%
2242 \fi%
2243 }

```

\exemplairepair To make some differences in the copies, checking if the student sheet number is odd, with **\exemplairepair** construct, can be useful.

```

2244 \def\exemplairepair{\ifodd\AMCid@etud}

```

\AMClabel Commands **\AMClabel**, **\AMCref** and **\AMCpageref** replaces L^AT_EX's **\label**, **\ref** and **\pageref** to be able to use different labels for different sheets.

```

\AMCref
2245 \newcommand\AMCstudentlabel[1]{\the\AMCid@etud-#1}
2246 \def\AMClabel#1{\expandafter\label{\AMCstudentlabel{#1}}}
2247 \def\AMCref#1{\expandafter\ref{\AMCstudentlabel{#1}}}
2248 \def\AMCpageref#1{\expandafter\pageref{\AMCstudentlabel{#1}}}

```

\AMCqlabel A label can be created for current question with **\AMCqlabel{<label>}**. This label can be used with **\AMCref** and **\AMCpageref**. This command is defined for backward compatibility only, since **\AMClabel** can also be used.

```

2249 \newcommand{\AMCqlabel}[1]{%

```



```

2250 \AMClabel{#1}%
2251 }

```

4.18 Pre-association

`\AMCassociation` Association between sheets and students can be made before the exam with the `\AMCassociation[<filename>]{<id>}` command. The optional argument *<filename>* will be used when printing student sheets to files.

```

2252 \newcommand{\AMCassociation}[2][]{%
2253   \ifAMC@calibration%
2254   \immediate\write\AMC@XYFILE{\string\association{\the\AMCid@etud}{#2}{#1}}%
2255   \fi%
2256 }

```

`\AMCstudentslistfile` You can also pass AMC the path to the CSV file with students, and the unique key that can be used, with `\AMCstudentslistfile{<path>}{<key>}`.

```

2257 \newcommand{\AMCstudentslistfile}[2]{%
2258   \ifAMC@calibration%
2259   \immediate\write\AMC@XYFILE{\string\with{studentslistfile=#1}}%
2260   \immediate\write\AMC@XYFILE{\string\with{studentslistkey=#2}}%
2261   \fi%
2262 }

```

4.19 Package options

See section 3.1 for the options descriptions.

```

2263 \def\AMC@lang@code{}
2264 \DeclareOptionX{noshuffle}{\AMC@ordretrue}
2265 \DeclareOptionX{noshufflegroups}{\AMC@shuffleGfalse}
2266 \DeclareOptionX{fullgroups}{\AMC@fullGroupstrue}
2267 \DeclareOptionX{answers}{\AMC@corretheadtrue\AMC@correcttrue}
2268 \DeclareOptionX{indivanswers}{\AMC@correcttrue}
2269 \DeclareOptionX{textpos}{\AMC@textPostrue}
2270 \DeclareOptionX{extractonly}{\AMC@extractOnlytrue\AMC@textPostrue\AMC@boxStyle{shape=none}\AMC@boxedAnswer}
2271 \DeclareOptionX{box}{\AMC@qbloctrue}
2272 \DeclareOptionX{asbox}{\AMC@asqbloctrue}
2273 \DeclareOptionX{separateanswersheet}{\AMC@ensembletrue}
2274 \DeclareOptionX{digits}{\AMC@inside@digittrue}
2275 \DeclareOptionX{ordre}{\AMC@ordretrue}
2276 \DeclareOptionX{correc}{\AMC@corretheadtrue\AMC@correcttrue}
2277 \DeclareOptionX{modele}{\AMC@corretheadtrue\AMC@correcfalse\AMC@ordretrue}
2278 \DeclareOptionX{correcindiv}{\AMC@correcttrue}
2279 \DeclareOptionX{init}{\AMC@SR@time}
2280 \DeclareOptionX{bloc}{\AMC@qbloctrue}
2281 \DeclareOptionX{completemulti}{\AMC@complete@multitrue}
2282 \DeclareOptionX{insidebox}{\AMC@inside@boxtrue}
2283 \DeclareOptionX{ensemble}{\AMC@ensembletrue}
2284 \DeclareOptionX{chiffres}{\AMC@inside@digittrue}
2285 \DeclareOptionX{outsidebox}{\AMC@outside@boxtrue}
2286 \DeclareOptionX{calibration}{\AMC@calibrationtrue}
2287 \DeclareOptionX{nowatermark}{\AMC@watermarkfalse}
2288 \newcommand\AMC@catalogMode{%
2289   \AMC@catalogtrue%

```

```

2290 \AMC@watermarkfalse\AMC@corretheadtrue%
2291 \AMC@correcttrue\AMC@ordretrue\AMC@shuffleGfalse%
2292 \AMC@fullGroupstrue%
2293 \def\AMC@intitleHead{\AMC@loc@catalog}\AMC@affichekeysttrue}
2294 \newcommand\AMC@keys@next{\AMC@keyslinefalse}
2295 \newcommand\AMC@keys@line{\AMC@keyslinefalse}
2296 \DeclareOptionX{catalog}{\AMC@catalogMode}
2297 \DeclareOptionX{keys}[next]{\csname AMC@keys@#1\endcsname{}}
2298 \DeclareOptionX{francais}{\def\AMC@lang@code{FR}\AMC@loc@FR}
2299 \DeclareOptionX{lang}{\def\AMC@lang@code{#1}\csname AMC@loc@#1\endcsname}
2300 \DeclareOptionX{versionA}{%
2301 \def\AMC@id@checkmax{31}\def\AMC@NCBetud{9}\def\AMC@NCBpage{4}%
2302 \def\AMC@NCBcheck{5}\setlength{\AMC@CBtaille}{4cm}%
2303 \def\AMC@premierecopie{100}}
2304 \DeclareOptionX{plain}{\AMC@plaintrue}
2305 \DeclareOptionX{nopage}{\AMC@pagelayoutfalse}
2306 \DeclareOptionX{postcorrect}{\AMC@postcorrecttrue}
2307 \DeclareOptionX{automarks}{\AMC@automarkstrue}
2308 \newif\ifAMCneeds@storebox\AMCneeds@storeboxfalse
2309 \DeclareOptionX{storebox}{\AMCneeds@storeboxtrue}
2310 \DeclareOptionX{pdfform}{\AMC@pdfformtrue}
2311 \DeclareOptionX{codedigit}{\AMC@codeID@{#1}}
2312 \newif\ifAMC@survey\AMC@surveyfalse
2313 \DeclareOptionX{survey}{\AMC@surveytrue}
2314 \ProcessOptionsX
2315 \ifAMCneeds@storebox
2316 \RequirePackage{storebox}\AtBeginDocument{}}}%
2317 \fi
2318 \ifAMC@pdfform
2319 \AMC@amclog{AUTOQCM[VAR:project:pdfform=1]^J}%
2320 \AMC@boxStyle{shape=form}%
2321 \RequirePackage{pageanchor=false}{hyperref}%
2322 \else%
2323 \AMC@amclog{AUTOQCM[VAR:project:pdfform=0]^J}%
2324 \fi
2325 \AtBeginDocument{%
2326 \ifAMCneeds@storebox%
2327 \let\AMC@new@savebox=\newstorebox%
2328 \let\AMC@save@box=\storebox%
2329 \let\AMC@use@box=\usestorebox%
2330 \fi%
2331 \AMC@new@savebox{\AMC@ovalbox@R}%
2332 \AMC@new@savebox{\AMC@ovalbox@RF}%
2333 \AMC@new@savebox{\AMC@ovalbox@O}%
2334 \AMC@new@savebox{\AMC@ovalbox@F}%
2335 \AMC@shapeprepare%
2336 }

```

4.20 Survey add-on

Some code and *tikz* settings to help handling surveys, see https://survey.codes/pdf/surveyamc_manual.pdf for more details. This survey add-on is originally written by Claudia Saalbach.

```

questionnaires (env.)
  auto (env.) 2337 \ifAMC@survey
question-auto (env.) 2338 \NewEnviron{Questionnaires}[1]{
  values (env.) 2339 \onecopy{#1}{
  values-auto (env.) 2340 \BODY
  variable-auto (env.) 2341 }
  \answer 2342 }
    2343 \NewEnviron{auto}[1]{
    2344 \csvreader[head to column names, separator=tab]{#1}{}{
    2345 \BODY
    2346 }
    2347 }
    2348 \NewEnviron{question-auto}[3]{
    2349 \csvreader[head to column names, separator=tab]{#1}{}{
    2350 \ifcsvstrcmp{#2}{#3}{\BODY \\\}
    2351 }
    2352 }
    2353 \newenvironment{values}{}{}
    2354 \NewEnviron{values-auto}[5]{
    2355 \csvreader[head to column names, separator=tab]{#1}{}{
    2356 \ifcsvstrcmp{#2}{#3}{
    2357 \ifcsvstrcmp{#4}{#5}{\BODY \\\}
    2358 }{}
    2359 }{}
    2360 }
    2361 }
    2362 \NewEnviron{variable-auto}[3]{
    2363 \foreach \x in {#3}{
    2364 \csvreader[head to column names, separator=tab]{#1}{}{
    2365 \ifcsvstrcmp{#2}{\x}{\BODY}{}
    2366 }
    2367 }
    2368 }
    2369 \newcommand{\answer}[5][\global\advance\AMCrep@count\one\relax%
    2370 \ifAMC@calibration\AMC@amclog{AUTOQCM[REP=\the\AMCrep@count:B]^^J}\fi%
    2371 \global\AMCune@bonnettrue%
    2372 \AMCload@@reponse{\une@rep{\ifAMC@correc\AMC@box{#1}{\AMC@checkbox}%
    2373 \else\AMC@box{#1}{\fi}{#2}{#3}{#4}{#5}}{\the\AMCrep@count}\ignorespaces}
    2374 \RequirePackage{tikz}
    2375 \usetikzlibrary{positioning, shapes, arrows, tikzmark, decorations.pathreplacing}
    2376 \tikzset{
    2377 checkbox-sc/.style={
    2378 right=of lab\thecsvrow
    2379 },
    2380 vallab-sc/.style={
    2381 text width=4cm,
    2382 align=left,
    2383 },
    2384 checkbox-mc/.style={
    2385 },
    2386 vallab-mc/.style={
    2387 above=of box\thecsvrow,
    2388 text width=1.4cm,

```

```

2389     align=center,
2390   },
2391   varlab-mc/.style={
2392     text width=4cm,
2393     align=left,
2394   },
2395   node distance= 0mm,
2396 }
2397 \fi

```

4.21 Package Errors

`\AMC@error@explain` Error to display if `\explain` command is used outside question like environments

```

2398 \def\AMC@error@explain{\PackageError{automultiplechoice}{
2399   Command \protect\explain\space can only be used inside\MessageBreak question like environments}{Some
2400 }}

```

4.22 Optional features

This package tries to see if optional packages `environ` and `etex` are loadable, and load them if possible. This behaviour can be cancelled by using `plain` option.

```

2401 \ifAMC@plain
2402 \else
2403   \IfFileExists{environ.sty}{\RequirePackage{environ}}{}
2404   \ifx\etexversion\@undefined
2405     \else
2406       \RequirePackage{etex}
2407   \fi
2408 \fi

```

`examcopy` (*env.*) Then, if `environ` package is loaded and defines command `\NewEnviron`, environment `examcopy` is defined.

Environment `{examcopy}[\langle n \rangle]` does the same as command `onecopy`: it encloses `LATEX` code which makes *one* exam copy. Optional argument $\langle n \rangle$ gives the number of desired copies – this can also be modified redefinig `\AMCNombreCopies`.

```

2409 \@ifpackageloaded{environ}{%
2410   \ifx\NewEnviron\undefined\PackageWarning{automultiplechoice}%
2411     {Package environ loaded but too old version:
2412       environnement examcopy/copieexamen will NOT be defined.}%
2413   \else\NewEnviron{examcopy}[1][5]{\onecopy{#1}{\BODY}}\fi}%
2414 {\PackageWarning{automultiplechoice}%
2415   {Package environ not loaded: environnement
2416     examcopy/copieexamen will NOT be defined.}}

```

4.23 Use with recent LuaTeX versions

In recent LuaTeX versions, the commands `pdfsavepos`, `pdflastxpos` and `pdflastypos` has been renamed, stripping the `pdf` part. The following code tries to detect this situation and make the bindings between the old and new command names.

```

2417 \ExplSyntaxOn
2418

```

```

2419 \cs_if_exist:NTF \pdfsavepos { } {
2420   \cs_if_exist:NTF \savepos { \cs_new_eq:NN \pdfsavepos \savepos } { }
2421 }
2422 \cs_if_exist:NTF \pdflastxpos { } {
2423   \cs_if_exist:NTF \lastxpos { \cs_new_eq:NN \pdflastxpos \lastxpos } { }
2424 }
2425 \cs_if_exist:NTF \pdflastypos { } {
2426   \cs_if_exist:NTF \lastypos { \cs_new_eq:NN \pdflastypos \lastypos } { }
2427 }

```

In some situations, the *page* dimensions are different from the *paper* dimensions. This must be taken into account when computing coordinates.

```

2428
2429 \cs_if_exist:NTF \pdfpagewidth { } {
2430   \cs_new_eq:NN \pdfpagewidth \paperwidth
2431 }
2432 \cs_if_exist:NTF \pdfpageheight { } {
2433   \cs_new_eq:NN \pdfpageheight \paperheight
2434 }
2435
2436 \ExplSyntaxOff

```

4.24 External control

`\SujetExterne` Some of the package options can be controlled defining `\xxxExterne` commands. For example, `\ScoringExterne` the following command will format the subject document, whatever options are used in the L^AT_EX file: `\CorrigeExterne`

`\CorrigeIndivExterne` pdf_{La}TeX '`\nonstopmode\def\SujetExterne{1}\def\NoWatermarkExterne{1}\input{mcq.tex}`'

`NoWatermarkExterne`

```

2437 \ifx\SujetExterne\undefined\else
2438 \message{***SUJET***^^J}
2439 \AMC@calibrationtrue\AMC@correcfalse\AMC@corretheadfalse\AMC@watermarkfalse
2440 \fi
2441 \ifx\ScoringExterne\undefined\else
2442 \message{***SCORING***^^J}
2443 \AMC@calibrationtrue\AMC@correcfalse\AMC@corretheadfalse\AMC@watermarkfalse\AMC@invisibletrue
2444 \fi
2445 \ifx\CorrigeExterne\undefined\else
2446 \message{***CORRIGE***^^J}
2447 \AMC@calibrationfalse\AMC@corretheadtrue\AMC@correcttrue\AMC@watermarkfalse
2448 \fi
2449 \ifx\CorrigeIndivExterne\undefined\else
2450 \message{***CORRIGE***^^J}
2451 \AMC@calibrationfalse\AMC@corretheadfalse\AMC@correcttrue\AMC@watermarkfalse
2452 \fi
2453 \ifx\CatalogExterne\undefined\else
2454 \message{***CATALOG***^^J}
2455 \AMC@catalogMode
2456 \fi
2457 \ifx\NoWatermarkExterne\undefined\else
2458 \AMC@watermarkfalse
2459 \fi
2460 \ifx\codeDigitExterne\undefined\else

```

```

2461 \AMCcodeID@{\codeDigitExterne}
2462 \fi

```

4.25 Page layout

The following code sets the correct page layout to have room for signs for scan analysis, and prepares watermark printing:

```

2463 \@ifpackageloaded{geometry}{\usepackage{geometry}}
2464 \ifAMC@pagelayout
2465   \ifAMC@correthead
2466     \geometry{hmargin=3cm,vmargin={1cm,1cm},includeheadfoot,headheight=1cm,footskip=1cm}
2467   \else
2468     \geometry{hmargin=3cm,headheight=2cm,headsep=.3cm,footskip=1cm,top=3.5cm,bottom=2.5cm}
2469   \fi
2470   \ifAMC@watermark
2471     \ifAMC@correthead\else
2472       \def\AMC@note{\begin{minipage}{0.65\linewidth}
2473         \AMC@LR{\textcolor{blue}{\AMC@loc@message}}
2474         \end{minipage}}
2475     }
2476   \fi
2477 \fi
2478 \fi

```

4.26 Initialisation

Initialisation of the check counter:

```

2479 \AMCid@check=\AMCid@checkmax\advance\AMCid@check\@ne

```

Telling outside if separate answer sheet, and boxes labelling, are requested:

```

2480 \ifAMC@ensemble\AMC@amclog{AUTOQCM[VAR:ensemble=1]^J}\fi
2481 \ifAMC@inside@box\AMC@amclog{AUTOQCM[VAR:insidebox=1]^J}\fi
2482 \ifAMC@outside@box\AMC@amclog{AUTOQCM[VAR:outsidebox=1]^J}\fi
2483 \ifAMC@postcorrect\AMC@amclog{AUTOQCM[VAR:postcorrect=1]^J}\fi

```

Preparing writing to .xy file :

```

2484 \ifAMC@calibration
2485 \newwrite\AMC@XYFILE%
2486 \immediate\openout\AMC@XYFILE\jobname.xy%
2487 \immediate\write\AMC@XYFILE{\string\version{\AMC@VERSION}}
2488 \immediate\write\AMC@XYFILE{\string\with{codedigit=squarebrackets}}
2489 \immediate\write\AMC@XYFILE{\string\with{version=\AMC@VERSION}}
2490 \immediate\write\AMC@XYFILE{\string\with{ensemble=\ifAMC@ensemble yes\else no\fi}}
2491 \immediate\write\AMC@XYFILE{\string\with{insidebox=\ifAMC@inside@box yes\else no\fi}}
2492 \immediate\write\AMC@XYFILE{\string\with{outsidebox=\ifAMC@outside@box yes\else no\fi}}
2493 \immediate\write\AMC@XYFILE{\string\with{postcorrect=\ifAMC@postcorrect yes\else no\fi}}
2494 \immediate\write\AMC@XYFILE{\string\with{extractonly=\ifAMC@extractOnly yes\else no\fi}}
2495 \immediate\write\AMC@XYFILE{\string\with{lang=\AMC@lang@code}}
2496 \ifx\AMCNombreCopies\undefined%
2497 \immediate\write\AMC@XYFILE{\string\with{ncopies=default}}}%
2498 \else%
2499 \immediate\write\AMC@XYFILE{\string\with{ncopies=\AMCNombreCopies}}}%
2500 \fi%
2501 \fi

```

Preparing writing to .cs file :

```
2502 \ifAMC@catalog%
2503 \newwrite\AMC@CSFILE%
2504 \immediate\openout\AMC@CSFILE\jobname.cs%
2505 \fi%
```

4.27 French command names

For backward compatibility, a lot of commands have their french counterpart:

```
2506 \let\reponses=\choices\let\endreponses=\endchoices
2507 \let\reponseshoriz=\choiceshoriz\let\endreponseshoriz=\endchoiceshoriz
2508 \let\reponsesperso=\choicescustom\let\endreponsesperso=\endchoicescustom
2509 \let\bonne=\correctchoice
2510 \let\mauvaise=\wrongchoice
2511 \let\bareme=\scoring
2512 \let\baremeDefaultM=\scoringDefaultM
2513 \let\baremeDefaultS=\scoringDefaultS
2514 \def\exemplaire{\AMC@loc@FR\onecopy}
2515 \@ifpackageloaded{environ}{%
2516   \let\copieexamen=\examcopy\let\endcopieexamen=\endexamcopy}{%
2517   \let\melangegroupe=\shufflegroup
2518   \let\restituegroupe=\insertgroup
2519   \let\alafin=\lastchoices
2520   \let\formulaire=\AMCform
2521   \let\AMCdebutFormulaire=\AMCformBegin
2522   \let\champnom=\namefield
2523   \let\choixIntervalles=\AMCIntervals
```

5 Outputs

In the .xy file, 1/⟨*n*⟩ means student sheet number 1 (there is only one “student sheet” for this document as we did not use \onecopy) and page number ⟨*n*⟩ inside this student sheet. Then, each instance of the \tracepos command shows *x* and *y* positions as arguments #2 and #3 (unit is sp, such that $65536 \times 72.27\text{sp}$ is one inch). One has to take min and max of the *x*-values to determine the left and right position of the box, and min and max values of *y*-values to determine top and bottom position of the box.

5.1 namefield command

Lines in the .xy file from a \namefield command:

```
\tracepos{0/34:nom}{0sp}{29866546sp}{square}
\tracepos{0/34:nom}{5873801sp}{0sp}{square}
\tracepos{0/34:nom}{15861297sp}{0sp}{square}
\tracepos{0/34:nom}{0sp}{26881368sp}{square}
```

5.2 AMCboxedchar command

Lines in the .xy file from a \AMCboxedchar command:

```
\tracepos{0/34:test}{22855914sp}{13919439sp}{square}
\tracepos{0/34:test}{23561334sp}{13214019sp}{square}
```

5.3 AMCcode command

Lines in the .xy file from a \AMCcode command. Here, `code.<n>:<q>,<v>` relates to digit number $\langle n \rangle$ from the right ($\langle n \rangle = 1$ for units, $\langle n \rangle = 2$ for tens, $\langle n \rangle = 3$ for hundreds and so on), question number $\langle q \rangle$ (\AMCcode uses a fake question; this number can be ignored), and value $\langle v \rangle - 1$ (box number $\langle v \rangle$ for the digit).

```
\tracepos{0/57:case:code[5]:16,1}{24875504sp}{39402246sp}{square}
\tracepos{0/57:case:code[5]:16,1}{25580924sp}{38696826sp}{square}
\boxchar{0/57:case:code[5]:16,1}{A}
\tracepos{0/57:case:code[5]:16,2}{24875504sp}{38288134sp}{square}
\tracepos{0/57:case:code[5]:16,2}{25580924sp}{37582714sp}{square}
\boxchar{0/57:case:code[5]:16,2}{B}
\tracepos{0/57:case:code[5]:16,3}{24875504sp}{37174022sp}{square}
\tracepos{0/57:case:code[5]:16,3}{25580924sp}{36468602sp}{square}
\boxchar{0/57:case:code[5]:16,3}{C}
\tracepos{0/57:case:code[5]:16,4}{24875504sp}{36059910sp}{square}
\tracepos{0/57:case:code[5]:16,4}{25580924sp}{35354490sp}{square}
\boxchar{0/57:case:code[5]:16,4}{D}
\tracepos{0/57:case:code[4]:17,1}{26540303sp}{41630470sp}{square}
\tracepos{0/57:case:code[4]:17,1}{27245723sp}{40925050sp}{square}
\boxchar{0/57:case:code[4]:17,1}{0}
\tracepos{0/57:case:code[4]:17,2}{26540303sp}{40516358sp}{square}
\tracepos{0/57:case:code[4]:17,2}{27245723sp}{39810938sp}{square}
\boxchar{0/57:case:code[4]:17,2}{1}
\tracepos{0/57:case:code[4]:17,3}{26540303sp}{39402246sp}{square}
\tracepos{0/57:case:code[4]:17,3}{27245723sp}{38696826sp}{square}
\boxchar{0/57:case:code[4]:17,3}{2}
\tracepos{0/57:case:code[4]:17,4}{26540303sp}{38288134sp}{square}
\tracepos{0/57:case:code[4]:17,4}{27245723sp}{37582714sp}{square}
\boxchar{0/57:case:code[4]:17,4}{3}
\tracepos{0/57:case:code[4]:17,5}{26540303sp}{37174022sp}{square}
\tracepos{0/57:case:code[4]:17,5}{27245723sp}{36468602sp}{square}
\boxchar{0/57:case:code[4]:17,5}{4}
\tracepos{0/57:case:code[4]:17,6}{26540303sp}{36059910sp}{square}
\tracepos{0/57:case:code[4]:17,6}{27245723sp}{35354490sp}{square}
\boxchar{0/57:case:code[4]:17,6}{5}
\tracepos{0/57:case:code[3]:18,1}{28032160sp}{41630470sp}{square}
\tracepos{0/57:case:code[3]:18,1}{28737580sp}{40925050sp}{square}
\boxchar{0/57:case:code[3]:18,1}{0}
\tracepos{0/57:case:code[3]:18,2}{28032160sp}{40516358sp}{square}
\tracepos{0/57:case:code[3]:18,2}{28737580sp}{39810938sp}{square}
\boxchar{0/57:case:code[3]:18,2}{1}
\tracepos{0/57:case:code[3]:18,3}{28032160sp}{39402246sp}{square}
\tracepos{0/57:case:code[3]:18,3}{28737580sp}{38696826sp}{square}
\boxchar{0/57:case:code[3]:18,3}{2}
\tracepos{0/57:case:code[3]:18,4}{28032160sp}{38288134sp}{square}
\tracepos{0/57:case:code[3]:18,4}{28737580sp}{37582714sp}{square}
\boxchar{0/57:case:code[3]:18,4}{3}
\tracepos{0/57:case:code[3]:18,5}{28032160sp}{37174022sp}{square}
```



```

\tracepos{0/57:case:code[3]:18,5}{28737580sp}{36468602sp}{square}
\boxchar{0/57:case:code[3]:18,5}{4}
\tracepos{0/57:case:code[3]:18,6}{28032160sp}{36059910sp}{square}
\tracepos{0/57:case:code[3]:18,6}{28737580sp}{35354490sp}{square}
\boxchar{0/57:case:code[3]:18,6}{5}
\tracepos{0/57:case:code[2]:19,1}{29524017sp}{41630470sp}{square}
\tracepos{0/57:case:code[2]:19,1}{30229437sp}{40925050sp}{square}
\boxchar{0/57:case:code[2]:19,1}{0}
\tracepos{0/57:case:code[2]:19,2}{29524017sp}{40516358sp}{square}
\tracepos{0/57:case:code[2]:19,2}{30229437sp}{39810938sp}{square}
\boxchar{0/57:case:code[2]:19,2}{1}
\tracepos{0/57:case:code[2]:19,3}{29524017sp}{39402246sp}{square}
\tracepos{0/57:case:code[2]:19,3}{30229437sp}{38696826sp}{square}
\boxchar{0/57:case:code[2]:19,3}{2}
\tracepos{0/57:case:code[2]:19,4}{29524017sp}{38288134sp}{square}
\tracepos{0/57:case:code[2]:19,4}{30229437sp}{37582714sp}{square}
\boxchar{0/57:case:code[2]:19,4}{3}
\tracepos{0/57:case:code[2]:19,5}{29524017sp}{37174022sp}{square}
\tracepos{0/57:case:code[2]:19,5}{30229437sp}{36468602sp}{square}
\boxchar{0/57:case:code[2]:19,5}{4}
\tracepos{0/57:case:code[2]:19,6}{29524017sp}{36059910sp}{square}
\tracepos{0/57:case:code[2]:19,6}{30229437sp}{35354490sp}{square}
\boxchar{0/57:case:code[2]:19,6}{5}
\tracepos{0/57:case:code[1]:20,1}{31015874sp}{41630470sp}{square}
\tracepos{0/57:case:code[1]:20,1}{31721294sp}{40925050sp}{square}
\boxchar{0/57:case:code[1]:20,1}{0}
\tracepos{0/57:case:code[1]:20,2}{31015874sp}{40516358sp}{square}
\tracepos{0/57:case:code[1]:20,2}{31721294sp}{39810938sp}{square}
\boxchar{0/57:case:code[1]:20,2}{1}
\tracepos{0/57:case:code[1]:20,3}{31015874sp}{39402246sp}{square}
\tracepos{0/57:case:code[1]:20,3}{31721294sp}{38696826sp}{square}
\boxchar{0/57:case:code[1]:20,3}{2}
\tracepos{0/57:case:code[1]:20,4}{31015874sp}{38288134sp}{square}
\tracepos{0/57:case:code[1]:20,4}{31721294sp}{37582714sp}{square}
\boxchar{0/57:case:code[1]:20,4}{3}
\tracepos{0/57:case:code[1]:20,5}{31015874sp}{37174022sp}{square}
\tracepos{0/57:case:code[1]:20,5}{31721294sp}{36468602sp}{square}
\boxchar{0/57:case:code[1]:20,5}{4}
\tracepos{0/57:case:code[1]:20,6}{31015874sp}{36059910sp}{square}
\tracepos{0/57:case:code[1]:20,6}{31721294sp}{35354490sp}{square}
\boxchar{0/57:case:code[1]:20,6}{5}

```

type	English	French
command	<code>\namefield</code>	<code>\champnom</code>
environment	<code>choices</code>	<code>reponses</code>
environment	<code>choiceshoriz</code>	<code>reponseshoriz</code>
environment	<code>choicescustom</code>	<code>reponsesperso</code>
command	<code>\correctchoice</code>	<code>\bonne</code>
command	<code>\wrongchoice</code>	<code>\mauvaise</code>
command	<code>\lastchoices</code>	<code>\alafin</code>
command	<code>\AMCIntervals</code>	<code>\choixIntervalles</code>
command	<code>\scoring</code>	<code>\bareme</code>
command	<code>\scoringDefaultM</code>	<code>\baremeDefautM</code>
command	<code>\scoringDefaultS</code>	<code>\baremeDefautS</code>
command	<code>\onecopy</code>	<code>\exemplaire</code>
environment	<code>examcopy</code>	<code>copieexamen</code>
command	<code>\shufflegroup</code>	<code>\melangegroupe</code>
command	<code>\insertgroup</code>	<code>\restituegroupe</code>
command	<code>\AMCform</code>	<code>\formulaire</code>
command	<code>\AMCformBegin</code>	<code>\AMCdebutFormulaire</code>
option	<code>noshuffle</code>	<code>ordre</code>
option	<code>answers</code>	<code>correc</code>
option	<code>indivanswers</code>	<code>correcindiv</code>
option	<code>box</code>	<code>bloc</code>
option	<code>separateanswersheet</code>	<code>ensemble</code>
option	<code>digits</code>	<code>chiffres</code>

Table 1: French equivalent commands

Contents

1	Introduction	1
2	Samples	1
2.1	Standard layout	4
2.2	Separate answer sheet	5
2.3	Without markers	6
3	Usage	10
3.1	Package options	10
3.2	Questions and answers	11
3.3	Scoring	13
3.4	Groups of questions	14
3.5	Students identification	15
3.6	Separate answer sheet	16
3.7	Random computation questions	17
3.8	French command names	20
3.9	Customisation	20
3.9.1	Boxes	20
3.9.2	Codes	22
3.9.3	Answers	22
4	Implementation	22
4.1	Variables	23
4.2	Dimensions	25
4.3	Human readable sheet ID position	26
4.4	Localisation	27
4.4.1	English	27
4.4.2	Catalan	27
4.4.3	Dutch	28
4.4.4	French	28
4.4.5	German	28
4.4.6	Italian	29
4.4.7	Norwegian	29
4.4.8	Portuguese	29
4.4.9	Spanish	30
4.4.10	Japanese	30
4.4.11	Other languages	30
4.5	Interaction with other packages	30
4.5.1	cleveref	30
4.6	Random	31
4.6.1	Random pseudo-generator	31
4.6.2	Uniform random deviates	31
4.6.3	Tokens shuffling	31
4.7	Keys numbering	32
4.8	Boxes	32
4.8.1	Character logging	32
4.8.2	Position logging	33
4.8.3	Boxes to be checked by students	35

4.8.4	Scoring zones	40
4.8.5	Binary boxes	40
4.9	Checking Environment	42
4.10	Handling groups of questions	42
4.11	Questions	46
4.11.1	Managing answers	47
4.11.2	Separate answer sheet	48
4.11.3	Formatting answers	51
4.11.4	Score zones	52
4.11.5	Formatting questions	55
4.11.6	Explanations	56
4.12	Scoring	57
4.13	Numerical data	57
4.13.1	Codes	57
4.13.2	Numerical questions	60
4.13.3	Intervals	73
4.14	Open questions	74
4.15	Boxes with letters only	77
4.16	Page formatting	78
4.16.1	Watermark	78
4.16.2	Signs for scan analysis	78
4.17	Defining a single exam copy content	80
4.18	Pre-association	81
4.19	Package options	81
4.20	Survey add-on	83
4.21	Package Errors	84
4.22	Optional features	84
4.23	Use with recent LuaTeX versions	85
4.24	External control	85
4.25	Page layout	86
4.26	Initialisation	86
4.27	French command names	87
5	Outputs	88
5.1	namefield command	88
5.2	AMCboxedchar command	88
5.3	AMCcode command	88

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

Symbols			1389,	1391,	1392,	1796,	1797,	1799,
\"	147, 153	1393,	1394,	1397,	1800,	1801,	1802,
\@aucune	832, 836, 837	1404,	1405,	1406,	1803,	1804,	1805,
\@firstoftwo	658	1408,	1410,	1411,	1808,	1809,	1810,
\@ifstar	996, 997	1413,	1415,	1420,	1811,	1815,	1817,
\@secondoftwo	660	1421,	1423,	1425,	1819,	1822,	1827,
\@skiphyperreffalse	...	1165	1426,	1427,	1429,	1828,	1829,	1830,
\@skiphyperreftrue		1161, 1165	1435,	1440,	1452,	1831,	1832,	1834,
\@tempboxa	.	2124, 2128, 2129	1486,	1488,	1490,	1835,	1836,	1837,
\@tempdimb	2113, 2115	1492,	1494,	1497,	1841,	1842,	1844,
\@tempdimc	2114, 2115	1500,	1503,	1506,	1850,	1857,	1862,
_	1186	1509,	1512,	1515,	1864,	1865,	1871,
\~	188, 189, 194, 195	1518,	1521,	1530,	1880,	1882,	1883,
A			1532,	1540,	1544,	1884,	1885,	1889,
\aa	174	1546,	1558,	1559,	1890,	1891,	1895,
\alafin	21, 2519	1560,	1561,	1562,	1896,	1897,	1898,
\amc	...	859, 870, 872, 874,	1563,	1564,	1565,	1900,	1901,	1902,
		875, 877, 880, 881,	1568,	1571,	1575,	1915,	1917,	1923,
		883, 886, 887, 890,	1578,	1581,	1585,	1932,	1935,	1936,
		891, 892, 893, 895,	1588,	1592,	1595,	1942,	1943,	1944,
		897, 898, 900, 902,	1600,	1602,	1604,	1945,	1946,	1947,
		903, 905, 907, 908,	1611,	1613,	1616,	1948,	1950,	1951, 1954
		911, 912, 914, 915,	1625,	1626,	1627,	\AMC@addpages	2228, 2230, 2232	
		917, 918, 920, 921,	1628,	1630,	1632,	\AMC@affecte	278, 1178
		923, 924, 926, 929,	1635,	1640,	1641,	\AMC@amclog	17,
		930, 932, 934, 938,	1643,	1647,	1649,		279, 591, 985, 1044,	
		939, 940, 941, 1243,	1652,	1653,	1654,		1049, 1196, 1228,	
		1244, 1245, 1246,	1655,	1657,	1658,		1229, 1230, 1231,	
		1247, 1249, 1256,	1659,	1662,	1665,		1266, 1356, 1548,	
		1259, 1264, 1268,	1670,	1672,	1675,		1580, 1582, 1587,	
		1276, 1279, 1280,	1679,	1680,	1681,		1589, 1594, 1596,	
		1281, 1286, 1288,	1683,	1686,	1691,		1605, 1618, 1634,	
		1290, 1291, 1292,	1697,	1704,	1705,		1717, 1720, 1736,	
		1293, 1295, 1300,	1712,	1714,	1715,		1738, 1758, 1809,	
		1302, 1304, 1312,	1716,	1718,	1721,		1816, 1832, 1834,	
		1317, 1318, 1319,	1723,	1726,	1729,		1837, 1839, 1842,	
		1321, 1323, 1326,	1730,	1735,	1745,		1844, 1847, 1851,	
		1327, 1328, 1329,	1746,	1747,	1748,		1854, 1856, 1863,	
		1331, 1333, 1336,	1749,	1750,	1751,		1868, 1870, 1910,	
		1337, 1339, 1340,	1752,	1753,	1754,		2007, 2063, 2082,	
		1342, 1343, 1344,	1756,	1761,	1762,		2099, 2205, 2219,	
		1345, 1365, 1366,	1765,	1766,	1770,		2319, 2323, 2370,	
		1371, 1372, 1373,	1771,	1772,	1774,		2480, 2481, 2482, 2483	
		1374, 1375, 1376,	1775,	1777,	1778,	\AMC@answerBox	477
		1381, 1383, 1384,	1779,	1780,	1781,	\AMC@answerBox@	...	358,
		1385, 1386, 1387,	1783,	1784,	1787,		485, 532, 534, 550,	
			1789,	1794,	1795,		552, 618, 620, 628, 630	

\AMC@binaryBoxes	651	\AMC@keepmemoryfalse . .	2220	\AMC@logfile	17, 18, 19
\AMC@binaryCode . . .	601,	\AMC@keepmemorytrue . . .	986	\AMC@LR	21,
652, 2142, 2143, 2144		\AMC@keyBox@		389, 2116, 2161, 2162,	
\AMC@box	519, 1046,	548, 1267, 1551, 1554	2163, 2164, 2165, 2473	
1047, 1050, 2372, 2373		\AMC@keys@line	2295	\AMC@makeovalbox	
\AMC@boxcolor 376, 502, 2036		\AMC@keys@next	2294	. 412, 431, 432, 433, 434	
\AMC@boxcolor@		\AMC@lang@code		\AMC@mem@add	900,
. 376, 377, 378, 380,		. 2263, 2298, 2299, 2495		946, 953, 960, 967, 1351	
398, 407, 419, 423, 440		\AMC@loc@CA	104	\AMC@mem@add@ifneeded . .	
\AMC@boxeddown 390, 490, 501		\AMC@loc@catalog 98, 111,		857, 1192
\AMC@boxedheight		125, 138, 152, 166,		\AMC@mem@addsingle@ifneeded	
. 403, 417, 418, 420,		179, 191, 205, 217, 2293		. 949, 989, 991, 993, 995	
421, 424, 425, 469,		\AMC@loc@corrected		\AMC@mem@addvar	905
492, 496, 497, 509, 512		97, 110,	\AMC@mem@aid	924, 959
\AMC@boxedrule	395,	124, 137, 151, 165,		\AMC@mem@answer	
417, 418, 419, 488, 499		178, 190, 204, 216, 2138		956, 1019, 1026,
\AMC@boxedwidth		\AMC@loc@DE	145	1027, 1028, 1033, 1039	
. 406, 417, 418, 420,		\AMC@loc@draft	92, 105,	\AMC@mem@category	918,
421, 424, 425, 469,		119, 132, 146, 160,		952, 1927, 2071, 2107	
491, 496, 498, 509, 510		173, 186, 199, 212, 2111		\AMC@mem@clear	875, 2222
\AMC@catalogMode		\AMC@loc@ES	198	\AMC@mem@next	895, 951, 965
.	2288, 2296, 2455	\AMC@loc@explain 99, 112,		\AMC@mem@openQuestion . .	
\AMC@CBtaille 599, 2166, 2302		139, 153, 192, 218, 1223		963, 1191
\AMC@checkbox		\AMC@loc@FR	131, 2298, 2514	\AMC@mem@qidaffname 912, 966	
. 358, 379, 382, 432,		\AMC@loc@IT	159	\AMC@mem@show	939, 976, 985
434, 444, 450, 460,		\AMC@loc@JA	211	\AMC@mem@show@filter 940, 980	
618, 620, 1046, 1549,		\AMC@loc@message 93, 106,		\AMC@mn@leftmargin	
1569, 1581, 1585, 2372		120, 133, 147, 161,		. 1056, 1064, 1067, 1073	
\AMC@chiffres	1232	174, 187, 200, 213, 2473		\AMC@mn@rightmargin	
\AMC@crosschar	401, 504	\AMC@loc@namesurname 1057, 1065, 1068, 1071	
\AMC@crossrule 423, 489, 505		. 103, 116, 129, 143,		\AMC@mn@sep	1055, 1071, 1073
\AMC@CSFILE	287, 2503, 2504	157, 170, 183, 196, 209		\AMC@mn@test 1054, 1061, 1070	
\AMC@definitnumero	279, 283	\AMC@loc@NL	118	\AMC@NCBcheck 595, 2144, 2302	
\AMC@draw@crossfalse	381	\AMC@loc@NO	172	\AMC@NCBetud	595, 2142, 2301
\AMC@draw@crosstrue	383	\AMC@loc@none	100, 113,	\AMC@NCBpage	595, 2143, 2301
\AMC@error@explain		126, 140, 154, 167,		\AMC@new@savebox	
.	1223, 1225, 2398	180, 193, 206, 219, 832		359, 2327,
\AMC@fillcolor@		\AMC@loc@PT	185	2331, 2332, 2333, 2334	
. 379, 397, 398, 414, 419		\AMC@loc@q	96, 109,	\AMC@note	2139,
\AMC@fin@rep	819, 1004,	123, 136, 150, 164,		2140, 2174, 2184, 2472	
1008, 1012, 1015, 1018		177, 189, 203, 215, 1168		\AMC@numeric@alsocorrect	
\AMC@formBox	519	\AMC@loc@qf	95, 108,	1536,
\AMC@formBox@	519	122, 135, 149, 163,		1853, 1857, 1867, 1871	
\AMC@fullGroupsfalse	34	176, 188, 202, 214, 841		\AMC@numeric@keepas	
\AMC@fullGroupstrue		\AMC@loc@question	1534, 1846, 1847
.	2266, 2292	101, 114,	\AMC@numeric@scoreapprox	
\AMC@if@separate@question		127, 141, 155, 168,		1526, 1813, 1823
.	870,	181, 194, 207, 220, 226		\AMC@numeric@scoreexact	
945, 950, 958, 964,		\AMC@loc@questions	1524, 1812, 1818
1350, 1927, 2071, 2107		102, 115,	\AMC@numeric@scorewrong	
\AMC@imax	712, 724, 725, 726	128, 142, 156, 169,		1528, 1820, 1823
\AMC@intituleHead		182, 195, 208, 221, 226		\AMC@numerotation	
.	2138, 2155, 2293	\AMC@logchar	286, 387	278, 282, 283

\AMC@outside@sep .. 494, 500	\AMC@SR@count 233,	\AMC@sza@depth 1112, 1132, 1137
\AMC@oval@radius 419, 493, 510, 512	234, 236, 244, 248,	\AMC@sza@height 1112, 1131, 1136
\AMC@ovalbox@ 433, 447, 2333	251, 254, 255, 256, 257	\AMC@sza@init@margin .. 1122
\AMC@ovalbox@F 434, 445, 2334	\AMC@SR@time 245, 2279	\AMC@sza@init@margin . 1126
\AMC@ovalbox@R 430, 431, 453, 2331	\AMC@SR@advance 231, 238, 239	\AMC@sza@init@none 1114
\AMC@ovalbox@RF 432, 451, 2332	\AMC@SR@bit 238	\AMC@sza@init@question 1118
\AMC@pagepos 292, 2151	\AMC@SR@const .. 229, 233, 236	\AMC@sza@width 1112, 1130, 1135
\AMC@premierecopie 600, 2207, 2210, 2303	\AMC@SR@max 244, 272	\AMC@tempenv 656, 657
\AMC@prepare .. 281, 284, 285	\AMC@SR@nextByte 244	\AMC@tmpXY ... 341, 344, 346
\AMC@prepare@element ... 675, 683, 793	\AMC@SR@num 246, 247, 249,	\AMC@tracebox 292, 347, 439, 465,
\AMC@printformoutside@false 523	250, 254, 257, 272, 273	583, 585, 588, 1035, 2134
\AMC@printformoutside@true 525, 526	\AMC@SR@set 230, 242, 243, 245	\AMC@tracechar 333, 536, 554
\AMC@printkeyoutside@false 540	\AMC@SR@test 239, 250	\AMC@trapepos 293, 404, 410,
\AMC@printkeyoutside@true 542, 544	\AMC@SR@value 241	1021, 1024, 1184, 1192
\AMC@qaff 842, 1158, 1186, 1219	\AMC@stepQuestion 1158, 1177, 1216	\AMC@trapeposx 302, 322
\AMC@save@box 360, 415, 2328	\AMC@sti 259, 267, 271, 274, 275	\AMC@trapeposy 311, 321, 323
\AMC@setcolors@ 375, 396, 413, 438	\AMC@stil 260,	\AMC@unnumero 278
\AMC@shape@form 472	268, 269, 270, 272, 276	\AMC@use@box 361,
\AMC@shape@form@base 459, 473	\AMC@surveyfalse 2312	445, 447, 451, 453, 2329
\AMC@shape@form@ticked . 461, 463, 466	\AMC@surveytrue 2313	\AMC@VERSION 2487, 2489
\AMC@shape@none 476	\AMC@sz@box 1077,	\AMC@watertext .. 2111, 2122
\AMC@shape@oval 437	1079, 1081, 1084, 1127	\AMC@XYFILE 295, 304, 313,
\AMC@shape@square 394	\AMC@sz@callin 1089, 1094, 1102,	325, 330, 331, 335,
\AMC@shapename 292, 300, 309, 318, 495	1104, 1169, 1187, 1188	344, 345, 346, 2213,
\AMC@shapename@ 292, 390, 506	\AMC@sz@callin@question 1079	2254, 2259, 2260,
\AMC@shapeprepare 506, 514, 2335	\AMC@sz@callout 1088, 1093,	2485, 2486, 2487,
\AMC@shapeprepare@form 458	1097, 1099, 1181, 1182	2488, 2489, 2490,
\AMC@shapeprepare@none 475	\AMC@sz@callout@margin 1081	2491, 2492, 2493,
\AMC@shapeprepare@oval 429	\AMC@sz@callout@margin 1084	2494, 2495, 2497, 2499
\AMC@shapeprepare@square 393	\AMC@sz@depth 1077, 1087, 1092	\AMC@XYspecial 340, 343, 345, 346
\AMC@shuffletoks 259, 745, 748, 812	\AMC@sz@height 1077, 1086, 1091	\AMC@addpagesto 2228
\AMC@smashbox .. 363, 366,	\AMC@sz@init@margin .. 1083	\AMC@answer 1039, 1040, 2025, 2086
367, 368, 369, 370, 373	\AMC@sz@width 1077, 1085, 1090	\AMC@association 2252
\AMC@smashboxheight 364, 367, 368, 369, 372	\AMC@sza@box 1112, 1120, 1123	\AMC@beforeQuestion 1167, 1180, 1251
\AMC@smashcentered 365, 407, 408, 440, 441	\AMC@sza@callin 851, 852,	\AMC@beginAnswer 1011, 1040, 2024, 2085
\AMC@SR 228,	1134, 1139, 1147, 1149	\AMC@beginQuestion 1167, 1186,
230, 233, 234, 235,	\AMC@sza@callin@margin 1124	1199, 1205, 1219, 1250
236, 238, 240, 241, 2214	\AMC@sza@callin@margin 1128	\AMC@bin@begin 650
	\AMC@sza@callin@none .. 1116	\AMC@bin@did 605, 613, 616,
	\AMC@sza@callin@question 1120	618, 623, 626, 628, 634
	\AMC@sza@callout 847, 848,	\AMC@bin@digit 603, 636, 639, 645, 648
	1133, 1138, 1142, 1144	\AMC@bin@hsep 607, 610, 614, 624
	\AMC@sza@callout@margin 1123	
	\AMC@sza@callout@margin 1127	
	\AMC@sza@callout@none . 1115	
	\AMC@sza@callout@question 1119	

\AMCbin@id	604,	\AMCdump@reponses . .	812, 826	\AMCid@etudstart	
609, 617, 618, 627, 628		\AMCemptybox 1052, 1077, 1112		29, 2206, 2225	
\AMCbin@endigits		\AMCendAnswer		\AMCid@name	65, 564,
606, 608, 645, 648		1012, 1040, 2024, 2085		567, 569, 573, 575,	
\AMCbin@number		\AMCexponent 1476, 1887, 1899		909, 966, 1021, 1024,	
602, 635, 638, 640, 642		\AMCform	16, 857, 2520	1035, 1178, 1192,	
\AMCbin@one	612, 640	\AMCformAfterQuestion . .		1267, 1551, 1554, 1969	
\AMCbin@sequence . .	601,	840, 1192		\AMCid@quest	26,
635, 640, 641, 646, 647		\AMCformAnswer	839	330, 331, 564, 567,	
\AMCbin@style	611, 635	\AMCformAnswerA . . .	856, 960	569, 573, 575, 583,	
\AMCbin@zero . .	622, 641, 646	\AMCformatChoices		585, 588, 908, 966,	
\AMCbloc	1174	1348, 1928, 2072, 2108		1021, 1024, 1035,	
\AMCbo@help .	2075, 2076, 2089	\AMCformBeforeQuestion .		1178, 1179, 1184,	
\AMCboHide	2102, 2108	839, 845		1192, 1267, 1552,	
\AMCboOpts	2079	\AMCformBegin .	16, 857, 2521	1555, 1758, 2007, 2082	
\AMCboShow	2080, 2108	\AMCformFilter	978	\AMCIDBoxesA	2142, 2146
\AMCbotextGoto . .	2074, 2103	\AMCformHSpace 66, 855, 2086		\AMCIDBoxesABC . .	2145, 2168
\AMCboxColor	517, 2166	\AMCformQuestion	839	\AMCIDBoxesB	2143, 2147
\AMCboxDimensions .	518, 635	\AMCformQuestionA .	843, 967	\AMCIDBoxesC	2144, 2147
\AMCBoxedAnswers .	998, 2270	\AMCformQuestionN .	842, 850	\AMCids@height .	76, 87, 2167
\AMCBoxOnly	2074	\AMCformS	857	\AMCids@sidefalse . .	79, 81
\AMCboxOutsideLetter . .		\AMCformVSpace	66, 839	\AMCids@sidetrue	83
519, 2026, 2087		\AMCgroup@pre	741, 764	\AMCids@topfalse	79, 83
\AMCboxStyle		\AMCgrouploop@next	766, 777, 792	\AMCids@toptrue	81
20, 488, 2270, 2320		\AMCgrouploop@prep		\AMCids@width . .	75, 86, 2170
\AMCccerle	2130, 2133	752, 775, 790		\AMCidsPosition	73
\AMCchoiceLabel . . .	477, 558	\AMCgrouppre@cyclic . . .	735	\AMCidsVar	77
\AMCchoiceLabelFormat . .		\AMCgrouppre@fixed	697	\AMCidsVarN	77, 78
391, 477		\AMCgrouppre@withoutreplacement		\AMCif@env . .	655, 1223, 1225
\AMCcleardoublepage 16, 2237		713		\AMCifcategory	941
\AMCcode	1344	\AMCgrouppre@withreplacement		\AMCinterBquest . . .	71, 1192
\AMCcodeGrid	15, 1232	704		\AMCinterBrep	66, 1025
\AMCcodeGridInt . . .	15, 1232	\AMChorizAnswerSep		\AMCinterIquest . . .	70, 1192
\AMCcodeH	1345	1029, 1030, 1038		\AMCinterIrep	66, 1002
\AMCcodeHspace		\AMChorizBoxSep		\AMCIntervalFormat 1939, 1950	
1233, 1271, 1306		1031, 1032, 1035, 1037		\AMCIntervals 17, 1939, 2523	
\AMCcodeID	1238, 1290	\AMCid@check		\AMClabel	2245, 2250
\AMCcodeID@@		27, 327, 2144, 2149,		\AMCload@@reponse .	823,
1237, 1240, 2311, 2461		2150, 2167, 2171, 2479		825, 1046, 1050, 2372	
\AMCcodeID@dot	1236	\AMCid@checkmax		\AMCload@counter	
\AMCcodeID@squarebrackets		595, 2150, 2301, 2479		25, 801, 802, 803,	
1235		\AMCid@etud	28,	804, 807, 808, 812,	
\AMCcodeVspace		289, 297, 306, 315,		815, 816, 817, 818, 821	
1234, 1269, 1305, 1308		327, 330, 331, 336,		\AMCload@reponse . .	806, 825
\AMCcompleteMulti . .	12, 63	352, 473, 2141, 2142,		\AMClocalized	91
\AMCcurrentenv 654, 657, 1176		2167, 2171, 2179,		\AMCloop@k	718, 724,
\AMCdebutFormulaire 21, 2521		2206, 2207, 2209,		728, 730, 751, 759, 768	
\AMCdecimalPoint		2214, 2219, 2224,		\AMCmarginNote	
1474, 1644, 1676		2225, 2244, 2245, 2254		1058, 1084, 1127	
\AMCdefault@groupmode . .		\AMCid@etudfin	30,	\AMCmem@elt@cat 915, 927, 931	
672, 686, 687		2208, 2209, 2210, 2224		\AMCmessage . .	17, 1179, 1192
\AMCdontAnnotate .	330, 2040			\AMCncol@Background	
\AMCdontScan	330, 2039			1484, 1879	

\AMCncol@Border .	1480, 1879	\AMCopen@Hspace . .	1972, 1973, 2027, 2032, 2043	\AMCscoreZone	579, 1052
\AMCncol@BorderWidth	1482, 1878	\AMCopen@LineHeight	1976, 1977, 1997	\AMCscoreZoneAnswerSheet	1052
\AMCneeds@storeboxfalse	2308	\AMCopen@Lines	1978, 1979, 2002	\AMCsection	988
\AMCneeds@storeboxtrue	2309	\AMCopen@lines	1995	\AMCsectionNumbered	988, 996
\AMCnobloc	1173, 1255	\AMCopen@lineuptext	1965, 1988, 2012, 2015, 2018	\AMCsectionStar	992, 996
\AMCnoCompleteMulti	12, 64, 2023	\AMCopen@question	1964, 1969, 2031, 2032	\AMCsetFoot	2140
\AMCNombreCopies	2203, 2204, 2496, 2499	\AMCopen@width	1974, 1975, 1996	\AMCsetScoreZone	1110, 1111, 1157
\AMCnoScoreZone	1157, 1252	\AMCopenHide	2066, 2072	\AMCsetScoreZoneAnswerSheet	1155, 1156, 1157
\AMCncontextGoto	1465, 1919	\AMCopenOpts	1994	\AMCshowSignificantDigits	1413
\AMCncontextSign	1472, 1695, 1696	\AMCopenShow	2005, 2072	\AMCsignificantDigits	1408
\AMCncontextVHead	1466, 1648	\AMCotextGoto	1957, 2067	\AMCstudentlabel	2245, 2246, 2247, 2248
\AMCnum@copies	31, 2203, 2204, 2205, 2208	\AMCotextReserved	1958, 1968, 2042, 2046, 2048	\AMCStudentNumber	2141
\AMCnum@Questions	813, 815	\AMCoutsideLabelFormat	519	\AMCstudentslistfile	2257
\AMCnumeric@Hspace	1467, 1479, 1606, 1608, 1644, 1663, 1899	\AMCpageref	2248	\AMCsubjectPageTag	2178, 2183
\AMCnumeric@Vspace	1468, 1478, 1579, 1586, 1593, 1620, 1636, 1650, 1684, 1696, 1886, 1888	\AMCpostOquest	72, 2059	\AMCsubsection	988
\AMCnumericChoices	18, 1348	\AMCqlabel	2249	\AMCsubsectionStar	994, 997
\AMCnumericChoicesPlain	1926, 1933	\AMCquestionaff	1158	\AMCsw@p	259
\AMCnumericHide	1923, 1928	\AMCquestionNumberfalse	1253	\AMCsw@p@	261, 263, 265
\AMCnumericOpts	1544	\AMCquestionNumbertrue	45	\AMCsz@loggedfalse	579
\AMCnumericShow	1915, 1928	\AMCrandomseed	242	\AMCsz@loggedtrue	592
\AMCnumero	1159, 2218	\AMCref	2245, 2245	\AMCtext	90
\AMCocol@Background	1959, 1966, 2030	\AMCrep@count	827, 829, 831	\AMCtok@ik	718, 719, 721, 726, 727, 728, 729, 730, 750, 758, 771, 778, 794
\AMCocol@BoxFrameRule	1960, 1984, 2030	\AMCrep@bloc	1001, 1019	\AMCtok@k	663, 678, 679, 680, 684, 794
\AMCocol@Foreground	1962, 1967, 2035, 2036, 2045, 2048	\AMCrep@count	564, 567, 569, 573, 575, 800, 809, 829, 831, 835, 921, 959, 1000, 1006, 1010, 1014, 1017, 1021, 1024, 1035, 1043, 1044, 1047, 1048, 1049, 1050, 1261, 1265, 1266, 1267, 1349, 1351, 1547, 1548, 1552, 1555, 2369, 2370, 2373	\AMCtok@max	664
\AMCocol@FrameRule	1961, 1985, 2056	\AMCrep@fini	823, 826, 830, 838	\AMCtok@size	665, 753, 754, 755, 756, 764, 772, 779, 795
\AMCOpen	1957	\AMCrep@init	819, 1003, 1006, 1010, 1014, 1017	\AMCw@termark	2110, 2152
\AMCopen@answer	1963, 1970, 1998, 2014	\AMCrep@itemize	1000, 1019	\AMCw@terprint	2110, 2152
\AMCopen@boxframerule	1982, 1983, 2029	\AMCrep@ligne	1006, 1019	amcxyfile (env.)	340
\AMCopen@boxmargin	1980, 1981, 2028	\AMCrep@o	820, 822	\answer	288, 1043, 2337
\AMCopen@contentcommand	1971, 2057	\AMCrep@perso	1010, 1019	answers (option)	10
\AMCopen@framerule	1986, 1987, 2055	\AMCrep@r	824	asbox (option)	10
		\AMCrep@tikz	1014, 1019	\association	2254
		\AMCrep@tikzmat	1017, 1019	auto (env.)	2337
		\AMCrien@deux	806, 823	automarks (option)	11

B

\bareme	21, 2511
\baremeDefautM	21, 2512
\baremeDefautS	21, 2513
\bf	1475
bloc (option)	21

<code>\bonne</code>	21, 2509				
<code>\bool</code> 933, 1246, 1247, 1268,					
1279, 1280, 1293,					
1295, 1304, 1602,					
1613, 1628, 1647,					
1652, 1693, 1704,					
1716, 1734, 1735,					
1761, 1765, 1774,					
1815, 1850, 1862, 1880					
<code>box (option)</code>	10				
<code>\boxchar</code>	336				
<code>\boxput</code>	6, 400, 439				
C					
<code>\c</code>	938				
<code>calibration (option)</code> . .	5, 10				
<code>catalog (option)</code>	10				
<code>\CatalogExterne</code>	2453				
<code>\champnom</code>	21, 2522				
<code>\char</code>	1368				
<code>\CheckBox</code>	466				
<code>chiffres (option)</code>	21				
<code>\choices</code>	2506				
<code>choices (env.)</code>	12, 998				
<code>\choicescustom</code>	2508				
<code>choicescustom (env.)</code> .	12, 998				
<code>\choiceshoriz</code>	2507				
<code>choiceshoriz (env.)</code> . .	12, 998				
<code>\choixIntervalles</code> .	21, 2523				
<code>\cleargroup</code>	14, 784				
<code>\clist</code> . . 1243, 1256, 1289,					
1318, 1327, 1328,					
1422, 1425, 1436,					
1437, 1641, 1642,					
1672, 1673, 1747, 1748					
<code>\codeDigitExterne</code> 2460, 2461					
<code>completemulti (option)</code> . .	10				
<code>\coordinate</code>	1060				
<code>\copieexamen</code>	2516				
<code>copieexamen (env.)</code>	21				
<code>\copygroup</code>	14, 784				
<code>\copygroupfrom</code>	14, 784				
<code>correc (option)</code>	21				
<code>correcindiv (option)</code>	21				
<code>\correctchoice</code>					
13, 837, 1043, 1949, 2509					
<code>\CorrigeExterne</code>	2437				
<code>\CorrigeIndivExterne</code> . .	2437				
<code>\crefalias</code>	225				
<code>\crefname</code>	226				
<code>\cs</code>	870, 874,				
875, 877, 880, 883,					
886, 890, 895, 897,					
900, 902, 905, 907,					
911, 912, 914, 917,					
918, 920, 923, 924,					
926, 929, 938, 939,					
940, 941, 1249, 1259,					
1264, 1286, 1317,					
1321, 1326, 1331,					
1336, 1339, 1342,					
1343, 1344, 1345,					
1363, 1371, 1381,					
1384, 1389, 1393,					
1405, 1408, 1410,					
1413, 1415, 1421,					
1435, 1440, 1452,					
1540, 1544, 1546,					
1560, 1575, 1600,					
1611, 1626, 1640,					
1670, 1691, 1712,					
1756, 1915, 1917,					
1923, 1932, 1935,					
1936, 1944, 1954,					
2419, 2420, 2422,					
2423, 2425, 2426,					
2429, 2430, 2432, 2433					
<code>\csvreader</code>					
. 2344, 2349, 2355, 2364					
D					
<code>\define@boolkey</code> 503, 1989,					
1990, 1991, 1992, 2077					
<code>\define@choicekey</code>					
. 77, 495, 1095, 1140					
<code>digits (option)</code>	10				
<code>\ding</code>	467				
<code>\dontannotate</code>	331				
<code>\dontscan</code>	330				
<code>\dotfill</code>	355, 2000, 2016				
<code>\draw</code>	419, 423, 1071, 1073				
E					
<code>\element</code>	14, 663				
<code>\endchoices</code>	2506				
<code>\endchoicescustom</code>	2508				
<code>\endchoiceshoriz</code>	2507				
<code>\endcopieexamen</code>	2516				
<code>\endexamcopy</code>	2516				
<code>\endreponses</code>	2506				
<code>\endreponseshoriz</code>	2507				
<code>\endreponsesperso</code>	2508				
<code>ensemble (option)</code>	21				
<code>environments:</code>					
<code>amcxyfile</code>	340				
<code>auto</code>	2337				
<code>choices</code>	12, 998				
<code>choicescustom</code>	12, 998				
<code>choiceshoriz</code>	12, 998				
<code>copieexamen</code>	21				
<code>examcopy</code>	2409				
<code>question</code>	11, 1172				
<code>question-auto</code>	2337				
<code>questionmult</code>	11, 1172				
<code>Questionnaires</code>	2337				
<code>questionouverte</code>	1172				
<code>reponses</code>	21				
<code>reponseshoriz</code>	21				
<code>reponsesperso</code>	21				
<code>tikz-multi</code>	998				
<code>tikz-single</code>	998				
<code>values</code>	2337				
<code>values-auto</code>	2337				
<code>variable-auto</code>	2337				
<code>variable-multi</code>	1172				
<code>variable-single</code>	1172				
<code>\evensidemargin</code> .	1065, 1067				
<code>\examcopy</code>	2516				
<code>examcopy (env.)</code>	2409				
<code>\exemplaire</code>	21, 2514				
<code>\exemplairepair</code>	2244				
<code>\explain</code>	1221, 2399				
<code>\ExplSyntaxOff</code>					
. 943, 1347, 1464,					
1925, 1938, 1956, 2436					
<code>\ExplSyntaxOn</code>					
. 857, 1241, 1361,					
1469, 1930, 1940, 2417					
F					
<code>\fancypagestyle</code>					
. 2154, 2159, 2181, 2188					
<code>\fbox</code>	2179				
<code>\footrulewidth</code>					
. 2157, 2176, 2186, 2191					
<code>\foreach</code>	2363				
<code>\formulaire</code>	21, 2520				
<code>\fp</code>	1375, 1383,				
1385, 1387, 1391,					
1396, 1398, 1400,					
1404, 1411, 1416,					
1423, 1441, 1444,					
1745, 1746, 1770,					
1771, 1780, 1808,					
1809, 1834, 1942,					
1943, 1945, 1946,					
1947, 1948, 1950, 1951					
<code>francais (option)</code>	10				
<code>fullgroups (option)</code>	11				
G					
<code>\group</code>	1367, 1379				

H		
\he@dbas . . .	2136, 2161, 2162	
\he@dhaut	2137, 2165	
\he@dtaille . .	2135, 2136, 2137	
\hfuzz	369	
\ht	367, 1053	
I		
\ifAMC@affichekeys	36, 1185, 1186	
\ifAMC@asqbloc . .	42, 840, 846	
\ifAMC@automarks	60, 972, 2217, 2233, 2240	
\ifAMC@calibration	46, 294, 303, 312, 325, 330, 331, 334, 1044, 1049, 1179, 1195, 1228, 1229, 1230, 1231, 1266, 2213, 2219, 2253, 2258, 2370, 2484	
\ifAMC@catalog . .	47, 386, 2502	
\ifAMC@correc	38, 378, 1046, 1550, 1998, 2014, 2372	
\ifAMC@correthead	35, 1222, 2152, 2195, 2210, 2465, 2471	
\ifAMC@draw@cross	362, 401, 422	
\ifAMC@ensemble	54, 524, 541, 562, 581, 860, 972, 975, 979, 984, 1186, 1354, 1757, 1908, 1909, 2006, 2011, 2025, 2031, 2062, 2081, 2086, 2089, 2098, 2217, 2480, 2490	
\ifAMC@extractOnly	40, 1876, 2494	
\ifAMC@fullGroups . .	34, 754	
\ifAMC@inside@box	52, 544, 572, 2026, 2087, 2481, 2491	
\ifAMC@inside@digit . .	55, 478	
\ifAMC@invisible . . .	61, 292	
\ifAMC@keepmemory . .	982, 2222	
\ifAMC@keyslines . .	37, 1185, 1186	
\ifAMC@ordre	32, 820	
\ifAMC@outside@box	53, 524, 542, 2482, 2492	
\ifAMC@pagelayout	58, 2149, 2194, 2464	
\ifAMC@pdfform	62, 350, 2211, 2226, 2318	
\ifAMC@plain	48, 2401	
\ifAMC@postcorrect	59, 837, 2483, 2493	
\ifAMC@printformoutside	522, 531	
\ifAMC@printformoutside@	521, 528	
\ifAMC@printkeyoutside	539, 549	
\ifAMC@printkeyoutside@	538, 546	
\ifAMC@qbloc	41, 1167, 1184, 1192, 1218, 1220, 1920, 2068, 2104	
\ifAMC@rbloc	43, 1001, 1004	
\ifAMC@shuffleG	33, 745, 748	
\ifAMC@survey	2312, 2337	
\ifAMC@textPos	39, 1021, 1024, 1034, 1184, 1192	
\ifAMC@watermark	51, 2152, 2470	
\ifAMC@zoneformulaire	57, 526, 563, 861	
\ifAMC@complete@multi	44, 834	
\ifAMC@formulaire@dedans	56, 525, 566, 582, 1757, 1909, 2006, 2062, 2081, 2098	
\ifAMC@ids@side	74, 2170	
\ifAMC@ids@top	73, 2167	
\ifAMC@needs@storebox	2308, 2315, 2326	
\ifAMC@questionNumber	45, 1165	
\ifAMC@sz@logged	579, 590	
\ifAMC@type@multi	50, 834	
\ifAMC@cune@bonne	49, 836	
\ifcase	78	
\ifcsname	1096, 1101, 1106, 1141, 1146, 1151	
\ifcsvstrcmp	2350, 2356, 2357, 2365	
\ifdim	1070	
\ifKV@AMC@BoxOnly@ordered	2090	
\ifKV@AMC@dim@cross	382, 397, 414	
\ifKV@AMC@Open@annotate	2040	
\ifKV@AMC@Open@dots	1999	
\ifKV@AMC@Open@lineup	2010, 2052	
\ifKV@AMC@Open@scan	2039	
indivanswers (option)	6, 10	
init (option)	10	
\InputIfFileExists	15	
\insertgroup	14, 744, 2518	
\insertgroupfrom	14, 744	
insidebox (option)	10	
\int	872, 874, 878, 884, 891, 930, 1245, 1256, 1290, 1312, 1376, 1392, 1420, 1423, 1425, 1426, 1427, 1429, 1442, 1445, 1447, 1453, 1454, 1456, 1457, 1459, 1558, 1561, 1563, 1564, 1565, 1567, 1576, 1601, 1612, 1619, 1625, 1627, 1629, 1635, 1641, 1643, 1648, 1654, 1658, 1662, 1665, 1672, 1674, 1680, 1683, 1686, 1714, 1715, 1718, 1721, 1723, 1726, 1729, 1730, 1749, 1750, 1751, 1754, 1762, 1765, 1766, 1772, 1777, 1779, 1783, 1796, 1797, 1802, 1810, 1811, 1817, 1819, 1822, 1829, 1836, 1837, 1841, 1842, 1844, 1857, 1864, 1865, 1871, 1885, 1898	
K		
\keys	1275, 1287, 1471, 1541, 1760, 1918	
keys (option)	10	
L		
\lastchoices	819, 2519	
\lastxpos	2423	
\lastypos	2426	
\linebreak	2021	
M		
\m@rque	2134, 2161, 2162, 2163, 2164	
\m@rqueCalage	2133, 2134	
\marginpar	1081, 1123	
\mauvaise	21, 2510	
\melangegroupe	21, 2517	

<code>\MessageBreak</code>	2399	<code>\or</code>	80, 82	<code>\section</code>	989, 993
<code>\multiSymbole</code> 1167 , 1194 , 1212		<code>ordre (option)</code>	21	<code>separateanswersheet (option)</code>	5, 10, 16
N					
<code>\namefield</code>	15, 347 , 2522	<code>outsidebox (option)</code>	10	<code>\seq</code>	1244, 1292, 1300, 1366, 1374, 1375, 1376
<code>\namefielddots</code>	348	P			
<code>\newbox</code>	363	<code>\PackageError</code>	648, 690, 761, 2398	<code>\setdefaultgroupmode</code>	686
<code>\newline</code>	1185	<code>\pageref</code>	2248	<code>\setgroupmode</code>	672, 686
<code>\newsavebox</code>	359	<code>pdfform (option)</code>	11	<code>\shuffle@it</code>	812 , 826
<code>\newstorebox</code>	2327	<code>pdfpageheight</code> 329 , 2432 , 2433		<code>\shufflegroup</code>	14, 710, 722, 744 , 2517
<code>\nobreak</code>	520, 2053	<code>pdfpagewidth</code> 329 , 2429 , 2430		<code>\shufflegroupslice</code>	727, 730, 747
<code>\node</code>	1026, 1027, 1208	<code>\pgfextractx</code>	1061	<code>\smash</code>	1998, 2014
<code>nopage (option)</code>	6, 11	<code>\pgfpointanchor</code>	1062	<code>\space</code>	2399
<code>noshuffle (option)</code>	10	<code>\pgfpointdiff</code>	1061	<code>\storebox</code>	2328
<code>noshufflegroups (option)</code>	10	<code>\pgfpointorigin</code>	1061	<code>storebox (option)</code>	11
<code>\nouveaugroupe</code>	663 , 785	<code>plain (option)</code>	11	<code>\str</code>	927
<code>nowatermark (option)</code>	4, 10	<code>postcorrect (option)</code>	11	<code>\strut</code>	1071, 1073
<code>\NoWatermarkExterne</code>	2437	<code>\prg</code>	859, 862, 864, 867, 1328, 1424, 1437	<code>\SujetExterne</code>	2437
O					
<code>\oddsidemargin</code>	1064, 1068	Q			
<code>\onecopy</code> 2202 , 2339 , 2413 , 2514		<code>\question</code>	1172	<code>\tex</code>	1369
options:					
<code>answers</code>	10	<code>question (env.)</code>	11, 1172	<code>\textasciicircum</code>	1477
<code>asbox</code>	10	<code>question-auto (env.)</code>	2337	<code>\TextField</code>	352
<code>automarks</code>	11	<code>\QuestionIndicative</code>	13, 1228 , 1260	<code>\textit</code>	99, 112, 139, 153, 192, 218
<code>bloc</code>	21	<code>questionmult (env.)</code>	11, 1172	<code>\textsc</code>	2155
<code>box</code>	10	<code>Questionnaires (env.)</code>	2337	<code>\textsf</code>	504
<code>calibration</code>	5, 10	<code>questionouverte (env.)</code>	1172	<code>\thecsvrow</code>	1026, 1027, 2378, 2387
<code>catalog</code>	10	R			
<code>chiffres</code>	21	<code>\raisebox</code>	1475	<code>tikz-multi (env.)</code>	998
<code>completemulti</code>	10	<code>\refstepcounter</code>	1165	<code>tikz-single (env.)</code>	998
<code>correc</code>	21	<code>\reponses</code>	2506	<code>\tikzset</code>	2376
<code>correcindiv</code>	21	<code>reponses (env.)</code>	21	<code>\times</code>	1477
<code>digits</code>	10	<code>\reponseshoriz</code>	2507	<code>\tl</code>	892, 893, 898, 903, 932, 934, 1363, 1365, 1372, 1373, 1559, 1562, 1568, 1571, 1713, 1724, 1725, 1728, 1732, 1733, 1740, 1752, 1753
<code>ensemble</code>	21	<code>reponseshoriz (env.)</code>	21	<code>\tracepos</code>	296, 305, 314
<code>francais</code>	10	<code>\reponsesperso</code>	2508	U	
<code>fullgroups</code>	11	<code>reponsesperso (env.)</code>	21	<code>\une@rep</code>	1000, 1001, 1006, 1010, 1014, 1017, 1046, 1050, 2372
<code>indivanswers</code>	6, 10	<code>\restituegroupe</code>	21, 2518	<code>\useasboundingbox</code>	417
<code>init</code>	10	<code>\rngstate</code>	2214	<code>\usebox</code>	361
<code>insidebox</code>	10	S			
<code>keys</code>	10	<code>\savebox</code>	360	<code>\usestorebox</code>	2329
<code>nopage</code>	6, 11	<code>\savepos</code>	2420	<code>\usetikzlibrary</code>	2375
<code>noshuffle</code>	10	<code>\sbox</code>	1053	V	
<code>noshufflegroups</code>	10	<code>\scoring</code>	13, 1200, 1206, 1228 , 2511	<code>values (env.)</code>	2337
<code>nowatermark</code>	4, 10	<code>\scoringDefaultM</code>	13, 1228 , 2512		
<code>ordre</code>	21	<code>\scoringDefaultS</code>	13, 1228 , 2513		
<code>outsidebox</code>	10	<code>\ScoringExterne</code>	2437		
<code>pdfform</code>	11				
<code>plain</code>	11				
<code>postcorrect</code>	11				
<code>separateanswersheet</code>	5, 10, 16				
<code>storebox</code>	11				

